


LIGHT TOWER



- LED light panels provide crisp, clean light
- Up to 10 hours of silent emission free operation



Rhino Equipment offers the perfect lighting solutions to tackle your applications. Trusted power generator packages, exceptional lamp performance, and flexible modular designs allow you to choose the model that best supports: construction sites, outdoor events, and industrial settings.

Rhino light towers are industrial heavy duty units that offer all the advantages of standard bulb or LED lighting. These towers feature reduced glare and light pollution with crisp, white light, along with the fuel savings that come from battery powered operation. We can customize the fuel tank of the portable generator such that it can operate continuously for 48 hours or more; depending on client requests.

Especifications

| Length mm (ft) | 2,993 (9.8) |
|-------------------------------|---|
| Width mm (ft) | 1,100 (3.6) |
| Height mm (ft) | 2,495 (8.1) |
| Mast Heigth(Fully Extended) m | (ft) 7.5 (24.6) |
| Net Weight kg (lb) | 740 (1,631) |
| Engine Brand | Kubota |
| Engine model | Z482-E4B-CHN1 |
| Frequency (Hz) | 60 |
| Speed (rpm) | 3,600 |
| Continuous Power kW (Hp) | 8.1 (10.8) |
| Number of Cylinders | 3 |
| Diesel Engine Type | 4 cycle, in line, watercooled diesel |
| Fuel Injection | Direct Injection |
| Engine Aspiration | Natural |
| Emission Level | NA |
| Alternator Brand | Italy Mecc alte |
| Alternator Model | S20FS-130 |
| Frequency (Hz) | 60 |
| Continuous Power kW (kVa) | 6 (7.5) |
| Alternator | Brushless & Single phase |
| Rating Voltage (V) | 220 |
| Alternator Insulation | Н |
| Fuel Tank Capacity L (gal) | 100 (26,4) |
| Fuel Tank Operating Hours | 50 Hours Approximately |
| Type of Lights | Metal halide Floodlight |
| Number & Power of Lights | 4x1000W |
| Mast Lifting & Extension | Manual Operation |
| Mast Rotation | 330° manual Operation |
| Light angle turning | Manual Operation |
| Base Support | Manual Operation |
| Acoustic Pressure | 65dB(A) at 7 meters away (23 ft away) |
| Trailer System | ngle axle, hexagonal rubber suspension, with inertia drum braking & parking brake, , telescopic prop stands, tire & rim 165/13", mudguard, stable towing, draw eye/towing coupling |

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.