



Hydraulic Hammers	Rhino 254SK		CAT H45ES		FURUKAWA FX35		FURUKAWA FX45		STANLEY MBF5		EPIROC SB152	
<b>General</b>												
Brand	Rhino Equipment		Caterpillar		Furukawa		Furukawa		Stanley		Epiroc	
Model	254SK		H45ES		Fx35		Fx45		MBF5		SB152	
<b>Weight</b>												
Equipment Class tons (lb)	2.5 - 4	(8,819-15,432)	1.5-3.2	(3,307-7,055)	1.5 - 4	(3,000-8,000)	2.5 - 5.5	(5,000-11,000)	2.2-3.5	(4,500-7,000)	1.9 - 4.5	(3,800-9,000)
Operational Weight Kg (lb)	150	(331)	250	(551)	157	(346)	208	(459)	N/P	N/P	140	(309)
Weight of the Main Body Kg (lb)	86	(190)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
<b>Dimensions</b>												
Height (Including Tool) mm (ft)	1,342	(4.4)	N/P	N/P	N/P	N/P	N/P	N/P	N/A	N/A	N/P	N/P
Tool Diameter mm (in)	53	(2.1)	48	(1.9)	N/P	N/P	N/P	N/P	70	(2.8)	50	(2.0)
Hose Diameter mm (inch)	13	(0.5)	N/P	N/P	N/P	N/P	N/P	N/P	19	(0.7)	N/P	N/P
<b>Hydraulics</b>												
Operating Pressure bar (psi)	90-120	(1,305-1,740)	170	(2,466)	120-160	(1,740-2,320)	120-160	(1,740-2,320)	100-140	(1,500-2,000)	100-150	(1,450-2,175)
Flow Rate l/min (gpm)	25-50	(7-11)	25	(7)	24-52	(6-11)	30-60	(6-11)	38-83	(10-22)	25-45	(7-12)
Impact Rate (bpm)	600-1,100		780-1,800		600-1,300		600-1,100		650-1,550		850-1,900	
Impact Energy Class J (ft-lb)	320	(236)	400	(295)	N/P	N/P	N/P	N/P	750	(553)	N/P	N/P
Equipment specifications and images may change without notice from Rhino Equipment Group Inc.												
Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.												