





| Hydraulic Hammers | Rhino 3255EX | | CAT H160E S | | EPIROC HB3100 | | STANLEY MBX458 | |
|---------------------------------|-----------------|------------------|-------------|------------------|---------------|------------------|----------------|-----------------|
| nyuraunc nammers | | | | | | | | |
| General | | | | | | | | |
| Brand | Rhino Equipment | | Caterpillar | | Epiroc | | Stanley | |
| Model | 3255EX | | H160E S | | HB3100 | | MBX458 | |
| Weight | | | | | | | | |
| Equipment Class tons (lb) | 32-55 | (77,162-110,231) | 32-55 | (70,548-121,254) | 32-52 | (70,548-114,640) | 35-50 | (70,400-99,000) |
| Operational Weight Kg (lb) | 3,020 | (6,658) | 3,530 | (7,782) | 3,100 | (6,834) | 2,890 | (6,371) |
| Weight of the Main Body Kg (lb) | 1,400 | (3,086) | N/P | N/P | N/P | N/P | N/P | N/P |
| Dimensions | | | | | | | | |
| Height (Including Tool) mm (ft) | 2,740 | (9.0) | N/P | N/P | N/P | N/P | N/P | N/P |
| Tool Diameter mm (in) | 160 | (6.3) | 160 | (6.3) | 160 | (6.3) | 160 | (6.3) |
| Hose Diameter mm (inch) | 1 | (0.0) | N/P | N/P | N/P | N/P | N/P | N/P |
| Hydraulics | | | | | | | | |
| Operating Pressure bar (psi) | 160-180 | (2,321-2,611) | 160 | (2,321) | 160-180 | (2,320-2,610) | 160-180 | (2,321-2,611) |
| Flow Rate I/min (gpm) | 190-250 | (50-65) | 220-300 | (58-79) | 210-270 | (56-71) | 190-250 | (50-66) |
| Impact Rate (bpm) | 250-400 | | 400-505 | | 280-560 | | N/P | |
| Impact Engergy Class J (ft-lb) | 10,000 | (7,376) | 11,524 | (8,500) | N/P | N/P | 11,300 | (8,335) |

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.