



Hydraulic Hammers	Rhino 47SK		Caterpillar H65E		FURUKAWA FX55		STANLEY MB556		EPIROC SB302	
General										
Brand	Rhino Equipment		Caterpillar		Everdigm		STANLEY		EPIROC	
Model	47SK		H65E		FX55		MB556		SB302	
Weight										
Equipment Class tons (lb)	4-7	(8,819-15,432)	3-9	(6,614-19,842)	4.4 - 7.7	(8,800-15,400)	2.2-5	(4,500-10,000)	4.5 - 9	(9,000-18,000)
Operational Weight Kg (lb)	275	(606)	305	(672)	280	(617)	300	(661)	300	(661)
Weight of the Main Body Kg (lb)	151	(333)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Dimensions										
Height (Including Tool) mm (ft)	1,600	(5.2)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Tool Diameter mm (in)	68	(2.7)	68	(2.7)	N/P	N/P	69	(2.7)	80	(3.1)
Hose Diameter mm (inch)	13	(0.5)	N/P	N/P	12	(0.5)	N/P	N/P	N/P	N/P
Hydraulics										
Operating Pressure bar (psi)	95-130	(1,565-1,991)	165	(2,393)	120-160	(1,740-2,320)	110-138	(1,600-2,000)	100-150	(1,450-2,176)
Flow Rate l/min (gpm)	30-45	(8-12)	40-115	(10-30)	40-72	(10-19)	45-83	(12-22)	50-80	(13-21)
Impact Rate (bpm)	500-900		720-1,740		500-1,100		590-1,100		600-1,400	
Impact Energy Class J (ft-lb)	690	(509)	1,085	(800)	N/P	N/P	1,000	(738)	N/P	N/P
Equipment specifications and images may change without notice from Rhino Equipment Group Inc.										
Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.										