



Excavator	Rhino REX210		Komatsu PC200LC-8		Caterpillar 320GC		John Deere 210G LC		Volvo EC210D		Case CX210C		JCB JS220	
<b>General</b>	Rhino Equipment		Komatsu		Caterpillar		John Deere		Volvo		Case		JCB	
Brand	Rhino Equipment		Komatsu		Caterpillar		John Deere		Volvo		Case		JCB	
Model	REX210		PC200LC-8		320GC		210G LC		EC210D		CX210C		JS220	
Arm Selection m (ft)	3.0	(9.8)	2.5	(8.2)	N/P	N/P	2.4	(7.9)	2.5	(8.2)	2.4	(7.9)	N/P	
<b>Weight</b>	20,600		22,000		21,900		22,910		21,890		21,400		22,550	
Operating Weight kg (lb)	20,600	(45,415)	22,000	(48,502)	21,900	(48,281)	22,910	(50,508)	21,890	(48,259)	21,400	(47,179)	22,550	(49,714)
Counterweight Mass kg (lb)	4,450	(9,811)	3,730	(8,223)	4,200	(9,259)	4,250	(9,370)	4,200	(9,259)	4,250	(9,370)	N/P	N/P
Ground Pressure Kpa (psi)	49	(7.1)	38	(5.5)	N/P	N/P	49	(7.1)	31	(4.5)	34	(4.9)	N/A	N/A
<b>Engine</b>	CUMMINS (RHINO)		KOMATSU		CAT		JOHN DEERE		VOLVO		ISUZU		ISUZU	
Engine Make (optional)	CUMMINS (RHINO)		KOMATSU		CAT		JOHN DEERE		VOLVO		ISUZU		ISUZU	
Engine Model	6BT5.9-C		SAA6D107E-1		C4.4 Acert		PowerTech		D5E		GI-4HK1X		BB-6BGIT	
Net Horsepower kW (hp)	112	(150)	110	(148)	90	(121)	119	(160)	115	(154)	119	(160)	102	(137)
Number of Cylinders	6		6		6		6		4		4		6	
Piston Displacement L (cu. In)	5.9	(360)	6.7	(409)	4.4	(269)	6.8	(415)	4.7	(287)	5.2	(317)	N/A	N/A
<b>Hydraulics</b>	452		439		442		424		N/P		422		N/P	
Max. Flow ltr/min (gpm)	452	(119)	439	(116)	442	(117)	424	(112)	N/P	N/P	422	(111)	N/P	N/P
Implement Relief Valve Setting Mpa (psi)	31	(4,496)	38	(5,511)	35	(5,076)	35	(5,091)	34	(4,931)	36	(5,178)	N/P	N/P
<b>Undercarriage</b>	5		6		6		6		6		6		N/A	
Max. Travel Speed: High Kph (mph)	5	(3)	6	(3)	6	(3)	6	(3)	6	(3)	6	(3)	N/A	N/A
Gradeability (deg)	35		35		N/P		35		35		35		N/A	
Number of Carrier Rollers per Side	2		2		2		2		2		2		N/A	
Number of Track Rollers	7		9		8		8		8		8		N/A	
<b>Swing</b>	12		12		11		13		12		12		13	
Swing Speed (rpm)	12		12		11		13		12		12		13	
Swing Torque kg-m (ft-lb)	6,710	(48,534)	6,900	(49,908)	6,180	(44,700)	7,026	(50,819)	7,811	(56,497)	6,526	(47,203)	N/P	N/P
<b>Performance</b>	1.0		1.2		1.2		0.9		1.4		1.2		N/P	
Bucket Capacity - 1134kg Material Loose m3 (cu. Yd)	1.0	(1.3)	1.2	(1.6)	1.2	(1.6)	0.9	(1.2)	1.4	(1.8)	1.2	(1.5)	N/P	N/P
SAE Arm Crowd Force at Power Max. kg (lb)	10,900	(24,030)	10,300	(22,708)	10,390	(22,906)	13,300	(29,321)	11,951	(26,347)	10,300	(22,708)	N/P	N/P
SAE Bucket Digging Force at Power Max. kg (lb)	11,421	(25,179)	14,100	(31,085)	12,590	(27,756)	14,200	(31,306)	13,297	(29,315)	14,200	(31,306)	N/P	N/P
<b>Dimensions</b>	2,939		3,040		2,960		2,950		2,930		2,950		N/A	
Overall Height to Top of Cab mm (ft)	2,939	(9.6)	3,040	(10.0)	2,960	(9.7)	2,950	(9.7)	2,930	(9.6)	2,950	(9.7)	N/A	N/A
Ground Clearance, Counterweight mm (in)	1,065	(41.9)	1,085	(42.7)	1,020	(40.2)	1,030	(40.6)	1,025	(40.4)	1,040	(40.9)	N/A	N/A
Swing Radius mm (ft)	3,974	(13.0)	2,750	(9.0)	2,830	(9.3)	2,890	(9.5)	2,850	(9.4)	2,750	(9.0)	N/A	N/A
Track Length on Ground mm (ft)	3,445	(11.3)	3,665	(12.0)	3,650	(12.0)	3,670	(12.0)	3,660	(12.0)	3,660	(12.0)	N/P	N/P
Track Length mm (ft)	4,256	(14.0)	4,450	(14.6)	4,460	(14.6)	4,460	(14.6)	4,460	(14.6)	4,470	(14.7)	N/P	N/P
Track Gauge mm (ft)	2,380	(7.8)	2,380	(7.8)	2,380	(7.8)	2,390	(7.8)	2,390	(7.8)	3,190	(10.5)	N/P	N/P
Overall Length mm (ft)	9,739	(32.0)	9,495	(31.2)	9,540	(31.3)	9,750	(32.0)	9,750	(32.0)	9,380	(30.8)	N/P	N/P
Overall Height to Top of Boom mm (ft)	3,135	(10.3)	3,190	(10.5)	3,130	(10.3)	3,180	(10.4)	3,120	(10.2)	3,000	(9.8)	N/P	N/P
Overall Width mm (ft)	2,980	(9.8)	3,180	(10.4)	2,980	(9.8)	2,990	(9.8)	3,190	(10.5)	3,190	(10.5)	N/P	N/P
Ground Clearance (Minimum) mm (in)	468	(18.4)	440	(17.3)	450	(17.7)	450	(17.7)	460	(18.1)	440	(17.3)	N/P	N/P
Shoe Width mm (in)	700	(27.6)	800	(31.5)	600	(23.6)	600	(23.6)	800	(31.5)	800	(31.5)	N/A	N/A
<b>Working Range</b>	6,930		6,095		6,720		6,180		6,330		6,650		5,010	
Max. Digging Depth mm (ft)	6,930	(22.7)	6,095	(20.0)	6,720	(22.0)	6,180	(20.3)	6,330	(20.8)	6,650	(21.8)	5,010	(16.4)
Max. Vertical Wall Digging Depth mm (ft)	5,915	(19.4)	5,430	(17.8)	5,060	(16.6)	5,300	(17.4)	5,520	(18.1)	5,960	(19.6)	4,440	(14.6)
Max. Digging Depth of Cut for 8' Level Bottom mm (ft)	6,735	(22.1)	5,780	(19.0)	6,550	(21.5)	5,950	(19.5)	6,110	(20.0)	6,470	(21.2)	N/P	N/P
Max. Digging Reach at Ground Level mm (ft)	9,993	(32.8)	9,190	(30.2)	9,860	(32.3)	9,250	(30.3)	9,350	(30.7)	9,730	(31.9)	7,750	(25.4)
Max. Digging Height mm (ft)	9,255	(30.4)	9,800	(32.2)	9,370	(30.7)	9,670	(31.7)	9,220	(30.2)	9,610	(31.5)	8,960	(29.4)
Max. Dumping Height mm (ft)	6,383	(20.9)	6,860	(22.5)	6,490	(21.3)	6,830	(22.4)	6,430	(21.1)	6,810	(22.3)	6,570	(21.6)
<b>Capacities</b>	340		400		345		403		375		410		343	
Refill Capacity - Fuel Tank L (gal)	340	(89.8)	400	(105.7)	345	(91.1)	403	(106.5)	375	(99.1)	410	(108.3)	343	(91)
Refill Capacity - Coolant L (gal)	30	(7.9)	20	(5.4)	25	(6.6)	31	(8.1)	15	(4.0)	30	(7.9)	35	(9.2)
Refill Capacity - Engine L (gal)	22	(5.7)	23	(6.1)	15	(4.0)	21	(5.5)	17	(4.5)	30	(7.9)	21	(5.5)
Refill Capacity - Final Drive, Each L (gal)	5.4	(1.4)	3.3	(0.9)	5	(1.3)	7.8	(2.1)	N/P	N/P	N/P	N/P	N/P	N/P
Refill Capacity - Swing Drive L (gal)	3.4	(0.9)	6.6	(1.7)	5	(1.3)	6.8	(1.8)	8.6	(2.3)	N/P	N/P	N/P	N/P
Refill Capacity - Hydraulic Tank L (gal)	246	(65.0)	135	(35.7)	115	(30.4)	135	(35.7)	160	(42.3)	250	(66.0)	120	(32)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.