



Track Asphalt Pavers	Rhino RAP60W				Cat AP1000F		Volvo PF4410		Dynapac F2500W	
Engine	Cummins				Cat		Volvo		Cummins	
Brand	Cummins				Cat		Volvo		Cummins	
Model	QSB3.9 / QSB5.9-C190				C7.1 Acert		PF4410		QSB 6.7	
Emission Rating (optional)	Tier 2 (3 / 4)				Interim Tier 4		Tier 2		Tier 3	
Displacement L (in3)	6	(366)	6	(366)	7	(427)	N/P	N/P	N/P	N/P
Gross Engine Output Kw (Hp)	93	(125)	140	(188)	168	(225)	118	(158)	110	(148)
Dimensions										
Min. Transport Height mm (ft)	2,750		(9)		2,850	(9)	N/P	N/P	3,100	(10)
Standard Screed Transport Width mm (ft)	2,800		(9)		3,240	(11)	2,400	(8)	2,550	(8)
Track Length on Ground mm (ft)	3,090		(10)		N/P	N/P	2,591	(9)	N/P	N/P
Overall Length with Standard Screed mm (ft)	6,394		(21)		5,460	(18)	5,430	(18)	6,100	(20)
Hopper Length mm (ft)	2,240		(7)		2,100	(7)	2,500	(8)	2,123	(7)
Overall Machine Height mm (ft)	3,695		(12)		3,720	(12)	N/P	N/P	3,900	(13)
Refill Capacities										
Fuel Tank L (gal)	200		(52.8)		348	(91.9)	144	(38.0)	315	(83.2)
Performance										
Max. Travel Speed kph (mph)	16.8		(10.4)		20	(12.4)	13.7	(8.5)	15	(9.3)
Rated Paving Width mm (ft)	2,800		(9)		3,000	(10)	2,440	(8)	2,500	(8)
Extended Paving Width - Std Screen mm (ft) - (optional 7,000)	6,000		(20)		6,000	(20)	7,620	N/P	6,000	N/P
Retracted Paving Width - Std Screen mm (ft)	2,800		(9)		N/P	N/P	N/P	N/P	N/P	N/P
Driving System Type	Wheeled				Wheeled		Wheeled		Wheeled	
Auger Type	Twin Screws				N/P		N/P		N/P	
Conveyor Type	Twin Conveyors				N/P		N/P		N/P	
Weights										
Operating Weight with Screed kg (lbs)	14,500		(31,967)		19,044	(41,985)	13,109	(28,900)	18,000	(39,683)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.