



Track Asphalt Pavers		Rhino RAP75T		Cat AP1055F		Bomag CR462		Dynapac F1000T	
<b>Engine</b>									
Brand	Rhino		Cat		Cummins		Cummins		
Model	SC8D190G2B1		C7.1 Acert		QSB6.7		QSB6.7-225		
Emission Rating (optional)	Tier 2 (3 / 4)		N/P		Tier 3		Tier 4I		
Displacement L (in3)	7	(439)	N/P	N/P	N/P	N/P	N/P	N/P	
Gross Engine Output Kw (Hp)	174	(233)	168	(225)	168	(225)	168	(225)	
<b>Dimensions</b>									
Min. Transport Height mm (ft)	2,900	(10)	3,050	(10)	N/P	N/P	2,692	(9)	
Standard Screed Transport Width mm (ft)	3,042	(10)	N/P	N/P	3,150	(10)	3,276	(11)	
Track Length on Ground mm (ft)	3,247	(11)	N/P	N/P	2,896	(10)	N/P	N/P	
Overall Length with Standard Screed mm (ft)	6,610	(22)	6,860	(23)	5,969	(20)	6,502	(21)	
Hopper Length mm (ft)	2,530	(8)	N/P	N/P	1,803	(6)	N/P	N/P	
Overall Machine Height mm (ft)	4,030	(13)	4,000	(13)	2,794	(9)	3,352	(11)	
<b>Refill Capacities</b>									
Fuel Tank L (gal)	325	(85.9)	348	(91.9)	273	(72.1)	370	(97.7)	
<b>Performance</b>									
Max. Travel Speed kph (mph)	2.9	(1.8)	14	(8.7)	15	(9.3)	16	(9.9)	
Rated Paving Width mm (ft)	3,000	(118)	3,000	(10)	3,150	(10)	3,000	(10)	
Extended Paving Width - Std Screen mm (ft) - (optional 9,000)	7,500	(25)	7,650	(25)	8,500	(28)	7,900	(26)	
Retracted Paving Width - Std Screen mm (ft)	3,000	(10)	N/P	N/P	N/P	N/P	N/P	N/P	
Driving System Type	Tracked		Tracked		Tracked		Tracked		
Auger Type	Twin Screws		N/P		N/P		N/P		
Conveyor Type	Twin Conveyors		N/P		N/P		N/P		
<b>Weights</b>									
Operating Weight with Screed kg (lbs)	25,000	(55,116)	20,452	(45,089)	15,740	(34,701)	15,900	(35,053)	

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.