



<b>Compactors</b>		<b>Rhino RC 200</b>		<b>DYNAPAC CA610D</b>	
<b>General</b>					
Brand	Rhino		Dynapac		
Model	RC 200		CA610D		
Rated Output kW (HP)	132	(177)	127	(170)	
Static Drum Weight Kg (lb)	10,500	(23,149)	N/A	N/A	
Operational Weight Kg (lb)	20,200	(44,533)	20,700	(45,636)	
Static Line Force N/cm (lb/in)	500	(286)	N/A	N/A	
<b>Engine</b>					
Model (optional)	Cummins (Rhino)		Cummins		
Type	6BT5.9		6BTAA5.9-C170		
Total Exhaust Cylinder L (cu. In)	5.9	(360)	N/P	N/P	
Rated Speed (rpm)	2,300		2,200		
Starting Type	Electric		Electric		
<b>Specifications</b>					
Static Drum Weight Kg (lb)	10,500	(23,149)	N/A	N/A	
Static Weight Tires Kg (lb)	9,500	(20,944)	N/P	N/P	
Drum Width mm (ft)	2,100	(6.9)	2,130	(7.0)	
Pad	OPT		No		
Weight Pad Kg (lb)	930	(2,050)	N/P	N/P	
<b>Driving System</b>					
Model	Hydrostatic Travel		Hydrostatic Travel		
Type	Drive Pump + Reducer		N/P		
System pressure Mpa (psi)	40	(5,802)	N/P	N/P	
<b>Hydraulic</b>					
Model	Gear		N/P		
Vibrating Hydraulic System Pressure Mpa (psi)	28	(4,061)	N/P		
<b>Dimensions</b>					
Length mm (ft)	6,435	(21.1)	6,180	(20.3)	
Height mm (ft)	3,090	(10.1)	3,000	(9.8)	
Wheelbase mm (ft)	3,380	(11.1)	2,992	(9.8)	
Width mm (ft)	2,280	(7.5)	2,130	(7.0)	
Min. Ground Clearance mm (ft)	480	(1.6)	N/A	N/A	
<b>Capacity</b>					
Fuel L (gal)	300	(79.3)	320	(84.5)	
Engine Oil L (gal)	15	(4.0)	N/P	N/P	
Oil Hydraulic L (gal)	200	(52.8)	N/P	N/P	
Oil for Vibrating Drum L (gal)	56	(14.8)	N/P	N/P	
Equipment specifications and images may change without notice from Rhino Equipment Group Inc.					
Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.					