





| 11111110 | | | | | | | | |
|---|----------------------|---------|------------------------------|----------|--------------------|---------|-------------------------|---------|
| Compactors General | Rhino RC 30 | | Dynapac CA1300D | | Bomag BW124DH-40 | | Cat CS34 | |
| Brand | Rhino | | Dynapac | | Bomag | | Cat | |
| Model | RC 30 | | CA1300D | | BW124DH-40 | | CS34 | |
| Rated Output kW (HP) | 22 (30) | | 56 (75) | | 34 (46) | | 55 (74) | |
| Static Drum Weight Kg (lb) | 1,510 | (3,329) | N/A | N/A | 1,600 | (3,527) | 2,040 | (4,497) |
| Operational Weight Kg (lb) | 3,000 | (6,614) | 4,800 | (10,582) | 3,180 | (7,011) | 4,445 | (9,800) |
| Static Line Force N/cm (lb/in) | 114 | (65) | N/A | N/A | N/A | N/A | N/A | N/A |
| Engine | | | | | | | | |
| Model | Rhino | | Kubota | | Deutz | | CAT | |
| Туре | ZN390Q | | V 3307 | | D2011 L03i | | C3.4B | |
| Total Exhaust Cylinder L (cu. In) | 1.8 | (110) | N/P | N/P | N/P | N/P | N/P | N/P |
| Rated Speed (rpm) | - 2 | 2,600 | 2,2 | 200 | 2,500 | | 2,100 | |
| Starting Type | Electric | | Electric | | Electric | | Electric | |
| Specifications | | | | | | | | |
| Static Drum Weight Kg (lb) | 1,510 | (3,329) | N/A | N/A | 1,600 | (3,527) | 2,040 | (4,497) |
| Static Weight Tires Kg (lb) | 1,490 | (3,285) | N/A | N/A | 1,580 | (3,483) | N/P | N/P |
| Drum Width mm (ft) | 1,200 | (3.9) | 1,370 | (4.5) | 1,310 | (4.3) | 1,270 | (4.2) |
| Pad | No | | No | | No | | No | |
| Weight Pad Kg (lb) | N/P | | N/P | | N/P | | N/P | |
| Driving System | | | | | | | | |
| Model | Hydrostatic Travel | | Hydrostatic Travel | | Hydrostatic Travel | | Hydrostatic Travel | |
| Туре | Drive Pump + Reducer | | Water Cooled Turbo Diesel | | N/P | | Drive Pump + Reducer | |
| System pressure Mpa (psi) | 24 | (3,481) | N | /P | N/P | | N/P | N/P |
| Hydraulic | | | | | | | | |
| Model | Gear | | Gear | | N/P | | N/P | N/P |
| Vibrating Hydraulic System Pressure Mpa (psi) | 10 | (1,450) | N/P | | N/P | | N/P | N/P |
| Dimensions | | | | | | | | |
| Length mm (ft) | 3,505 | (11.5) | 3,950 | (13.0) | 3,450 | (11.3) | 4,150 | (13.6) |
| Height mm (ft) | 2,265 | (7.4) | 2,530 | (8.3) | 2,471 | (8.1) | 2,510 | (8.2) |
| Wheelbase mm (ft) | 1,970 | (6.5) | 1,860 | (6.1) | 1,805 | (5.9) | 2,240 | (7.3) |
| Width mm (ft) | 1,390 | (4.6) | 1,400 | (4.6) | 1,310 | (4.3) | 1,390 | (4.6) |
| Min. Ground Clearance mm (ft) | 210 | (0.7) | N/A | N/A | 320 | (1.0) | 347 | (1.1) |
| Capacity | | | | | | | | |
| Fuel L (gal) | 80 | (21.1) | 117 | (30.9) | 60 | (15.9) | 113 | (29.9) |
| Engine Oil L (gal) | 4 | (1.1) | N/P | N/P | N/P | N/P | 8 | (2.1) |
| Oil Hydraulic L (gal) | 95 | (25.1) | N/P | N/P | N/P | N/P | 40 | (10.6) |
| Oil for Vibrating Drum L (gal) | 2 | (0.5) | N/P | N/P | N/P | N/P | N/A | N/A |
| | | | | | | | | |

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.