



Compactors		Rhino RC 80				Cat CS44B	
<b>General</b>							
Brand	Rhino				Cat		
Model	RC 80				CS44		
Rated Output kW (HP)	42	(56)	80	(107)	75	(101)	
Static Drum Weight Kg (lb)	3,900		(8,598)		3,510	(7,738)	
Operational Weight Kg (lb)	8,200		(18,078)		6,900	(15,212)	
Static Line Force N/cm (lb/in)	215		(123)		N/A	N/A	
<b>Engine</b>							
Model	Rhino		Cummins		CAT		
Type	A498BG		4B3.9-C		C4.4		
Rated Speed (rpm)	2,300				2,200		
Starting Type	Electric				Electric		
<b>Specifications</b>							
Static Drum Weight Kg (lb)	3,900		(8,598)		3,510	(7,738)	
Static Weight Tires Kg (lb)	2,100		(4,630)		N/P	N/P	
Drum Width mm (ft)	1,700		(3,748)		1,680	(5.5)	
Pad	No				Yes		
Weight Pad Kg (lb)	930		(2,050)		990	(2,183)	
<b>Driving System</b>							
Model	Hydrostatic Travel				Hydrostatic Travel		
Type	Drive Pump + Reducer				Drive Pump + Reducer		
System pressure Mpa (psi)	28		(4,061)		N/P	N/P	
<b>Hydraulic</b>							
Model	Gear				N/P	N/P	
Vibrating Hydraulic System Pressure Mpa (psi)	12		(1,740)		N/P	N/P	
<b>Dimensions</b>							
Length mm (ft)	5,180		(17.0)		5,080	(16.7)	
Height mm (ft)	2,580		(8.5)		2,970	(9.7)	
Wheelbase mm (ft)	2,750		(9.0)		2,060	(6.8)	
Width mm (ft)	1,920		(6.3)		1,800	(5.9)	
Min. Ground Clearance mm (ft)	320		(1.0)		380	(1.2)	
<b>Capacity</b>							
Fuel L (gal)	210		(55.5)		180	(47.6)	
Engine Oil L (gal)	10		(2.6)		8.5	(2.2)	
Oil Hydraulic L (gal)	100		(26.4)		80	(21.1)	
Oil for Vibrating Drum L (gal)	7		(1.8)		6	(1.6)	

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.