



Tandem Compactors

Engine	Rhino RCT120H		Cat CB64		DYNAPAC CC6200		Volvo DD120C	
Brand (optional)	Cummins (Rhino)		CAT		Cummins		Volvo	
Model	4BTA3.9		C4.4 ACERT		QSB 4.5		EPA	
Emission Rating (optional)	Tier 2 (3/4)		Tier 4		Tier 4		Tier 4	
Displacement L (in3)	4	(238)	4.4	(269)	4.5	(275)	4	(244)
Gross Engine Output Kw (Hp)	93	(125)	96	(129)	119	(160)	110	(148)
Transmission								
Transmission Type	Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic	
Dimensions								
Overall Length mm (ft)	5,360	(18)	N/P	N/P	5,410	(18)	5,973	(20)
Overall Height mm (ft)	2,970	(10)	N/P	N/P	2,997	(10)	3,177	(10)
Overall Width mm (ft)	2,270	(7)	2,335	(8)	2,286	(8)	2,000	(7)
Steering Angle	35 degrees		35 degrees		32 degrees		N/P	
Outside Turning Radius mm (ft)	7,000	(23)	N/P	N/P	N/P	N/P	N/P	N/P
Refill Capacities								
Fuel Tank L (gal)	192	(50.7)	191	(50.5)	239	(63.1)	200	(52.8)
Performance								
Linear Drum Load - Front kg/cm (lb/in)	28.2	157.9	N/P	N/P	N/P	N/P	N/P	N/P
Linear Drum Load - Rear kg/cm (lb/in)	28.2	157.9	N/P	N/P	N/P	N/P	N/P	N/P
Travel Speed kph (mph)	13	(8)	13	(8)	N/P	N/P	12	(7)
Vibration Frequency Hz (vpm)	50	(29)	N/P	N/P	N/P	N/P	N/P	N/P
Drum Vibration	Both		N/P		N/P		N/P	
Weights								
Max. Operating Weight kg (lbs)	12,000	(26,455)	12,980	(28,616)	13,608	(30,001)	12,565	(27,701)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.