



Tandem Compactors

Engine	Rhino RCT14H3		Cat CB68B		Volvo DD140C	
Brand (optional)	Cummins (Rhino)		CAT		Volvo	
Model	6BTAA5.9		C4.4 ACERT		EPA	
Emission Rating (optional)	Tier 2 (3/4)		Tier 4		Tier 4	
Displacement L (in3)	6	(360)	4.4	(269)	4	(244)
Gross Engine Output Kw (Hp)	110	(148)	106	(142)	110	(148)
Transmission						
Transmission Type	Hydrostatic		Hydrostatic		Hydrostatic	
Dimensions						
Overall Length mm (ft)	4,890	(16)	4,742	(16)	5,973	(20)
Overall Height mm (ft)	3,120	(10)	3,068	(10)	3,177	(10)
Overall Width mm (ft)	2,240	(7)	2,130	(7)	2,135	(7)
Steering Angle	35 degrees		36 degrees		N/P	
Outside Turning Radius mm (ft)	7,000	(23)	N/P	N/P	N/P	N/P
Refill Capacities						
Fuel Tank L (gal)	250	(66.0)	250	(66.0)	220	(58.1)
Performance						
Linear Drum Load - Front kg/cm (lb/in)	32.9	184.2	N/P	N/P	N/P	N/P
Linear Drum Load - Rear kg/cm (lb/in)	32.9	184.2	N/P	N/P	N/P	N/P
Travel Speed kph (mph)	13	(8)	13	(8)	12	(7)
Vibration Frequency Hz (vpm)	50	(29)	42	(24)	N/P	N/P
Drum Vibration	Both		N/P		N/P	
Weights						
Max. Operating Weight kg (lbs)	14,000	(30,865)	14,180	(31,262)	13,828	(30,486)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.