



Tandem Compactors		Rhino RCT40H		Cat CB36B		Bomag BW120AD		DYNAPAC CC1300		Volvo DD35B	
Engine											
Brand	Rhino			CAT		Kubota		Kubota		Kubota	
Model	ZN390Q			C2.2		V 2403		V2203-M		D1803	
Emission Rating (optional)	Tier 2 (3/4)			Tier 4		Tier 4		Tier 4		Tier 4	
Displacement L (in3)	1.8	(110)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Gross Engine Output Kw (Hp)	22	(30)	36	(48)	33.6	(45)	33	(44)	37	(50)	
Transmission											
Transmission Type	Hydrostatic			Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic	
Dimensions											
Overall Length mm (ft)	3,180	(10)	2,859	(9)	2,819	(9)	2725	(9)	2,566	(8)	
Overall Height mm (ft)	2,650	(9)	N/P	N/P	2692	(9)	2750	(9)	2,956	(10)	
Overall Width mm (ft)	1,420	(5)	1,500	(5)	1371	(4)	1450	(5)	1,363	(4)	
Steering Angle	35 degrees			N/P		30 degrees		30 degrees		N/P	
Outside Turning Radius mm (ft)	3,800	(12)	N/P	N/P	N/P	N/P	4240	(14)	N/P	N/P	
Refill Capacities											
Fuel Tank L (gal)	80	(21.1)	90	(23.8)	53	(14.0)	50	(13.2)	66	(17.4)	
Performance											
Linear Drum Load - Front kg/cm (lb/in)	15	84.0	13.6	76.2	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Linear Drum Load - Rear kg/cm (lb/in)	18.4	103.0	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Travel Speed kph (mph)	8	(5)	13	(8)	6	(4)	N/P	N/P	10	(6)	
Vibration Frequency Hz (vpm)	50	(29)	55	(31)	67	(38)	N/P	N/P	67	(38)	
Drum Vibration	Both			N/P		Front/Both		N/P		N/P	
Weights											
Max. Operating Weight kg (lbs)	4,000	(8,818)	3,803	(8,384)	5,953	(13,124)	4,030	(8,885)	3,713	(8,186)	

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.