



Tandem Compactors	Rhino RCT80H		Cat CD8		Bomag BW151AD		DYNAPAC CC2300	
Engine								
Brand (optional)	Cummins (Rhino)		CAT		Kubota		Deutz	
Model	4BTA3.9		C3.4 B		V3307 CR-T		TCD 3.6L4	
Emission Rating (optional)	Tier 2 (3/4)		Tier 4		Tier 4		Tier 4	
Displacement L (in3)	4	(238)	4.4	(269)	N/P	N/P	3.6	(220)
Gross Engine Output Kw (Hp)	93	(125)	N/P	N/P	55	(74)	75	(101)
Transmission								
Transmission Type	Hydrostatic		Hydrostatic		N/P		Hydrostatic	
Dimensions								
Overall Length mm (ft)	5,080	(17)	4,284	(14)	4,400	(14)	4,490	(15)
Overall Height mm (ft)	2,850	(9)	2,940	(10)	3,000	(10)	2,990	(10)
Overall Width mm (ft)	2,160	(7)	1,664	(5)	1,844	(6)	2,540	(8)
Steering Angle	35 degrees		N/P		N/P		32 degrees	
Outside Turning Radius mm (ft)	7,000	(23)	N/P	N/P	N/P	N/P	5,190	(17)
Refill Capacities								
Fuel Tank L (gal)	200	(52.8)	135	(35.7)	125	(33.0)	130	(34.3)
Performance								
Linear Drum Load - Front kg/cm (lb/in)	21	117.6	N/P	N/P	23	128.8	28.3	158.5
Linear Drum Load - Rear kg/cm (lb/in)	21	117.6	N/P	N/P	22	123.2	28.3	158.5
Travel Speed kph (mph)	12	(7)	12	(7)	12	(7)	12	(7)
Vibration Frequency Hz (vpm)	50	(29)	53	(30)	70	(40)	67	(38)
Drum Vibration	Both		Both		Front/Both/Rear		Both	
Weights								
Max. Operating Weight kg (lbs)	8,000	(17,637)	8,390	(18,497)	7,600	(16,755)	8,500	(18,739)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.