



Reach Stackers

Rhino RRS4500

HYSTER RS45-27

General

Brand	Rhino		Hyster	
Model	RFL4500D-RS		RS45-27	
Rated Capacity Kg (lb)	45,000	(99,208)	45,000	(99,208)
Max. Stacking Height mm (in)	15,100	(921,457)	15,000	(915,354)
Net Horsepower kW (hp)	250	(335)	250	(335)
Operating weight kg (lb)	73,000	(160,937)	68,500	(151,017)

Engine

Make	Cummins		Cummins	
Model	QSM11		QSM11	
Rotating Speed (RPM)	2,100		2,100	

Drivetrain

Work Speed with Load Kph (mph)	20	(12)	N/P	N/P
Work Speed without Load Kph (mph)	25	(16)	N/P	N/P

Performance

Rated Operating Capacity Kg (lb)	73,000	(160,937)	68,500	(151,017)
Max. Lifting Speed with Load mm/s (in/s)	60	(2.0)	N/P	N/P
Gradeability with Load	15		N/P	

Dimensions

Overall Height Top of Boom mm (in)	4,650	(183,071)	4,700	(185,039)
Overall Height Top of Cab mm (in)	3,730	(146,850)	N/P	N/P
Overall Length mm (in)	11,373	(447,756)	11,873	(467,441)
Overall Width mm (in)	4,200	(165,354)	4,200	(165,354)
Spreader Min. Length mm (in)	6,042	(237,874)	6,100	(240,157)
Spreader Max. Length mm (in)	12,175	(479,331)	12,200	(480,315)
Spreader Width mm (in)	2,420	(95,276)	N/P	N/P
Lifting Height mm (in)	15,100	(594,488)	15,260	(600,787)
Front Tread mm (in)	3,033	(119,409)	N/P	N/P
Rear Tread mm (in)	2,750	(108,268)	N/P	N/P
Wheelbase mm (in)	5,500	(216,535)	6,200	(244,094)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.