



Excavators	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
General	Rhino Equipment		Komatsu		Caterpillar		John Deere		Volvo		Case		JCB	
Brand	Rhino Equipment		Komatsu		Caterpillar		John Deere		Volvo		Case		JCB	
Model	REX130		PC138USLC-11		313F GC		130G		EC140D		CX130D		JS145	
Arm Selection m (ft)	2.5	(8.2)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Weight	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
Operating Weight kg (lb)	13,000	(28,660)	15,682	(34,573)	13,300	(29,321)	13,388	(29,515)	13,550	(29,873)	13,800	(30,424)	14,367	(31,674)
Counterweight Mass kg (lb)	2,450	(5,401)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Ground Pressure Kpa (psi)	38	(5.5)	45	(6.5)	29	(4.2)	38	(5.5)	35	(5.1)	37	(5.4)	N/A	N/A
Engine	CUMMINS (RHINO)		KOMATSU		CAT		JOHN DEERE		Volvo		ISUZU		ISUZU	
Engine Make (optional)	CUMMINS (RHINO)		KOMATSU		CAT		JOHN DEERE		Volvo		ISUZU		ISUZU	
Engine Model	4BT3.9-C110		SAA4D95LE-5		C4.4 Acert		PWS 4.5L		D3.8E		AR-4JJ1X		4JJIX	
Net Horsepower kW (hp)	86	(115)	73	(98)	74	(99)	70	(94)	74	(99)	77	(103)	81	(109)
Number of Cylinders	4		4		N/P		4		4		4		4	
Piston Displacement L (cu. In)	3.9	(238)	3.2	(195)	3.4	(207)	4.5	(275)	4.0	(244)	3.0	(182)	N/A	N/A
Hydraulics	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
Max. Flow ltr/min (gpm)	256	(68)	242	(64)	240	(63)	105	(28)	236	(62)	N/P	N/P	N/P	N/P
Implement Relief Valve Setting Mpa (psi)	31	(4,496)	36	(5,221)	30	(4,351)	35	(5,091)	35	(5,076)	N/P	N/P	N/P	N/P
Undercarriage	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
Max. Travel Speed: High Kph (mph)	5	(3)	5	(3)	5	(3)	6	(3)	6	(3)	5	(3)	N/A	N/A
Gradeability (deg)	35		35		N/P		N/P		35		35		N/A	
Number of Carrier Rollers per Side	2		1		1		1		1		1		N/A	
Number of Track Rollers	7		7		7		7		7		7		N/A	
Swing	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
Swing Speed (rpm)	13		11		11		13		12		14		14	
Swing Torque kg-m (ft-lb)	2,722	(19,688)	N/P	N/P	10,337	(74,768)	3,400	(24,592)	3,957	(28,621)	N/P	N/P	N/P	N/P
Performance	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
Bucket Capacity - 1134kg Material Loose m3 (cu. Yd)	0.5	(0.7)	0.6	(0.8)	N/P	N/P	0.5	(0.7)	0.8	(1.0)	N/P	N/P	N/P	N/P
SAE Arm Crowd Force at Power Max. kg (lb)	6,460	(14,242)	N/P	N/P	N/P	N/P	6,500	(14,330)	6,700	(14,771)	N/P	N/P	N/P	N/P
SAE Bucket Digging Force at Power Max. kg (lb)	7,995	(17,626)	N/P	N/P	N/P	N/P	8,500	(18,739)	8,902	(19,626)	N/P	N/P	N/P	N/P
Dimensions	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
Overall Height to Top of Cab mm (ft)	2,813	(9.2)	2,815	(9.2)	2,760	(9.1)	2,790	(9.2)	2,800	(9.2)	2,830	(9.3)	N/A	N/A
Ground Clearance, Counterweight mm (in)	870	(34.3)	900	(35.4)	900	(35.4)	840	(33.1)	920	(36.2)	895	(35.2)	N/A	N/A
Swing Radius mm (ft)	2,015	(6.6)	1,545	(5.1)	N/P	N/P	1,490	(4.9)	2,200	(7.2)	2,170	(7.1)	N/A	N/A
Track Length on Ground mm (ft)	2,750	(9.0)	3,140	(10.3)	N/P	N/P	2,880	(9.4)	3,040	(10.0)	N/A	N/A	N/P	N/P
Track Length mm (ft)	3,486	(11.4)	3,870	(12.7)	3,740	(12.3)	3,580	(11.7)	3,760	(12.3)	3,500	(11.5)	N/P	N/P
Track Gauge mm (ft)	1,960	(6.4)	1,990	(6.5)	1,990	(6.5)	1,990	(6.5)	1,990	(6.5)	N/A	N/A	N/P	N/P
Overall Length mm (ft)	7,600	(24.9)	7,385	(24.2)	7,700	(25.3)	7,370	(24.2)	7,700	(25.3)	N/A	N/A	N/P	N/P
Overall Height to Top of Boom mm (ft)	2,780	(9.1)	2,850	(9.4)	2,830	(9.3)	2,790	(9.2)	2,830	(9.3)	N/A	N/A	N/P	N/P
Overall Width mm (ft)	2,490	(8.2)	2,590	(8.5)	2,490	(8.2)	2,590	(8.5)	2,590	(8.5)	2,590	(8.5)	N/P	N/P
Ground Clearance (Minimum) mm (in)	370	(14.6)	395	(15.6)	440	(17.3)	410	(16.1)	436	(17.2)	N/A	N/A	N/P	N/P
Shoe Width mm (in)	500	(19.7)	600	(23.6)	N/P	N/P	600	(23.6)	600	(23.6)	N/A	N/A	N/A	N/A
Working Range	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
Max. Digging Depth mm (ft)	5,500	(18.0)	5,480	(18.0)	6,040	(19.8)	5,490	(18.0)	5,530	(18.1)	5,330	(17.5)	5,010	(16.4)
Max. Vertical Wall Digging Depth mm (ft)	4,940	(16.2)	4,900	(16.1)	5,200	(17.1)	4,730	(15.5)	4,960	(16.3)	5,550	(18.2)	4,440	(14.6)
Max. Digging Depth of Cut for 8' Level Bottom mm (ft)	5,305	(17.4)	5,265	(17.3)	5,860	(19.2)	5,270	(17.3)	5,310	(17.4)	N/A	N/A	N/P	N/P
Max. Digging Reach at Ground Level mm (ft)	8,180	(26.8)	8,180	(26.8)	8,620	(28.3)	8,240	(27.0)	8,190	(26.9)	8,770	(28.8)	7,750	(25.4)
Max. Digging Height mm (ft)	8,630	(28.3)	9,340	(30.6)	N/P	N/P	9,290	(30.5)	8,390	(27.5)	N/A	N/A	8,960	(29.4)
Max. Dumping Height mm (ft)	6,180	(20.3)	6,840	(22.4)	N/P	N/P	6,830	(22.4)	5,980	(19.6)	6,390	(21.0)	6,570	(21.6)
Capacities	Rhino REX130		Komatsu PC138USLC-11		Caterpillar 313F GC		John Deere 130G		Volvo EC140D		Case CX130D		JCB JS145	
Refill Capacity - Fuel Tank L (gal)	247	(65.3)	200	(52.8)	250	(66.0)	280	(74.0)	250	(66.0)	260	(68.7)	253	(67)
Refill Capacity - Coolant L (gal)	14	(3.7)	17	(4.5)	11	(2.9)	N/P	N/P	23	(6.1)	N/A	N/A	20	(5.3)
Refill Capacity - Engine L (gal)	11	(2.9)	12	(3.2)	8	(2.1)	N/P	N/P	13	(3.4)	N/A	N/A	20	(5.3)
Refill Capacity - Final Drive, Each L (gal)	2.6	(0.7)	2.1	(0.6)	3	(0.8)	N/P	N/P	N/P	N/P	N/A	N/A	N/P	N/P
Refill Capacity - Swing Drive L (gal)	0.5	(0.1)	2.5	(0.7)	2	(0.6)	N/P	N/P	3.9	(1.0)	N/A	N/A	N/P	N/P
Refill Capacity - Hydraulic Tank L (gal)	145	(38.3)	69	(18.2)	162	(42.8)	69	(18.2)	85	(22.5)	82	(21.7)	73	(19)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.