



Excavator	Rhino REX360		Komatsu PC360LC		Caterpillar 336F		John Deere 350G LC		Case CX350D	
General										
Brand	Rhino Equipment		Komatsu		Caterpillar		John Deere		Case	
Model	REX360		PC360LC		336F		350G LC		CX350D	
Arm Selection m (ft)	3.2	(10.5)	2.5	(8.2)	3.2	(10.5)	2.7	(8.9)	2.6	(8.5)
Weight										
Operating Weight kg (lb)	34,500	(76,059)	35,748	(78,811)	36,570	(80,623)	34,726	(76,558)	37,414	(82,484)
Counterweight Mass kg (lb)	6,866	(15,137)	7,371	(16,250)	6,000	(13,228)	6,928	(15,274)	7,400	(16,314)
Ground Pressure Kpa (psi)	68	(9.9)	49	(7.1)	53	(7.7)	54	(7.8)	52	(7.5)
Engine										
Engine Make (optional)	CUMMINS (RHINO)		KOMATSU		CAT		JOHN DEERE		ISUZU	
Engine Model	6CTAA8.3-C		SAA6D114E-6		C9.3 ACERT		9.0L		AQ-6HK1X	
Net Horsepower kW (hp)	192	(257)	192	(257)	217	(291)	202	(271)	200	(268)
Number of Cylinders	6		6		6		6		6	
Piston Displacement L (cu. In)	8.3	(506)	8.3	(506)	9.3	(568)	9.0	(549)	8	(476)
Hydraulics										
Max. Flow ltr/min (gpm)	555	(147)	535	(141)	578	(153)	576	(152)	N/P	N/P
Implement Relief Valve Setting Mpa (psi)	31	(4,496)	38	(5,511)	36	(5,221)	36	(5,221)	N/P	N/P
Undercarriage										
Max. Travel Speed: High Kph (mph)	5	(3)	6	(4)	5	(3)	5	(3)	5	(3)
Gradeability (deg)	35		35		N/P		35		35	
Number of Carrier Rollers per Side	2		2		2		2		2	
Number of Track Rollers	8		8		9		8		8	
Swing										
Swing Speed (rpm)	11		10		9		11		10	
Swing Torque kg-m (ft-lb)	11,259	(81,437)	11,386	(82,355)	11,114	(80,388)	12,237	(88,510)	11,421	(82,608)
Performance										
Bucket Capacity - 1134kg Material Loose m3 (cu. Yd)	1.6	(2.1)	2.0	(2.6)	2.3	(3.0)	1.8	(2.4)	1.0	(1.3)
SAE Arm Crowd Force at Power Max. kg (lb)	18,400	(40,565)	19,700	(43,431)	18,460	(40,697)	20,420	(45,018)	19,500	(42,990)
SAE Bucket Digging Force at Power Max. kg (lb)	20,800	(45,856)	23,300	(51,368)	23,470	(51,742)	22,520	(49,648)	22,880	(50,442)
Dimensions										
Overall Height to Top of Cab mm (ft)	3,280	(10.8)	3,130	(10.3)	3,360	(11.0)	3,140	(10.3)	3,110	(10.2)
Ground Clearance, Counterweight mm (in)	2,265	(89.2)	1,185	(46.7)	3,360	(132.3)	1,180	(46.5)	1,210	(47.6)
Swing Radius mm (ft)	3,420	(11.2)	3,450	(11.3)	3,500	(11.5)	3,600	(11.8)	3,550	(11.6)
Track Length on Ground mm (ft)	3,700	(12.1)	4,030	(13.2)	4,040	(13.3)	4,050	(13.3)	4,040	(13.3)
Track Length mm (ft)	4,600	(15.1)	4,955	(16.3)	5,020	(16.5)	4,940	(16.2)	4,980	(16.3)
Track Gauge mm (ft)	2,590	(8.5)	2,590	(8.5)	2,590	(8.5)	2,590	(8.5)	3,400	(11.2)
Overall Length mm (ft)	11,080	(36.4)	11,180	(36.7)	10,890	(35.7)	11,330	(37.2)	11,200	(36.7)
Overall Height to Top of Boom mm (ft)	3,180	(10.4)	3,410	(11.2)	3,600	(11.8)	3,470	(11.4)	3,640	(11.9)
Overall Width mm (ft)	3,190	(10.5)	3,440	(11.3)	3,440	(11.3)	3,390	(11.1)	3,400	(11.2)
Ground Clearance (Minimum) mm (in)	720	(28.3)	500	(19.7)	510	(20.1)	500	(19.7)	480	(18.9)
Shoe Width mm (in)	600	(23.6)	850	(33.5)	850	(33.5)	800	(31.5)	800	(31.5)
Working Range										
Max. Digging Depth mm (ft)	7,370	(24.2)	6,705	(22.0)	6,650	(21.8)	6,840	(22.4)	6,730	(22.1)
Max. Vertical Wall Digging Depth mm (ft)	6,380	(20.9)	5,880	(19.3)	4,450	(14.6)	5,510	(18.1)	5,970	(19.6)
Max. Digging Depth of Cut for 8' Level Bottom mm (ft)	7,020	(23.0)	6,250	(20.5)	5,810	(19.1)	6,640	(21.8)	6,550	(21.5)
Max. Digging Reach at Ground Level mm (ft)	10,910	(35.8)	10,355	(34.0)	10,260	(33.7)	10,360	(34.0)	10,470	(34.4)
Max. Digging Height mm (ft)	10,200	(33.5)	9,965	(32.7)	9,970	(32.7)	9,990	(32.8)	10,320	(33.9)
Max. Dumping Height mm (ft)	7,135	(23.4)	6,895	(22.6)	6,620	(21.7)	6,940	(22.8)	7,140	(23.4)
Capacities										
Refill Capacity - Fuel Tank L (gal)	610	(161.1)	605	(159.8)	620	(163.8)	628	(165.9)	580	(153.2)
Refill Capacity - Coolant L (gal)	45	(11.9)	30	(7.9)	56	(14.8)	40	(10.6)	38	(10.0)
Refill Capacity - Engine L (gal)	33	(8.7)	35	(9.2)	31	(8.2)	27	(7.1)	48	(12.7)
Refill Capacity - Final Drive, Each L (gal)	8.3	(2.2)	8.5	(2.2)	8	(2.1)	8.5	(2.2)	10.0	(2.6)
Refill Capacity - Swing Drive L (gal)	17.0	(4.5)	13.0	(3.4)	19	(5.0)	12.0	(3.2)	5.0	(1.3)
Refill Capacity - Hydraulic Tank L (gal)	310	(81.9)	188	(49.7)	175	(46.2)	193	(51.0)	175	(46.2)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.