



Forklifts		RHINO RFL200-E		Cat EP20NT		Toyota 7FBH20		Komatsu FB20SHU-6		Hyundai 20B-9	
<b>General</b>											
Brand	Rhino		Caterpillar		Toyota		Komatsu		Hyundai		
Model	RFL200-E		EP20NT		7FBH20		FB20SHU-6		20B-9		
Rated Capacity kg (lb)	2,000	(4,409)	2,000	(4,409)	2,000	(4,409)	1,815	(4,001)	1,815	(4,001)	
Overall Height (mast raised) mm (in)	4,080	(161)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Net Horsepower kW (hp)	20	(27)	14.0	(19)	11.0	(15)	14	(19)	14	(19)	
Operating Weight kg (lb)	3,950	(8,708)	3,520	(7,760)	2,745	(6,052)	4,050	(8,929)	3,479	(7,670)	
<b>Electrical</b>											
Volts V	48		48		48		36		48		
Amps Ah	700		720		730		675		510		
<b>Drivetrain</b>											
Work Speed with Load Kph (mph)	13	(7.8)	17.0	(10.6)	14.5	(9.0)	8.7	(5.4)	9.9	(6.2)	
Work Speed with out Load Kph (mph)	14	(8.7)	17.0	(10.6)	16.5	(10.3)	9.3	(5.8)	11	(6.6)	
<b>Performance</b>											
Rated Operating Capacity kg (lb)	3,950	(8,708)	3,520	(7,760)	2,745	(6,052)	4,050	(8,929)	3,479	(7,670)	
Max. Lifting Speed with Load mm/s (in/s)	250	(10)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Max. Traction with Load kN(lbf)	10	(2,248)	N/P	N/P	N/P	N/P	N/P	n	N/P	N/P	
Gradeability with Load	15		13		15		25		25		
<b>Dimensions</b>											
Max. Height with Mast Lowered mm (in)	2,130	(83.9)	2,105	(82.9)	3,000	(118.1)	2,159	(85.0)	2,130	(83.9)	
Overall Height Top of Cab mm (in)	2,130	(83.9)	2,048	(80.6)	N/P	N/P	N/P	N/P	2,048	(80.6)	
Overall Length mm (in)	3,350	(131.9)	2,952	(116.2)	N/P	N/P	N/P	N/P	3,000	(118.1)	
Overall Width mm(in)	1,160	(45.7)	1,130	(44.5)	1,160	(45.7)	1,070	(42.1)	1,130	(44.5)	
Fork Length mm (in)	1,070	(42.1)	920	(36.2)	1,070	(42.1)	1,070	(42.1)	1,067	(42.0)	
Fork Width mm (in)	100	(3.9)	100	(3.9)	120	(4.7)	100	(3.9)	100	(3.9)	
Fork Thickness mm (in)	40	(1.6)	35	(1.4)	38	(1.5)	40	(1.6)	35	(1.4)	
Lifting Height mm (in)	3,000	(118.1)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Front Tread mm (in)	970	(38.2)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Rear Tread mm (in)	950	(37.4)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Wheelbase mm (in)	1,550	(61.0)	1,410	(55.5)	1,500	(59.1)	1,295	(51.0)	1,435	(56.5)	

Forklifts		RHINO RFL300-E		Cat EP30N		Toyota 7FBH30		Komatsu FB30SHU-6		Hyundai 30B-9	
<b>General</b>											
Brand	Rhino		Caterpillar		Toyota		Komatsu		Hyundai		
Model	RFL300-E		EP30N		7FBH30		FB30SHU-6		30B-9		
Rated Capacity kg (lb)	3,000	(6,614)	3,000	(6,614)	3,000	(6,614)	2,722	(6,001)	3,000	(6,614)	
Overall Height (mast raised) mm (in)	4,260	(168)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Net Horsepower kW (hp)	22	(30)	25	(34)	12.0	(16)	15	(19)	17	(23)	
Operating Weight kg (lb)	4,900	(10,803)	5,152	(11,358)	4,740	(10,450)	4,844	(10,679)	4,750	(10,472)	
<b>Engine</b>											
Volts V	80		80		80		36		48		
Amps Ah	500		700		370		900		740		
<b>Drivetrain</b>											
Work Speed with Load Kph (mph)	14	(8.7)	20.0	(12.4)	14.0	(8.7)	8.7	(5.4)	17.0	(10.6)	
Work Speed with out Load Kph (mph)	16	(9.9)	20.0	(12.4)	15	(9.3)	10.6	(6.6)	18	(11.2)	
<b>Performance</b>											
Rated Operating Capacity kg (lb)	4,900	(10,803)	5,152	(11,358)	4,740	(10,450)	4,844	(10,679)	4,750	(10,472)	
Max. Lifting Speed with Load mm/s (in/s)	290	(11)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Max. Traction with Load kN(lbf)	12.0	(2,698)	N/P	N/P	N/P	N/P	N/P	n	N/P	N/P	
Gradeability with Load	15		20		16		17		27		
<b>Dimensions</b>											
Max. Height with Mast Lowered mm (in)	2,200	(86.6)	2,165	(85.2)	2,020	(79.5)	2,159	(85.0)	2,162	(85.1)	
Overall Height Top of Cab mm (in)	2,200	(86.6)	2,240	(88.2)	N/P	N/P	N/P	N/P	N/P	N/P	
Overall Length mm (in)	3,705	(145.9)	3,628	(142.8)	3,560	(140.2)	N/P	N/P	3,538	(139.3)	
Overall Width mm(in)	1,240	(48.8)	1,190	(46.9)	1,240	(48.8)	1,070	(42.1)	1,200	(47.2)	
Fork Length mm (in)	1,220	(48.0)	1,070	(42.1)	1,070	(42.1)	1,070	(42.1)	1,102	(43.4)	
Fork Width mm (in)	125	(4.9)	125	(4.9)	120	(4.7)	100	(3.9)	117	(4.6)	
Fork Thickness mm (in)	45	(1.8)	45	(1.8)	45	(1.8)	40	(1.6)	N/P	N/P	
Lifting Height mm (in)	3,000	(118.1)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Front Tread mm (in)	1,000	(39.4)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Rear Tread mm (in)	980	(38.6)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Wheelbase mm (in)	1,700	(66.9)	1,730	(68.1)	1,650	(65.0)	1,500	(59.1)	1,600	(63.0)	

Forklifts		RHINO RFL350-E		Cat EP35N		Toyota 7FBJ35		Komatsu FB32SHU-6		Hyundai 35B-9	
<b>General</b>											
Brand	Rhino		Caterpillar		Toyota		Komatsu		Hyundai		
Model	RFL350-E		EP35N		7FBJ35		FB32SHU-6		35B-9		
Rated Capacity kg (lb)	3,500	(7,716)	3,500	(7,716)	3,500	(7,716)	3,000	(6,614)	3,500	(7,716)	
Overall Height (mast raised) mm (in)	4,250	(167)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Net Horsepower kW (hp)	22	(30)	25	(34)	12.0	(16)	15	(19)	17	(23)	
Operating Weight kg (lb)	5,160	(11,376)	5,591	(12,326)	5,300	(11,684)	5,100	(11,244)	5,190	(11,442)	
<b>Electric</b>											
Volts V	80		80		80		36		48		
Amps Ah	500		700		370		900		740		
<b>Drivetrain</b>											
Work Speed with Load Kph (mph)	13.5	(8.4)	18.0	(11.2)	13.0	(8.1)	8.7	(5.4)	17.0	(10.6)	
Work Speed with out Load Kph (mph)	15	(9.3)	18.0	(11.2)	15	(9.3)	10.6	(6.6)	18	(11.2)	
<b>Performance</b>											
Rated Operating Capacity kg (lb)	5,160	(11,376)	5,591	(12,326)	5,300	(11,684)	5,100	(11,244)	5,190	(11,442)	
Max. Lifting Speed with Load mm/s (in/s)	285	(11)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Max. Traction with Load kN(lbf)	13.0	(2,923)	N/P	N/P	N/P	N/P	N/P	n	N/P	N/P	
Gradeability with Load	15		20		20		17		27		
<b>Dimensions</b>											
Max. Height with Mast Lowered mm (in)	2,200	(86.6)	2,291	(90.2)	2,020	(79.5)	2,159	(85.0)	2,162	(85.1)	
Overall Height Top of Cab mm (in)	2,200	(86.6)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Overall Length mm (in)	3,745	(147.4)	3,300	(129.9)	3,560	(140.2)	N/P	N/P	3,538	(139.3)	
Overall Width mm(in)	1,240	(48.8)	1,190	(46.9)	1,240	(48.8)	1,070	(42.1)	1,200	(47.2)	
Fork Length mm (in)	1,220	(48.0)	1,070	(42.1)	1,070	(42.1)	1,070	(42.1)	1,102	(43.4)	
Fork Width mm (in)	125	(4.9)	125	(4.9)	120	(4.7)	100	(3.9)	117	(4.6)	
Fork Thickness mm (in)	45	(1.8)	45	(1.8)	45	(1.8)	40	(1.6)	N/P	N/P	
Lifting Height mm (in)	3,000	(118.1)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Front Tread mm (in)	1,000	(39.4)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Rear Tread mm (in)	980	(38.6)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P	
Wheelbase mm (in)	1,700	(66.9)	1,730	(68.1)	1,650	(65.0)	1,500	(59.1)	1,600	(63.0)	

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.