



Forklifts	RHINO RFL200-LPG		Cat GP20N		Toyota 8FGCU20		Komatsu FG20ST-16		Doosan GC20SC-5	
General										
Brand	Rhino		Caterpillar		Toyota		Komatsu		Doosan	
Model	RFL200-G LPG		GP20N		8FGCU20		FG20ST-16		GC20SC-5	
Rated Capacity kg (lb)	2,000	(4,409)	2,000	(4,409)	2,000	(4,409)	2,000	(4,409)	2,000	(4,409)
Overall Height (mast raised) mm (in)	4,080	(161)	4,650	(183)	N/P	N/P	4,460	(176)	N/P	N/P
Net Horsepower kW (hp)	41	(55)	42.0	(56)	38	(51)	42	(56)	34	(46)
Operating Weight kg (lb)	3,320	(7,319)	3,310	(7,297)	3,240	(7,143)	3,320	(7,319)	3,085	(6,801)
Engine										
Make	RHINO/Nissan		CAT		Toyota		GCT		N/P	
Model	BR491/K25		K21LE		4Y-ECS		K21		G424IE	
Net Horsepower kW (hp)	41	(55)	42.0	(56)	38	(51)	42	(56)	34	(46)
Piston Displacement L (cu. In)	2.0	(122)	2.5	(153)	2.2	(134)	2.5	(153)	2.4	(146)
Rotating Speed (RPM)	2,800		2,700		2,250		2,700		2,450	
Drivetrain										
Work Speed with Load Kph (mph)	17	(10.6)	N/P	N/P	10.6	(6.6)	10.6	(6.6)	N/P	N/P
Work Speed with out Load Kph (mph)	19	(11.8)	19	(11.5)	N/P	N/P	10.6	(6.6)	18.0	(11.2)
Performance										
Rated Operating Capacity kg (lb)	3,320	(7,319)	3,310	(7,297)	3,240	(7,143)	3,320	(7,319)	3,085	(6,801)
Max. Lifting Speed with Load mm/s (in/s)	400	(16)	N/P	N/P	630	(25)	610	(24)	600	(24)
Max. Traction with Load kN(lbf)	14	(3,147)	N/P	N/P	3,240	N/P	19.3	(4,339)	N/P	N/P
Max. Traction without Load kN(lbf)	9	(2,023)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Gradeability with Load	25		30		36		N/P		N/P	
Gradeability without Load	51		N/P		N/P		36		29	
Dimensions										
Max. Height with Mast Lowered mm (in)	2,190	(86.2)	2,145	(84.4)	N/P	N/P	2,171	(85.5)	3,000	(118.1)
Overall Height Top of Cab mm (in)	2,165	(85.2)	2,145	(84.4)	2,050	(80.7)	2,054	(80.9)	N/P	N/P
Overall Length mm (in)	3,485	(137.2)	3,558	(140.1)	2,320	(91.3)	3,375	(132.9)	N/P	N/P
Overall Width mm(in)	1,160	(45.7)	1,150	(45.3)	1,064	(41.9)	1,070	(42.1)	991	(39.0)
Fork Length mm (in)	1,070	(42.1)	1,070	(42.1)	N/P	N/P	1,070	(42.1)	1,050	(41.3)
Fork Width mm (in)	100	(3.9)	100	(3.9)	N/P	N/P	100	(3.9)	100	(3.9)
Fork Thickness mm (in)	40	(1.6)	40	(1.6)	N/P	N/P	40	(1.6)	35	(1.4)
Lifting Height mm (in)	3,000	(118.1)	N/P	N/P	N/P	N/P	3,250	(128.0)	N/P	N/P
Front Tread mm (in)	970	(38.2)	N/P	N/P	N/P	N/P	880	(34.6)	N/P	N/P
Rear Tread mm (in)	970	(38.2)	N/P	N/P	N/P	N/P	900	(35.4)	N/P	N/P
Wheelbase mm (in)	1,640	(64.6)	1,600	(63.0)	N/P	N/P	1,400	(55.1)	1,225	(48.2)

Forklifts	RHINO RFL300-LPG		Cat GP30N		Toyota 8FGU30		Komatsu FG30HT-16		Doosan GC30E-5	
General										
Brand	Rhino		Caterpillar		Toyota		Komatsu		Doosan	
Model	RFL300-GLPG		GP30N		8FGU30		FG30HT-16		GC30E-5	
Rated Capacity kg (lb)	3,000	(6,614)	3,000	(6,614)	2,700	(5,952)	2,722	(6,001)	3,000	(6,614)
Overall Height (mast raised) mm (in)	4,250	(167)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Net Horsepower kW (hp)	41	(55)	38	(51)	42	(56)	45	(60)	48	(64)
Operating Weight kg (lb)	4,250	(9,370)	4,360	(9,612)	4,210	(9,281)	4,266	(9,405)	4,180	(9,215)
Engine										
Make	RHINO/Nissan		N/P		N/P		N/P		N/P	
Model	BR491/K25		S4S-DPB		N/P		N/P		G424IE	
Net Horsepower kW (hp)	41	(55)	38	(51)	42	(56)	45	(60)	48	(64)
Piston Displacement L (cu. In)	2.0	(122)	3.3	(201)	N/P	N/P	N/P	N/P	N/P	N/P
Rotating Speed (RPM)	2,800		2,300		2,700		2,700		2,600	
Drivetrain										
Work Speed with Load Kph (mph)	18	(11.2)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Work Speed with out Load Kph (mph)	20	(12.4)	19	(11.5)	19	(11.5)	19	(11.5)	16.0	(9.9)
Performance										
Rated Operating Capacity kg (lb)	4,250	(9,370)	4,360	(9,612)	4,210	(9,281)	4,266	(9,405)	4,180	(9,215)
Max. Lifting Speed with Load mm/s (in/s)	400	(16)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Max. Traction with Load kN(lbf)	15.5	(3,485)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Max. Traction without Load kN(lbf)	10.5	(2,360)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Gradeability with Load	15		30		27		27		N/P	
Gradeability without Load	20		N/P		N/P		N/P		29	
Dimensions										
Max. Height with Mast Lowered mm (in)	2,230	(87.8)	2,165	(85)	2,165	(85)	N/P	N/P	2,333	(91.9)
Overall Height Top of Cab mm (in)	2,190	(86.2)	N/P	N/P	N/P	N/P	2,159	(85.0)	2,130	(83.9)
Overall Length mm (in)	3,810	(150.0)	3,795	(149)	2,780	(109.4)	3,795	(149)	4,480	(176)
Overall Width mm(in)	1,230	(48.4)	1,150	(45.3)	1,240	(48.8)	1,230	(48.4)	1,110	(43.7)
Fork Length mm (in)	1,220	(48.0)	1,070	(42)	1,070	(42)	1,070	(42)	1,050	(41.3)
Fork Width mm (in)	125	(4.9)	100	(3.9)	125	(4.9)	100	(3.9)	125	(4.9)
Fork Thickness mm (in)	45	(1.8)	40	(2)	45	(2)	40	(2)	45	(1.8)
Lifting Height mm (in)	3,000	(118.1)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Front Tread mm (in)	1,000	(39.4)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Rear Tread mm (in)	970	(38.2)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Wheelbase mm (in)	1,750	(68.9)	1,600	(63.0)	1,700	(66.9)	1,720	(67.7)	1,410	(55.5)

Forklifts	RHINO RFL350-LPG		Cat GP35N		Toyota 8FGU32		Komatsu FG32HT-16		Doosan GC33P-5	
General										
Brand	Rhino		Caterpillar		Toyota		Komatsu		Doosan	
Model	RFL350-GLPG		GP35N		8FGU32		FG32HT-16		GC33P-5	
Rated Capacity kg (lb)	3,500	(7,716)	3,500	(7,716)	3,000	(6,614)	3,000	(6,614)	3,000	(6,614)
Overall Height (mast raised) mm (in)	4,250	(167)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Net Horsepower kW (hp)	41	(55)	38	(51)	42	(56)	45	(60)	48	(64)
Operating Weight kg (lb)	4,550	(10,031)	4,770	(10,516)	4,320	(9,524)	4,441	(9,791)	4,180	(9,215)
Engine										
Make	RHINO/Nissan		N/P		Toyota		GCT		N/P	
Model	BR491/K25		S4S-DPB		4Y-ECS		K25		G424IE	
Net Horsepower kW (hp)	41	(55)	38	(51)	42	(56)	45	(60)	48	(64)
Piston Displacement L (cu. In)	2.0	(122)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Rotating Speed (RPM)	2,800		2,300		2,570		2,700		2,550	
Drivetrain										
Work Speed with Load Kph (mph)	17	(10.6)	N/P	N/P	N/P	N/P	17	(10.6)	N/P	N/P
Work Speed with out Load Kph (mph)	19	(11.8)	19	(11.5)	18	(11.2)	19	(11.5)	16.0	(9.9)
Performance										
Rated Operating Capacity kg (lb)	4,550	(10,031)	4,770	(10,516)	4,320	(9,524)	4,441	(9,791)	4,180	(9,215)
Max. Lifting Speed with Load mm/s (in/s)	375	(15)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Max. Traction with Load kN(lbf)	16.0	(3,597)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Max. Traction without Load kN(lbf)	11.0	(2,473)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Gradeability with Load	15		20		26		27		N/P	
Gradeability without Load	20		N/P		21		N/P		29	
Dimensions										
Max. Height with Mast Lowered mm (in)	2,230	(87.8)	2,300	(91)	3,345	(132)	2,230	(87.8)	2,368	(93.2)
Overall Height Top of Cab mm (in)	2,190	(86.2)	N/P	N/P	N/P	N/P	N/P	N/P	2,130	(83.9)
Overall Length mm (in)	3,835	(151.0)	3,860	(152)	2,800	(110.2)	3,835	(151.0)	4,480	(176)
Overall Width mm(in)	1,230	(48.4)	1,290	(50.8)	1,240	(48.8)	N/P	N/P	1,110	(43.7)
Fork Length mm (in)	1,220	(48.0)	1,070	(42)	1,070	(42)	1,070	(42.1)	1,050	(41.3)
Fork Width mm (in)	125	(4.9)	125	(4.9)	125	(4.9)	125	(4.9)	125	(4.9)
Fork Thickness mm (in)	50	(2.0)	45	(2)	45	(2)	50	(2.0)	45	(1.8)
Lifting Height mm (in)	3,000	(118.1)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Front Tread mm (in)	1,000	(39.4)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Rear Tread mm (in)	970	(38.2)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Wheelbase mm (in)	1,750	(68.9)	1,700	(66.9)	1,700	(66.9)	1,700	(66.9)	1,410	(55.5)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.