



Mining Truck		Rhino RMT60		SDLG MT60	
General					
Brand	Rhino		SDLG		
Model	RMT60		MT60		
Rated Horsepower kW (hp)	309	(414)	276	(370)	
Nominal Payload Capacity kg (lb)	60,000	(132,277)	60,000	(132,277)	
Engine					
Engine Model	WD60		WD12.375		
Rated Horsepower kW (hp)	309	(414)	276	(370)	
Engine Type	Water Cooled, 4 Cycle		Water Cooled, 4 Cycle		
Aspiration	Turbocharged, Aftercooled		Turbo-charged		
Number of Cylinders	6		6		
Bore x Stroke mm (in)	125 x 147	(4.9 x 5.8)	126 x 155	(4.9 x 6.1)	
Piston Displacement L (cu. In)	12	(732)	11.6	(708)	
Governor Type	Electronically Controlled		N/P		
Max Torque Nm (lb-ft)	1,820	(1,342)	1,500	(1,106)	
Fan Drive for Radiator Cooling	Belt		Mechanical		
Fuel System	Direct Injection		Direct Injection		
Air Cleaner	Dry Type Dual Element and Precleaner, Oil Bath Elements (Optional)		Dry type with double elements and precleaner, plus dust indicator		
Emission Certificaion	Euro II		Euro 2		



Drivetrain				
Transmission Type	Powershift		Powershift	
Number of Speeds (Fwd/Rev)	7/1		9/2	
Max. Speed (Fwd) kph (mph)	68	(42)	41	(25)
Tires				
Tires	14.00-R25		13.00-25	
Dump Body				
Dump Body Capacity m3 (cu. Yd)	27	(35)	26	(34)
Payload kg (lb)	60,000	(132,277)	60,000	(132,277)
Dump Body Structure	Box Type		Box Type	
Dimensions				
Overall Length mm (ft)	8,780	(28.8)	8,560	(28.1)
Overall Width mm (ft)	3,354	(11.0)	3,240	(10.6)
Overall Height mm (ft)	3,620	(11.9)	3,970	(13.0)
Approach Angle	34 degrees		27 degrees	
Departure Angle	47 degrees		40 degrees	
Gradeability	27 degrees		20 degrees	
Min. Turning Radius mm (ft)	11,000	(36.1)	11,000	(36.1)
Ground Clearance mm (in)	390	(15.4)	362	(14.3)
Refill Capacities				
Fuel Tank L (Gal)	500	(132)	400	(106)

N/P = Not Published



www.rhinoeq.com