



| Pipelayer  | RHINO RPL45                               |          | CAT PL72                                  |          | DRESSTA SB-30                             |          | VOLVO PL3005                              |           |
|--|---|----------|---|----------|---|----------|---|-----------|
| <b>General</b>   |   |          |   |          |   |          |   |           |
| Brand  | Rhino                                     |          | Caterpillar                               |          | DRESSTA                                   |          | Volvo                                     |           |
| Model  | RPL45                                     |          | PL72                                      |          | SB-30                                     |          | PL3005                                    |           |
| Shoe (No Choice Spec Arrang) mm (in)   | 610                                       | (24.0)   | 760                                       | (29.9)   | 711                                       | (28.0)   | 600                                       | (23.6)    |
| Net Horsepower kw (hp)   | 169                                       | (227)    | 158                                       | (212)    | 140                                       | (188)    | 179                                       | (240)     |
| Operating Weight kg (lb)   | 34,000                                    | (74,957) | 31,278                                    | (68,956) | 27,580                                    | (60,803) | 35,030                                    | (77,228)  |
| <b>Engine</b>  |   |          |   |          |   |          |   |           |
| Engine Make (optional)   | Cummins (Rhino)                           |          | CAT                                       |          | Cummins                                   |          | Volvo                                     |           |
| Engine Model   | NT855                                     |          | C9.3 ACERT                                |          | QSB 6.7                                   |          | D8J                                       |           |
| Engine Type  | 4 Cycle, Water - Cooled, Direct Injection |          | 4 Cycle, Water - Cooled, Direct Injection |          | 4 Cycle, Water - Cooled, Direct Injection |          | 4 Cycle, Water - Cooled, Direct Injection |           |
| Aspiration   | Turbocharged                              |          | Turbocharged                              |          | Turbocharged                              |          | Turbocharged                              |           |
| Number of Cylinders  | 6   |          | 6   |          | 6   |          | 6   |           |
| <b>Undercarriage</b>   |   |          |   |          |   |          |   |           |
| Track Roller Type  | Lifetime Lubrication                      |          | Sealed and Lubricated                     |          | N/P                                       |          | Sealed and Lubricated                     |           |
| Number of track Rollers  | 8   |          | 8   |          | 8   |          | 8   |           |
| Number of Carrier Rollers  | 2   |          | 1   |          | N/P                                       |          | 2   |           |
| Type of Shoes  | Singel Grouser                            |          | N/P                                       |          | N/P                                       |          | Singel Grouser                            |           |
| Number of Shoes per Side   | 45  |          | 45  |          | 43  |          | 45  |           |
| Grouser Height mm (in)   | 60  | (2.4)    | N/P                                       | N/P      | N/P                                       | N/P      | N/P                                       | N/P       |
| <b>Hydraulics</b>  |   |          |   |          |   |          |   |           |
| Hydraulic Type   | Closed-Center                             |          | N/P                                       |          | N/P                                       |          | Variable Displacement                     |           |
| Hydraulic Pump Type  | Gear                                      |          | N/P                                       |          | N/P                                       |          | Axial Pistons                             |           |
| Hydraulic Pump Capacity L/min (gpm)  | 450                                       | (119)    | N/P                                       | N/P      | N/P                                       | N/P      | 526                                       | (139)     |
| Relief Valve Setting Mpa (psi)   | 20  | (2,901)  | N/P                                       | N/P      | N/P                                       | N/P      | N/P                                       | N/P       |
| <b>Pipelayer Boom</b>  |   |          |   |          |   |          |   |           |
| Max. Lifting Capacity kg (lb)  | 45,000                                    | (99,208) | 40,823                                    | (89,999) | 33,000                                    | (72,753) | 51,000                                    | (112,436) |
| <b>Dimensions</b>  |   |          |   |          |   |          |   |           |
| Max. Lifting Height mm (ft)  | 5,250                                     | (17.2)   | 8,010                                     | (26.3)   | N/P                                       | N/P      | N/P                                       | N/P       |
| Overall Height mm (ft)   | 3,360                                     | (11.0)   | 2,600                                     | (8.5)    | 3,520                                     | (11.5)   | 3,273                                     | (10.7)    |
| Height to Top of Exhaust Stack mm (ft)   | 3,120                                     | (10.2)   | 3,430                                     | (11.3)   | 3,420                                     | (11.2)   | N/P                                       | N/P       |
| Overall Length mm (ft)   | 4,750                                     | (15.6)   | 4,780                                     | (15.7)   | 4,400                                     | (14.4)   | 4,968                                     | (16.3)    |
| Overall Width (Shipping) mm (ft)   | 3,700                                     | (12.1)   | 3,050                                     | (10.0)   | 3,210                                     | (10.5)   | 3,190                                     | (10.5)    |
| Ground Clearance mm (in)   | 400                                       | (15.7)   | N/P                                       | N/P      | N/P                                       | N/P      | 542                                       | (21.3)    |
| <b>Capacity</b>  |   |          |   |          |   |          |   |           |
| Coolant L (gal)  | 40  | (11)     | 51  | (13)     | 40  | (11)     | N/P                                       | N/P       |
| Fuel Tank L (gal)  | 350                                       | (92)     | 415                                       | (110)    | 316                                       | (83)     | N/P                                       | N/P       |
| Engine L (gal)   | 22  | (6)      | 25  | (7)      | 23  | (6)      | N/P                                       | N/P       |
| Hydraulics L (gal)   | 100                                       | (26)     | 100                                       | (26)     | 115                                       | (30)     | N/P                                       | N/P       |
| Final Drives, Each L (gal)   | 60  | (16)     | 14  | (4)      | 38  | (10)     | N/P                                       | N/P       |
| Power Train L (gal)  | 90  | (24)     | 148                                       | (39)     | N/P                                       | N/P      | N/P                                       | N/P       |
| Equipment specifications and images may change without notice from Rhino Equipment Group Inc.  |   |          |   |          |   |          |   |           |
| Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment. |   |          |   |          |   |          |   |           |