



Pneumatic Rollers										
	Rhino RPR109		Cat CW34		Hamm HP280i		Bomag BW 24 RH		Dynapac CP2700	
Engine										
Brand (optional)	Cummins (Rhino)		Cat		Deutz		Deutz		Cummins	
Model	4BT3.9		C4.4B Acert		TCD 2012 L04 2V		TCD 2012 L04 2V		QSB 4.5	
Emission Rating (optional)	Tier 2 (3/4)		Tier 4		Tier 3		Tier 3		Tier 4	
Displacement L (in3)	3.9	(238)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Net Horsepower kW (hp)	73.5	(99)	98	(131)	85	(114)	75	(101)	85	(114)
Transmission										
Transmission Type	Hydrostatic		N/P		N/P		N/P		Hydrostatic	
Wheels and Tires / Trackplates										
Tire Size	11.0 R20		11.0 R20		11.00-R20		11.00-20 18PR		11.0 R20	
Number of Wheels	9		8		8		8		9	
Dimensions										
Overall Length mm (ft)	4,847	(15.9)	5,350	(17.6)	4,970	(16.3)	4,940	(16.2)	5,480	(18.0)
Overall Height mm (ft)	3,103	(10.2)	3,000	(9.8)	3,000	(9.8)	3,090	(10.1)	2,990	(9.8)
Overall Width mm (ft)	2,290	(7.5)	2,090	(6.9)	2,166	(7.1)	2,042	(6.7)	2,332	(7.7)
Wheelbase mm (ft)	3,797	(12.5)	3,900	(12.8)	N/P	N/P	3,700	(12.1)	4,300	(14.1)
Steering Angle	35 degrees		N/P		N/P		N/P		N/P	
Inside Turning Radius mm (ft)	5,200	(17.1)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Outside Turning Radius mm (ft)	7,500	(24.6)	N/P	N/P	N/P	N/P	N/P	N/P	9,046	(29.7)
Capacities										
Fuel Tank L (gal)	250	(66)	270	(71)	235	(62)	250	(66)	210	(55)
Water Tank L (gal)	800	(211.3)	N/P	N/P	650	(171.7)	N/P	N/P	N/P	N/P
Performance										
Ballast Type	Water / Stand		Steel / Sand		N/P		Steel / Sand		N/P	
Ballast Volume m3 (ft3)	4	(137.7)	N/P	N/P	N/P	N/P	4	(123.6)	N/P	N/P
Travel Speed Kph (mph)	14	(9)	19	(12)	19	(12)	20	(12)	20	(12)
Oscillation Angle	5 degrees		N/P		N/P		N/P		N/P	
Weights										
Operating weight kg (lb)	10,000	(22,046)	10,000	(22,046)	10,500	(23,149)	8,800	(19,401)	12,400	(27,337)
Max. Operating Weight kg (lb)	16,000	(35,274)	27,000	(59,525)	27,960	(61,641)	24,000	(52,911)	27,000	(59,525)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.