



Pneumatic Rollers					
General	Rhino RPR1611		Dynapac CP275		
Brand (optional)	Cummins (Rhino)		Cummins		
Model	6BT5.9		4BTAA3.9		
Emission Rating (optional)	Tier 2 (3/4)		N/P		
Displacement L (in3)	6	(360)	N/P	N/P	
Net Horsepower kW (hp)	110	(148)	97	(130)	
Transmission	Hydrostatic		Hydrostatic		
Wheels and Tires / Trackplates	11.0 R20		11.0 R20		
Tire Size	11		11		
Number of Wheels	35 degrees		N/P		
Dimensions	5,400		N/P		
Overall Length mm (ft)	4,847	(15.9)	5,310	(17.4)	
Overall Height mm (ft)	3,103	(10.2)	3,080	(10.1)	
Overall Width mm (ft)	2,790	(9.2)	2,370	(7.8)	
Wheelbase mm (ft)	3,667	(12.0)	4,250	(13.9)	
Steering Angle	7,710		9,000		
Inside Turning Radius mm (ft)	7,710	(25.3)	9,000	(29.5)	
Outside Turning Radius mm (ft)	Capacities	250		320	
Fuel Tank L (gal)	250	(66)	320	(85)	
Water Tank L (gal)	800	(211.3)	N/P	N/P	
Performance	Water / Stand		Water / Steel / Sand		
Ballast Type	3.2	(113.0)	N/P	N/P	
Ballast Volume m3 (ft3)	20	(12)	18	(11)	
Travel Speed Kph (mph)	5 degrees		N/P		
Oscillation Angle	Weights	16,000		14,000	
Operating weight kg (lb)	16,000	(35,274)	14,000	(30,865)	
Max. Operating Weight kg (lb)	26,000	(57,320)	30,000	(66,139)	
Equipment specifications and images may change without notice from Rhino Equipment Group Inc.					
Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.					