



RHINO EQUIPMENT



Pneumatic Rollers	Rhino RPR2011		Hamm GRW 24		Tiangong YL30		Bomag BW 27RH4i	
Engine	Cummins		Deutz		Cummins		Deutz	
Manufacturer	Cummins		Deutz		Cummins		Deutz	
Model	6BT5		TCD 2012 L04		6BTA5.9		TCD4.1 L04	
Emission Rating	Tier 2		Tier 3		N/P		Interim Tier 4	
Displacement L (in3)	5.9	(360)	N/P	N/P	5.9	(360)	4.1	N/P
Gross Engine Output kW (hp)	110	(148)	85	(114)	128	(172)	95	(127)
Transmission	Hydrostatic		Hydrostatic		N/P		Hydrostatic	
Transmission Type	Hydrostatic		Hydrostatic		N/P		Hydrostatic	
Wheels and Tires / Trackplates	11.0 R20		11.0 R20		11.0 - 20		11.0 - 20	
Tire Size	11.0 R20		11.0 R20		11.0 - 20		11.0 - 20	
Dimensions	4,847 (16)		4,745 (16)		5,000 (16)		4,940 (16)	
Overall Length mm (ft)	4,847 (16)		4,745 (16)		5,000 (16)		4,940 (16)	
Overall Height mm (ft)	3,103 (10)		3,355 (11)		3,200 (10)		3,090 (10)	
Overall Width mm (ft)	2,790 (9)		1,986 (7)		2,895 (9)		2,098 (7)	
Wheelbase mm (ft)	3,865 (13)		3,595 (12)		N/P N/P		3,700 (12)	
Steering Angle	35 degrees		30 degrees		N/P		N/P	
Inside Turning Radius mm (ft)	6,100 (20)		5,900 (19)		N/P N/P		N/P N/P	
Outside Turning Radius mm (ft)	8,000 (26)		N/P N/P		9,000 (30)		5,320 (17)	
Capacities	300 (79)		198 (52)		150 (40)		250 (66)	
Fuel Tank L (gal)	300 (79)		198 (52)		150 (40)		250 (66)	
Tank Capacity for Tires L (gal)	800 (211)		750 (198)		N/P N/P		N/P N/P	
Performance	Water/Sand		N/P		N/P		N/P	
Ballast Type	Water/Sand		N/P		N/P		N/P	
Ballast Volume m3 (ft3)	3.2 (113)		N/P N/P		N/P N/P		N/P N/P	
Travel Speed kph (mph)	20.5 (12.7)		21.2 (13.2)		16.0 (9.9)		7.1 (4.4)	
Oscillation Angle	5 degrees		4 degrees		N/P		N/P	
Weights	30,000 (66,139)		28,000 (61,729)		30,000 (66,139)		27,000 (59,525)	
Max. Operating Weight kg (lbs)	30,000 (66,139)		28,000 (61,729)		30,000 (66,139)		27,000 (59,525)	

N/P=Not Published



www.rhinoeq.com