



SKID STEERS	RHINO RS50-S		BOBCAT S550		Cat 226 D		John Deere 318E		VOLVO MC85C	
<b>General</b>										
Brand	Rhino		Bobcat		Caterpillar		John Deere		Volvo	
Model	RS 50-S		S550		226 D		318E		MC85C	
Rated Operating Capacity kg (lb)	1,060	(2,337)	894	(1,971)	703	(1,550)	885	(1,951)	795	(1,753)
Loader Type	Radial		Vertical		Vertical		Vertical		Vertical	
Operating Weight kg (lb)	3,100	(6,834)	2,841	(6,263)	2,588	(5,706)	3,178	(7,006)	3,093	(6,819)
<b>Engine</b>										
Make	Rhino		Kubota		Kubota		CAT		Yanmar	
Model	A498BPG		V3600		V2607DITE3BBC2		C2.2		4TNV98C	
Net Horsepower kW (hp)	45	(60)	63	(84)	45	(60)	49	(66)	48	(64)
Piston Displacement L (cu. In)	3.2		(195)		N/A		N/A		2.2	
Rotating Speed (RPM)	2,500		N/A		N/P		2,500		N/P	
Alternator (A)	50		N/A		N/A		N/A		100	
<b>Drivetrain</b>										
Work Speed Kph (mph)	11	(6.8)	17	(10.6)	13	(7.9)	11	(6.8)	12	(7.5)
Max Speed Kph (mph)	11	(7.0)	11	(6.8)	18	(11.2)	16	(10.1)	19	(11.5)
<b>Hydraulics</b>										
Pump Flow ltr/min (gpm)	64	(17)	64	(17)	N/A	N/A	68	(18)	70	(18)
High Pump Flow Option ltr/min (gpm)	100	(26)	101	(27)	N/A	N/A	95	(25)	100	(26)
Relief Valve Setting Mpa (psi)	16	(2,321)	24	(3,481)	23	(3,336)	22	(3,162)	23	(3,336)
Lever Control (Standard)	Manual H/F		N/P		N/P		N/P		N/P	
<b>Performance</b>										
Rated Operating Capacity kg (lb)	1,060	(2,337)	894	(1,971)	703	(1,550)	885	(1,951)	795	(1,753)
Tipping Load kg (lb)	1,100	(2,425)	1,788	(3,942)	1,406	(3,100)	1,771	(3,904)	1,590	(3,505)
Bucket Capacity m3 (cu. Yd)	0.47	(0.61)	N/A	N/A	N/P	N/P	N/P	N/P	N/P	N/P
Operating Weight kg (lb)	3,100	(6,834)	2,841	(6,263)	2,588	(5,706)	3,178	(7,006)	3,093	(6,819)
<b>Dimensions</b>										
Max. Height mm (ft)	3,970	(13.0)	3,787	(12.4)	3,657	(12.0)	N/A	N/A	3,000	(9.8)
Dump Height mm (ft)	2,100	(6.9)	2,205	(7.2)	N/A	N/A	2,430	(8.0)	2,260	(7.4)
Height Top of Cab mm (ft)	2,090	(6.9)	1,972	(6.5)	2,032	(6.7)	1,980	(6.5)	1,980	(6.5)
Overall Length with Bucket mm (ft)	3,525	(11.6)	3,378	(11.1)	3,225	(10.6)	3,470	(11.4)	3,530	(11.6)
Bucket Width mm (ft)	1,800	(5.9)	1,727	(5.7)	N/P	N/P	N/P	N/P	1,680	(5.5)
Overall Width to Outside of Tire mm (ft)	1,720	(5.6)	1,643	(5.4)	1,525	(5.0)	1,610	(5.3)	1,600	(5.2)
Ground Clearance mm (in)	210	(8.3)	185	(7.3)	178	(7.0)	217	(8.5)	210	(8.3)
Clearance Circle - Front mm (ft)	2,090	(6.9)	N/A	N/A	N/A	N/A	N/A	N/A	2,090	(6.9)
Clearance Circle - Rear mm (ft)	1,578	(5.2)	N/A	N/A	N/A	N/A	N/A	N/A	1,650	(5.4)
Height to Bucket Hinge Pin mm (ft)	3,970	(13.0)	3,787	(12.4)	N/A	N/A	3,050	(10.0)	3,000	(9.8)
Wheelbase mm (ft)	991	(3.3)	1,082	(3.5)	1,066	(3.5)	1,130	(3.7)	1,070	(3.5)
<b>Maintenance</b>										
Refill Capacity - Coolant L (Gal)	10	(2.6)	N/A	N/A	N/A	N/A	N/P	N/P	10	(2.6)
Refill Capacity - Fuel Tank L (Gal)	60	(15.9)	93	(24.6)	58	(15.3)	76	(20.1)	92	(24.3)
Refill Capacity - Engine L (Gal)	7	(1.8)	N/A	N/A	N/A	N/A	N/P	N/P	10	(2.6)
Refill Capacity - Hydraulics L (Gal)	60	(15.9)	N/A	N/A	N/A	N/A	N/P	N/P	44	(11.5)
Refill Capacity - Chain Cases L (Gal)	13	(3.4)	N/A	N/A	N/A	N/A	N/P	N/P	N/P	N/P

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.