



Skid Steers	RHINO RS 60-S		BOBCAT S630		Cat 242 D		John Deere 326E		Volvo MC110C	
General										
Brand	Rhino		Bobcat		Caterpillar		John Deere		Volvo	
Model	RS 60		S630		242D		326E		MC110C	
Rated Operating Capacity kg (lb)	1,300	(2,866)	1,040	(2,293)	975	(2,150)	1,294	(2,853)	1,021	(2,251)
Loader Type	Radial		Radial		Vertical		Radial		Radial	
Operating Weight kg (lb)	3,520	(7,760)	3,452	(7,610)	3,166	(6,980)	3,723	(8,208)	3,608	(7,954)
Engine										
Make	Rhino		Bobcat		CAT		Yanmar		Volvo	
Model	A498BPG		D24		C3.3B		4TNV98CT		TCAE-55	
Net Horsepower kW (hp)	56	(75)	56	(75)	55	(74)	54	(72)	63	(84)
Piston Displacement L (cu. In)	3.2	(195)	2	(140)	2	(122)	3.3	(201)	4.3	(262)
Rotating Speed (RPM)	2,500		N/P		1,500		2,500		2,200	
Alternator (A)	50		N/P		N/P		70		95	
Drivetrain										
Work Speed Kph (mph)	11	(6.8)	11	(6.5)	12	(7.5)	11	(6.8)	11	(6.8)
Max Speed Kph (mph)	18	(11.2)	N/P	N/P	18	(11.2)	18	(11.2)	20	(12.4)
Hydraulics										
Pump Flow ltr/min (gpm)	78	(21)	87	(23)	N/A	N/A	80	(21)	90	(24)
High Pump Flow Option ltr/min (gpm)	95	(25)	115	(30)	N/A	N/A	125	(33)	125	(33)
Relief Valve Setting Mpa (psi)	20	(2,901)	24	(3,481)	20	(2,901)	24	(3,452)	N/A	N/A
Lever Control (Standard)	Manual H/F		N/A		N/A		N/A		N/P	
Performance										
Rated Operating Capacity kg (lb)	1,300	(2,866)	1,040	(2,293)	975	(2,150)	1,294	(2,853)	1,021	(2,251)
Tipping Load kg (lb)	2,206	(4,863)	2,079	(4,583)	1,950	(4,299)	2,452	(5,406)	2,226	(4,907)
Operating Weight kg (lb)	3,520	(4,604)	3,452	(4,515)	3,166	(4,141)	3,723	(4,870)	3,608	(4,719)
Dimensions										
Max. Height mm (ft)	3,919	(12.9)	3,950	(13.0)	N/A	N/A	N/P	N/P	N/P	N/P
Dump Height mm (ft)	2,480	(8.1)	2,367	(7.8)	N/A	N/A	2,540	(8.3)	2,460	(8.1)
Height Top of Cab mm (ft)	2,065	(6.8)	2,065	(6.8)	2,108	(6.9)	2,120	(7.0)	2,090	(6.9)
Overall Length with Bucket mm (ft)	3,539	(11.6)	3,474	(11.4)	3,479	(11.4)	3,930	(12.9)	3,690	(12.1)
Bucket Width mm (ft)	1,855	(6.1)	1,880	(6.2)	N/P	N/P	N/A	N/A	1,829	(6.0)
Overall Width to Outside of Tire mm (ft)	1,784	(5.9)	1,832	(6.0)	N/P	N/P	1,840	(6.0)	1,820	(6.0)
Ground Clearance mm (in)	223	(8.8)	207	(8.1)	228	(9.0)	254	(10.0)	238	(9.4)
Clearance Circle - Front mm (ft)	2,127	(7.0)	N/P	N/P	N/A	N/A	N/P	N/P	N/P	N/P
Clearance Circle - Rear mm (ft)	1,460	(4.8)	N/P	N/P	N/A	N/A	N/P	N/P	N/P	N/P
Height to Bucket Hinge Pin mm (ft)	3,165	(10.4)	3,073	(10.1)	3,073	(10.1)	3,180	(10.4)	3,175	(10.4)
Wheelbase mm (ft)	1,197	(3.9)	1,150	(3.8)	1,117	(3.7)	1,230	(4.0)	1,242	(4.1)
Maintenance										
Refill Capacity - Coolant L (Gal)	10	(2.7)	N/A	N/A	N/A	N/A	6.2	(1.6)	N/A	N/A
Refill Capacity - Fuel Tank L (Gal)	100	(26.4)	90	(23.8)	105	(27.7)	66	(17.4)	103	(27.2)
Refill Capacity - Engine L (Gal)	7	(1.8)	N/A	N/A	N/A	N/A	9	(2.4)	N/A	N/A
Refill Capacity - Hydraulics L (Gal)	90	(23.8)	N/A	N/A	N/A	N/A	19	(5.0)	N/A	N/A
Refill Capacity - Chain Cases L (Gal)	14	(3.7)	N/A	N/A	N/A	N/A	33	(8.7)	N/P	N/P

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.