



Skid Steers	RHINO RS70		Bobcat S770		CAT 272D2		John Deere 330G		GEHL V400		NEW HOLLAND L234		CASE SV340	
General														
Brand	Rhino		Bobcat		Caterpillar		John Deere		GEHL		New Holland		Case	
Model	RS70		S770		272D2		330G		V400		L234		SV340	
Rated Operating Capacity kg (lb)	1,600	(3,527)	1,520	(3,351)	1,542	(3,400)	1,362	(3,003)	1,814	(3,999)	1,542	(3,400)	1,542	(3,400)
Loader Type	Radial		Vertical		Vertical		Vertical		Verticle		Vertical		Verticle	
Net Horsepower kW (hp)	75	(100)	69	(92)	73	(98)	68	(91)	74	(99)	67	(90)	67	(90)
Operating Weight kg (lb)	4,260	(9,392)	4,225	(9,315)	3,977	(8,768)	4,495	(9,910)	5,034	(11,098)	4,045	(8,918)	4,136	(9,118)
Engine														
Make	Perkins		Bobcat		CAT		Yanmar		Cummins		FPT		FPT	
Model	1104D-44T		D34		C3.8 DIT		4TNV94FHT		QSB 4.5		F5H FL413		F5B FL413 E*B002	
Net Horsepower kW (hp)	75	(100)	69	(92)	73	(98)	68	(91)	74	(99)	67	(90)	67	(90)
Piston Displacement L (cu. In)	4.4	(269)	3.5	(214)	3.8	(232)	3.1	(189)	4.5	(275)	3.4	(207)	3.4	(207)
Rotating Speed (RPM)	2,200		2,400		N/P		2,500		2,200		2,500		2,500	
Alternator (A)	N/P		90		100		90		N/P		N/P		160	
Drivetrain														
Work Speed Kph (mph)	11	(6.8)	11.4	(7.1)	10.6	(6.6)	11.3	(7.0)	10.5	(6.5)	12.4	(7.7)	12.4	(7.7)
Max Speed Kph (mph)	20	(12.7)	19.8	(12.3)	15.1	(9.4)	19.3	(12.0)	18	(11.2)	18.5	(11.5)	18.6	(11.6)
Hvdraulics														
Pump Flow ltr/min (gpm)	88	(23)	87.1	(23)	86	(23)	80	(21)	121	(32)	91.5	(24)	91.5	(24)
High Pump Flow Option ltr/min (gpm)	158	(42)	138.5	(37)	121	(32)	138	(36)	154	(41)	142.5	(38)	146.5	(39)
Relief Valve Setting Mpa (psi)	16	(2,321)	24	(3,481)	23	(3,336)	23.79	(3,450)	24.13	(3,500)	23.79	(3,450)	23.79	(3,450)
Lever Control (Standard)	Hydraulic Joystick		ACS/SJC		N/P		N/P		N/P		3 Spool/ Open Center		3 Spool/ Open Center	
Performance														
Rated Operating Capacity kg (lb)	1,600	(3,527)	1,520	(3,351)	1,542	(3,400)	1,362	(3,003)	1,814	(3,999)	1,542	(3,400)	1,542	(3,400)
Tipping Load kg (lb)	N/P	N/P	3,137	(6,916)	3,084	(6,799)	3,084	(6,799)	3,629	(8,000)	3,084	(6,799)	3,084	(6,799)
Operating Weight kg (lb)	4,260	(5,572)	4,225	(9,315)	3,977	(8,768)	4,495	(9,910)	5,034	(11,098)	4,045	(8,918)	4,136	(9,118)
Dimensions														
Max. Height mm (ft)	4,234	(13.9)	4,232	(13.9)	4,067	(13.3)	N/P	N/P	4,745	(15.6)	4,199	(13.8)	4,180	(13.7)
Dump Height mm (ft)	2,710	(8.9)	2,649	(8.7)	2,438	(8.0)	2,690	(8.8)	2,916	(9.6)	2,655	(8.7)	2,560	(8.4)
Height Top of Cab mm (ft)	2,080	(6.8)	2,065	(6.8)	2,082	(6.8)	2,190	(7.2)	2,083	(6.8)	2,042	(6.7)	2,000	(6.6)
Overall Length with Bucket mm (ft)	3,666	(12.0)	3,597	(11.8)	3,954	(13.0)	3,710	(12.2)	4,026	(13.2)	3,760	(12.3)	3,760	(12.3)
Bucket Width mm (ft)	1,980	(6.5)	1,880	(6.2)	1,850	(6.1)	2,100	(6.9)	2,134	(7.0)	1,950	(6.4)	1,780	(5.8)
Overall Width to Outside of Tire mm (ft)	1,938	(6.4)	1,832	(6.0)	1,829	(6.0)	1,980	(6.5)	2,019	(6.6)	1,940	(6.4)	1,770	(5.8)
Ground Clearance mm (in)	240	(9.4)	207	(8.1)	226	(8.9)	250	(9.8)	185	(7.3)	243	(9.6)	200	(7.9)
Clearance Circle - Front mm (ft)	2,200	(7.2)	2,179	(7.1)	2,280	(7.5)	2,180	(7.2)	2,248	(7.4)	2,246	(7.4)	2,230	(7.3)
Clearance Circle - Rear mm (ft)	1,850	(6.1)	1,890	(6.2)	N/P	N/P	N/P	N/P	1,791	(5.9)	1,809	(5.9)	1,810	(5.9)
Height to Bucket Hinge Pin mm (ft)	3,355	(11.0)	3,353	(11.0)	3,122	(10.2)	3,350	(11.0)	3,647	(12.0)	3,327	(10.9)	3,300	(10.8)
Wheelbase mm (ft)	1,218	(4.0)	1,227	(4.0)	1,386	(4.5)	1,270	(4.2)	1,387	(4.6)	1,322	(4.3)	1,320	(4.3)
Maintenance														
Refill Capacity - Coolant L (Gal)	20	(5.3)	14	(3.8)	16	(4.2)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Refill Capacity - Fuel Tank L (Gal)	99	(26.2)	124	(32.8)	122	(32.2)	97	(25.5)	118	(31.2)	97	(25.5)	97	(25.5)
Refill Capacity - Engine L (Gal)	15	(4.0)	11	(3.0)	13	(3.4)	N/P	N/P	N/P	N/P	8.5	(2.2)	8.5	(2.2)
Refill Capacity - Hydraulics L (Gal)	55	(14.5)	47	(12.5)	55	(14.5)	N/P	N/P	63	(16.6)	45	(12.0)	45	(12.0)
Refill Capacity - Chain Cases L (Gal)	13	(3.4)	N/P	N/P	20.4	(5.4)	N/P	N/P	N/P	N/P	22	(5.9)	22	(5.9)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.