



Soil Compactors						
General	Rhino RSC223		Bomag BC462		CAT 815K	
Brand	Rhino		Bomag		Caterpillar	
Model	RSC223		BC462		815K	
Rated Output kW (HP)	147	(197)	190	(255)	185	(248)
Operational Weight Kg (lb)	23,000	(50,706)	21,300	(46,958)	22,386	(49,353)
Engine						
Model	Rhino		Deutz		Caterpillar	
Type	D6114		TCD2013 L06		C7.1 ACERT	
Total Exhaust Cylinder L (cu. In)	6.1	(372)	N/P	N/P	7	(427)
Rated Speed (rpm)	2,200		2,300		N/P	
Starting Type	Electric		Electric		Electric	
Specifications						
Drum Width, Front mm (ft)	1,040	(3.4)	900	(3.0)	991	(3.3)
Drum Width, Rear mm (ft)	835	(2.7)	900	(3.0)	991	(3.3)
Drum Diameter mm (ft)	1,500	(4.9)	1,580	(5.2)	1,425	(4.7)
Blades Per Wheel, Front	50		48		60	
Blades Per Wheel, Rear	40		48		60	
Blade Type	Straight		N/P		N/P	
Blade Width mm (ft)	3,000	(9.8)	3,600	(11.8)	3,761	(12.3)
Blade Height mm (ft)	1,650	(5.4)	N/P	N/P	860	(2.8)
Driving System						
Travel Speed kmh (mph)	10	(6.2)	14	(8.7)	17.6	(10.9)
Model	Hydrostatic Travel		Hydrostatic		Hydrostatic	
Type	Double Reduction				N/P	
System pressure Mpa (psi)	12	(1,740)	12	(1,740)	12	(1,740)
Dimensions						
Length mm (ft)	7,355	(24.1)	8,620	(28.3)	6,845	(22.5)
Height mm (ft)	3,600	(11.8)	3,390	(11.1)	3,347	(11.0)
Wheelbase mm (ft)	3,350	(11.0)	3,500	(11.5)	3,350	(11.0)
Width mm (ft)	3,000	(9.8)	3,600	(11.8)	3,791	(12.4)
Min. Ground Clearance mm (ft)	435	(1.4)	600	(2.0)	390	(1.3)
Capacity						
Fuel L (gal)	350	(92.5)	375	(99.1)	500	(132)
Engine Oil L (gal)	30	(7.9)	28	(7.3)	20	(5.3)
Oil Hydraulic L (gal)	110	(29.1)	280	(74.0)	75	(19.8)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.