



Soil Compactors				
General	Rhino RSC228		CAT 816K	
Brand	Rhino		Caterpillar	
Model	RSC228		816K	
Rated Output kW (HP)	187 (251)	216 (290)	212 (284)	
Operational Weight Kg (lb)	28,000	(61,729)	25,809	(56,899)
Engine				
Model	Rhino		Caterpillar	
Type (optional)	C6120 (C6121)		C7.1 ACERT	
Total Exhaust Cylinder L (cu. In)	8.0	(488)	7	(427)
Rated Speed (rpm)	2,200		N/P	
Starting Type	Electric		Electric	
Specifications				
Drum Width, Front mm (ft)	1,195	(3.9)	1,016	(3.3)
Drum Width, Rear mm (ft)	970	(3.2)	1,016	(3.3)
Drum Diameter mm (ft)	1,620	(5.3)	1,300	(4.3)
Blades Per Wheel, Front	50		20	
Blades Per Wheel, Rear	40		20	
Blade Type	Straight		Straight	
Blade Width mm (ft)	3,800	(12.5)	3,657	(12.0)
Blade Height mm (ft)	1,880	(6.2)	1,914	(6.3)
Driving System				
Travel Speed kmh (mph)	10.9	(6.8)	9.5	(5.9)
Model	Hydrostatic Travel		Hydrostatic	
Type	Double Reduction		N/P	
System pressure Mpa (psi)	13	(1,885)	15.5	(2,248)
Dimensions				
Length mm (ft)	8,150	(26.7)	7,854	(25.8)
Height mm (ft)	3,810	(12.5)	3,801	(12.5)
Wheelbase mm (ft)	3,500	(11.5)	3,350	(11.0)
Width mm (ft)	3,800	(12.5)	3,657	(12.0)
Min. Ground Clearance mm (ft)	490	(1.6)	456	(1.5)
Capacity				
Fuel L (gal)	480	(126.8)	500	(132)
Engine Oil L (gal)	45	(11.9)	20	(5.3)
Oil Hydraulic L (gal)	320	(84.5)	75	(19.8)
Equipment specifications and images may change without notice from Rhino Equipment Group Inc.				
Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.				