



TOWER CRANE		RHINO		POTAIN		COMEDIL TEREX		LIEBHERR		L. COMANSA	
General											
Brand		RHINO EQUIPMENT		POTAIN		COMEDIL TEREX		LIEBHERR		L. COMANSA	
Model		RTC5013		MCT 88		CTT 91-5 TS12		85 EC-B 5		11 LC 90	
Capacities											
Maximum lifting capacity tons (lb)		6	(12,000)	5	(10,000)	5	(10,000)	5	(10,000)	6	(12,000)
Maximum lifting capacity - at Jib nose tons (lb)		1.3	(2,600)	1.6	(3,200)	1.4	(2,800)	1.3	(2,600)	1.2	(2,400)
Dimensions											
Maximum Radius m (ft)		50	(164)	52	(171)	50	(164)	50	(164)	52	(171)
Standard Height m (ft)		40	(131)	39	(129)	36	(117)	45	(149)	32	(104)
Maximum Height m (ft)		140	(459)	200	(656)	186	(610)	140	(459)	140	(459)
Rear Swing Radius m (ft)		13	(42)	14	(45)	10	(34)	13	(41)	12	(39)
Radius of maximum capacity m (ft)		14	(45)	15	(49)	25	(82)	10	(33)	20	(66)
Engine											
Power (Kw)		18		18		15		22		24	
Voltage (V)		200 to 400		200 to 400		200 to 400		200 to 400		200 to 400	
Frequency (Hz)		50 or 60		51 or 60		50 or 60		50 or 60		50	
Relations											
Hoisting speed m/min (ft/min)		80	(262)	63	(207)	60	(197)	60	(197)	90	(295)
Working swing radius m (ft)		12	(40)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Max. Working wind speed m/s (ft/s)		20	(66)	25	(82)	22	(72)	25	(82)	20	(66)
Max. Wind speed for top Rising m/s (ft/s)		13	(43)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Max. Rising speed (r/min)		0.5		0.8		0.76		0.8		0.7	
Equipment specifications and images may change without notice from Rhino Equipment Group Inc.											
Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.											