



TOWER CRANE	RHINO		POTAIN		COMEDIL TEREX		L. COMANSA	
General	RHINO EQUIPMENT		POTAIN		COMEDIL TEREX		L. COMANSA	
Brand	RHINO EQUIPMENT		POTAIN		COMEDIL TEREX		L. COMANSA	
Model	RTC-5512		MDT 98		CTT 121/A-5		11 LC 132	
Capacities								
Maximum lifting capacity tons (lb)	8	(16,000)	6	(12,000)	5	(10,000)	6	(12,000)
Maximum lifting capacity - at Jib nose tons (lb)	1.2	(2,400)	1.2	(2,400)	1.8	(3,500)	1.2	(2,400)
Dimensions								
Maximum Radius m (ft)	55	(180)	55	(180)	55	(180)	60	(197)
Standard Height m (ft)	46	(151)	37.8	(124)	36	(117)	41	(134)
Maximum Height m (ft)	150	(492)	278	(912)	186	(610)	145	(476)
Rear Swing Radius m (ft)	11	(36)	13.64	(45)	11	(36)	12	(39)
Radius of maximum capacity m (ft)	11.2	(37)	11.08	(36)	30	(98)	20	(66)
Engine								
Power (Kw)	42.4		22		18		37	
Voltage (V)	200 to 400		200to 400		200 to 400		400	
Frequency (Hz)	50 or 60		50 or 60		50 or 60		50	
Relations								
Hoisting speed m/min (ft/min)	80	(262)	79	(259)	60	(197)	90	(295)
Working swing radius m (ft)	66	(216.5)	N/P	N/P	N/P	N/P	N/P	N/P
Max. Working wind speed m/s (ft/s)	25	(82)	N/P	N/P	24	(79)	20	(66)
Max. Wind speed for top Rising m/s (ft/s)	13	(43)	N/P	N/P	N/P	N/P	N/P	N/P
Max. Rising speed (r/min)	0.7		0.8		0.84		0.7	

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.