



TOWER CRANE	RHINO		POTAIN		COMEDIL TEREX		LIEBHERR		L. COMANSA	
General										
Brand	RHINO EQUIPMENT		POTAIN		COMEDIL TEREX		LIEBHERR		L. COMANSA	
Model	RTC-6014B		MDT 178		CTT 181/B-8 TS21		154 EC-H 10		11 LC 160	
Capacities										
Maximum lifting capacity tons (lb)	10	(20,000)	8	(16,000)	8	(16,000)	10	(20,000)	8	(16,000)
Maximum lifting capacity - at Jib nose tons (lb)	1.4	(2,800)	1.5	(3,000)	1.4	(2,800)	1.4	(2,800)	1.4	(2,800)
Dimensions										
Maximum Radius m (ft)	60	(197)	60	(197)	65	(213)	60	(197)	65	(213)
Standard Height m (ft)	46	(152)	42	(137)	45	(147)	63	(207)	41	(134)
Maximum Height m (ft)	200	(656)	200	(656)	228	(748)	180	(591)	120	(394)
Rear Swing Radius m (ft)	15	(48)	15	(48)	15	(50)	14	(46)	12	(39)
Radius of maximum capacity m (ft)	12	(38)	14	(47)	30	(98)	10	(33)	20	(66)
Engine										
Power (Kw)	25		22		30		37		24	
Voltage (V)	200 to 400		201 to 400		202 to 400		200 to 400		400	
Frequency (Hz)	50 or 60		51 or 60		52 or 60		50 or 60		50	
Relations										
Hoisting speed m/min (ft/min)	80	(262)	79	(259)	64	(210)	100	(328)	90	(295)
Working swing radius m (ft)	66	(217)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Max. Working wind speed m/s (ft/s)	25	(82)	N/P	N/P	24	(79)	25	(82)	N/P	N/P
Max. Wind speed for top Rising m/s (ft/s)	13	(43)	N/P	N/P	N/P	N/P	N/P	N/P	N/P	N/P
Max. Rising speed (r/min)	0.7		0.8		0.84		0.8		0.7	
Equipment specifications and images may change without notice from Rhino Equipment Group Inc.										
Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.										