



Track Loader		Rhino RTL17		Cat 963K		John Deere 755K	
<b>General</b>							
Brand	Rhino		Cat		John Deere		
Model	RTL17		963K		755K		
Shoe (No Choice Spec Arrang) mm (in)	560	(22)	550	(22)	N/P	N/P	
Net Horsepower kW (hp)	131	(176)	144	(193)	142	(190)	
Operating Weight, as Equipped kg (lb)	20,068	(44,242)	20,021	(44,139)	20,492	(45,177)	
<b>Engine</b>							
Engine Make	RHINO		CAT		JOHN DEERE		
Engine Model	C6121ZG57		C7.1 ACERT		PVX 6068		
Engine Type	4 Cycle, Water - Cooled, Direct Injection		N/P		4 Cycle, Water - Cooled, Direct Injection		
Aspiration	Turbocharged, Air-to-Air After Cooled		N/P		Turbocharged, Air-to-Air After Cooled		
Number of Cylinders	6		N/P		4		
Bore x Stroke mm (in)	121 x 152	(4.8 x 6)	105 x 135	(4.1 x 5.3)	105 x 127	(4.1 x 5)	
Piston Displacement L (cu. In)	9.7	(592)	7.0	(427)	6.8	(415)	
Fan Drive for Radiator Cooling	Belt Driven		N/P		N/P		
Fuel System	Direct Injection		N/P		N/P		
<b>Drivetrain</b>							
Drivetrain Type	Hydrostatic		Hydrostatic		N/P		
Number of Speeds (Fwd/Rev)	3F/3R		Infinite		N/P		
Max. Speed Forward Kph (mph)	10	(6)	10	(6)	10	(6)	
Max. Speed Reverse Kph (mph)	12	(7)	N/P	N/P	10	(6)	
Steering Control	HSSR		N/P		Single-Lever Steering		
Minimum Turning Radius m (ft)	4.5	(14.8)	N/P	N/P	N/P	N/P	
Final Drives	Double Reduction		N/P		N/P		
Sprockets	Segments		N/P		N/P		
<b>Undercarriage</b>							
Undercarriage Suspension Type	Oscillating		N/P		N/P		
Track Roller Frame	Box Section		N/P		N/P		
Track Roller Type	Lifetime Lubrication		N/P		N/P		
Number of Track Rollers	6		7		6		
Number of Carrier Rollers	2		N/P		N/P		
Type of Shoes	Single Grouser		Double Grouser		N/P		
Number of Shoes per Side	37		38		38		
Grouser Height mm (in)	60	(2)	42	(2)	N/P	N/P	
Ground Contact Area cm2 (in2)	27,216	(4,218)	28,000	(4,340)	28,985	(4,493)	
Ground Pressure Kpa (psi)	52	(7,542)	71	(10,298)	76	(11,023)	
Track Gauge mm (ft)	1,880	(6.2)	1,850	(6.1)	1,880	(6.2)	
Length of Track on Ground mm (ft)	2,430	(8.0)	N/P	N/P	N/P	N/P	
<b>Hydraulics</b>							
Hydraulic Type	Closed-Center		Closed-Center Load-Sensing		Load sense, piston pump		
Hydraulic Pump Type	Piston		N/P		N/P		
Hydraulic Pump Capacity L/min (gpm)	240	(63)	230	(61)	246	(65)	
Raise Time sec	6		N/P		N/P		
Dump Time sec	1.2		N/P		N/P		
Float Down Time sec	2.1		N/P		N/P		
Relief Valve Setting Mpa (psi)	14	(2,031)	N/P	N/P	N/P	N/P	
<b>Bucket Type</b>							
Bucket Type	General Purpose		N/P		General Purpose		
Bucket Capacity m3 (cu. Yd)	1.7	(2.2)	2.45	(3.2)	2.5	(3.3)	
Bucket Width mm (ft)	2,450	(8.0)	2,612	(8.6)	2,591	(8.5)	
<b>Dimensions</b>							
Overall Length mm (ft)	6,580	(21.6)	7,001	(23.0)	6,824	(22.4)	
Overall Height mm (ft)	3,440	(11.3)	3,325	(10.9)	3,330	(10.9)	
Overall Width (Shipping) mm (ft)	2,450	(8.0)	2,400	(7.9)	2,591	(8.5)	
Clearance at Full Height 45° Dump mm (ft)	2,600	(8.5)	N/P	N/P	2,950	(9.7)	
Height Bucket Hinge mm (ft)	3,440	(11.3)	3,940	(12.9)	N/P	N/P	
Max. Height Fully Raised mm (ft)	4,540	(14.9)	5,402	(17.7)	N/P	N/P	
<b>Maintenance</b>							
Refill Capacity - Coolant L (gal)	79	(20.9)	32	(8.5)	32	(8.5)	
Refill Capacity - Fuel Tank L (gal)	300	(79)	320	(85)	326	(86)	
Refill Capacity - Engine L (gal)	28	(7.4)	N/P	N/P	25	(6.6)	
Refill Capacity - Hydraulics L (gal)	80	(21.1)	90	(23.8)	121	(32.0)	
Refill Capacity - Final Drives, Each L (gal)	62	(16.4)	15	(4.0)	15	(4.0)	
Refill Capacity - Power Train L (gal)	52	(13.7)	N/P	N/P	N/P	N/P	
Equipment specifications and images may change without notice from Rhino Equipment Group Inc.							
Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.							