



RADT30

ARTICULATED DUMP TRUCK



More Power and control mean more productivity.



Rhino Equipment developed the concept of the articulated truck

Around the globe, we're still the undisputed leader of articulated hauling in the most demanding conditions, terrain and applications. Simple, easy operation and automotive style comfort along with combined service points and extended service intervals means more focus on the work to be done, more time on the job, less time and money spent on servicing.

With heavy-duty front and rear frames designed for severe off-road operation and long service life, these machines have the quality, reliability and durability that you expect from Rhino.

MAIN PARAMETERS

Payload kg (lb)	30,000(66.139)
Empty Weight kg (lb)	20,000(44.093)
Gross Vehicle Weight kg (lb)	50,000(110.231)
Drive Style	6x6
Max. Speed km/h (mph)	55(35)
Max. Gradeability (°)	43
Max. Steering Angle (°)	45
Undercarriage	Constructed from high strength steel large U section stiffeners and a high tensile floor, rubber cushion between body and frame
Body Struck m3 (cu.Yd)	13,9(18.1)
LxWxH mm (in)	9,500x2,900x3,450(374x114x136)
Engine Model	Cummins M11-C330 or Rhino 6650
Emissions (optional)	Tier 2 (Tier 3, Tier 4)
Power kW (Hp) @2,100rpm	330(443)
Max. Torque Nm (ft-lb) @1,400rpm	1,704(1.257)
Transmission	ZF 6WG260-RADT30
Type of Transmission	Automatic
Brake System	Dual circuit air over hydraulic disc brake
Hoist Time (seconds)	12
Hoist Angle (°)	70
Cab	ROPS&FOPS
Tires	750/65R25/23,5R25
Electrical System	24 volts

