



RADT40

ARTICULATED DUMP TRUCK



More Power and control mean more productivity.



Rhino Equipment developed the concept of the articulated truck

Around the globe, we're still the undisputed leader of articulated hauling in the most demanding conditions, terrain and applications. Simple, easy operation and automotive style comfort along with combined service points and extended service intervals means more focus on the work to be done, more time on the job, less time and money spent on servicing.

With heavy-duty front and rear frames designed for severe off-road operation and long service life, these machines have the quality, reliability and durability that you expect from Rhino.

MAIN PARAMETERS

Payload kg (lb)	39,000(85.980)
Empty Weight kg (lb)	34,000(74.957)
Gross Vehicle Weight kg (lb)	73,000(160.937)
Drive Style	6x6
Max. Speed km/h (mph)	60(38)
Max. Gradeability (°)	45
Max. Steering Angle (°)	45
Body Struck m ³ (cu.Yd)	17,5/18,5(22.9/24.2)
Body Headped m ³ (cu.Yd)	22.9/24(29.9/32)
LxWxH mm (in)	10,690x3,370x3,793(420x132x149)
Engine Model	Cummins or Rhino 6060
Emissions (optional)	Tier 2 (Tier 3, Tier 4)
Power kW (Hp) @1,800rpm	350(470)
Max. Torque Nm (ft-lb) @1,300rpm	2,300(1.696)
Transmission	ZF 8EP420-RADT40
Speed Range	Eight forward and four reverse gears
Brake System	Wet disc brakes
Hoist Time (seconds)	12
Hoist Angle (°)	70
Cab	ROPS&FOPS
Tires	29.5R25
Electrical System	24 volts



