



RADT60

ARTICULATED DUMP TRUCK



More Power and control mean more productivity.



Rhino Equipment developed the concept of the articulated truck

Around the globe, we're still the undisputed leader of articulated hauling in the most demanding conditions, terrain and applications. Simple, easy operation and automotive style comfort along with combined service points and extended service intervals means more focus on the work to be done, more time on the job, less time and money spent on servicing.

With heavy-duty front and rear frames designed for severe off-road operation and long service life, these machines have the quality, reliability and durability that you expect from Rhino.

MAIN PARAMETERS

Payload kg (lb)	60,000(132.277)
Empty Weight kg (lb)	48,000(105.821)
Gross Vehicle Weight kg (lb)	108,000(238.099)
Drive Style	6xN(N=2~6)
Max. Speed km/h (mph)	45(28)
Max. Gradeability (°)	26
Max. Steering Angle (°)	45
Body Struck m3 (cu.Yd)	31(40.5)
Body Headped m3 (cu.Yd)	38(49.7)
LxWxH mm (in)	12,610x4,085x4,320(496x160x170)
Engine Model	Cummins QSK19 or Rhino 6065
Emissions (optional)	Tier 2 (Tier 3, Tier 4)
Power kW (Hp) @2,100rpm	522(700)
Max. Torque Nm (ft-lb) @1,500rpm	2,118(1.562)
Transmission	AC drive system with sleepless speed regulation
Speed Range	Fully hydraulic controlled dry disc brakes
Brake System	Wet disc brakes
Hoist Time (seconds)	16
Hoist Angle (°)	68
Cab	ROPS&FOPS
Tires	875/65R29
Electrical System	24 volts



