

RTC6014

TOWER CRANE




Rhino Tower Cranes are economical to transport, fast and easy to set up and have innovative drivelines. These cranes are powerful enough for medium to large construction projects. The individual crane components can be transported in the order in which they are later assembled.

It comprises machines of all systems and size categories, with the ideal lifting technology for any civil engineering task.

The highly adaptable fast-erecting cranes and the efficient top-slewing cranes have proved their worth both in the construction of residential buildings and on large-scale industrial projects all over the world.

The Rhino Tower Cranes have their reputation for being easy to adapt to their working environment: sites which are high up, crowded or widely spread. They make it possible to hoist and distribute loads be a easy work.





2

LOAD CAPACITIES			US Tons	Tons	Lb
Radius					
At 2.5m - 11.8m (8 ft - 39 ft)			8.8	8	16,000
At 15 m (49 ft)			7.9	7.14	14,280
At 25 m (82 ft)			4.2	3.83	7,660
At 30 m (98 ft)			3.2	2.93	5,860
At 35 m (115 ft)			2.6	2.33	4,660
At 40 m (131 ft)			2.1	1.88	3,760
At 45 m (148 ft)			1.7	1.54	3,080
At 50 m (164 ft)			1.4	1.26	2,520
At 55 m (180 ft)			1.1	1.04	2,080
At 60 m (197 ft)			0.9	0.85	1,700
PERFORMANCE			Metric		US
Normal Hoisting Moment			1,250 KN	lm 9	21,953 ft-lb
Rated Hoisting Weight at Jib Nose			0.9 ton	s	1,800 lb
Working Radius			2.5 - 60	m	8 - 197 ft
Rear Swing Radius			13 m		42.7 ft
Max. Working Wind Speed			20 m/s	5	66 ft/s
Max. Wind Speed for Top Rising			13 m/s	5	43 ft/s
mbient Temperature Working Range			-20 to 40	•°C -	4 to 104 °F
HEIGHT					
Standard Height			46 m		150.9 ft
Max. Height	161 m		1	528 ft	
PERFORMANCE				Metric	US
Reach				60 m	196.9 ft
Max. Capacity			8 tons		16,000 lb
HOISTING SPEED	Hoisting	Hoisting Speed		Hoisting Weig	
Working Modes	m/min	ft/min	US tons	tons	lb
2x Speed	26	85	8.8	8	16,000
	53	174	4.4	4	8,000
4x Speed	53	174	4.4	4	8,000
	105	344	2.2	2	4,000
WORKING MODES					4x Speed
Swing Speed				0 rp	m - 0.8 rpm
Radius Changing Speed			58	58 m/min	
Top Rising Speed			0.4	0.4 m/min	
OPERATING WEIGHTS				tons	
Net Weight				99	lb 198,000
Ballast Weight				17	34,000
Total Weight (with anchoring)				116	232,000

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.