



REX70.8

EXCAVATOR



Unprecedented precision and ease of operation.



This Rhino excavator is loaded with enhancements that not only increase productivity and uptime, but lower daily operating costs, too. A high-efficiency “on-demand” cooling system, advanced multifunction monitor, and productivity modes to allow you to choose your digging style headline the long list of advances.



1. Level climate-control system with automotive-style adjustable louvers helps keep the glass clear and the cab comfortable.
2. LCD monitor provide intuitive access to a wealth of information and functions.
3. Ergonomically correct short-throw pilot levers provide smooth, predictable fingertip control with less movement or effort.

ENGINE

Engine Make / Engine Model	YANMAR 4TNV98T
Emissions (optional)	Tier2(Tier3, Tier4)
Cylinders	4
Displacement L (cu. In)	3.3(201)
Net Power kW (Hp) @2,200 rpm	54.3(73)
Fuel System	Direct Injection
Aspiration	Naturally Aspirated

COOLING

Fan Drive	Belt Driven
-----------	-------------

POWERTRAIN

Type	Dual speed mode for tracks on-dash one-button activation
Max. Travel Speeds: km/h (mph)	
Low	2,7(1.68)
High	5,1(3.17)

HYDRAULICS

Type	Open center, load sensing, two variable-displacement axial piston pumps
Ground Pressure Mpa (psi)	30(4351.13)
Max. Flow L/min (gpm) (each)	154(41)
Power Boost Mpa (psi)	29(4.206)
Control	2 Pilot levers, low-effort hydraulic controls with horn and boost buttons

CYLINDERS	Bore	Rod Diameter	Stroke
Boom (2) mm (in)	115(4.5)	65(2.6)	885(34.8)
Arm (1) mm (in)	95(3.7)	60(2.4)	900(35.4)
Bucket (1) mm (in)	85(3.3)	55(2.2)	730(28.7)



ELECTRICAL

Number of Batteries	2
Voltage	24 volts
Alternator Rating	70A
Lights	4 Front lights, 1 Rear light

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

UNDERCARRIAGE	
Carrier Rollers (each side)	1
Track Rollers (each side)	5
Shoes (each side) Triple Semi-Grousers	40
Adjustment	Hydraulic
Guides	Front Idler
Chain	Sealed and lubricated
GROUND PRESSURE	
Triple Semi-Grouser (500mm) (20in) Kpa (psi)	30(4.4)
SWING MECHANISM	
Speed rpm	10
REFILL CAPACITIES L (gal)	
Fuel Tank	130(34)
Cooling System	8(2)
Engine Oil	11,7(3)
Hydraulic Tank	90(24)
Swing Drive	5(1)
Final Drive Case (each)	70(18)
OPERATING WEIGHTS	
With full fuel tank, 79kg (175lb) operator, 0,34m ³ (0.44 cu.Yd) general purpose bucket, 350mm (13.8in) tracks and 1,450mm (4.8ft) arm	
Base Weight kg (lb)	8,000(17.637)
OPERATING DIMENSIONS	
Arm length mm (ft)	1,650(5.4)
Bucket Capacity m ³ (cu. Yd.)	0,34(0.44)
Bucket Excavating Force kN ISO (lb)	60(13,489)
Lift at end at 15' radius, at ground level kg (lb)	3,170(6,989)
Lift on the side at 15' radius, at ground level kg (lb)	1,925(4,244)
Length of Swing Arm mm (ft)	3,710(12.17)
Gradeability(%)	70


Equipment specifications and images may change without notice from Rhino Equipment Group Inc.



MACHINE DIMENSIONS mm (ft)

A Overall length	6100 (20.0)
B Overall width	2300 (7.5)
C Total height(Swing arm top)	2515 (8.3)
D Total height(Cab roof)	2680 (8.8)
E Counterweight ground clearance	760 (2.5)
F Min. ground clearance	380 (1.2)
G Turning radius of vehicle tail	1755 (5.8)
H Ground contact length of track	2150 (7.1)
J Track shoe length	2760 (9.1)
K Track gauge	1700 (5.6)
L Track shoe length	2150 (7.1)
M Track shoe width	450 (1.5)
N Rotary table width	2198 (7.2)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.



OPERATING RANGE mm (ft)

O Maximum excavating height	7165 (23.5)
P Maximum unloading height	5065 (16.6)
Q Maximum excavating depth	4038 (13.2)
R Maximum vertical wall excavating depth	3505 (11.5)
T Maximum excavating distance	6330 (20.8)
U Maximum excavating distance at ground level	6180 (20.3)
V Minimum turning radius	1795 (5.9)
W Maximum height at minimum turning radius	5500 (18.0)
X Distance between the center of gyration and the rear end side	1755 (5.8)
Z Counterweight height	1725 (5.7)
A1 Ground contact length(during transportation)	3700 (12.1)


Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

OPTIONS

Rhino Excavators can come with different options like: Tier2, Tier3, Tier4 Engine, Close cab, Rock bucket, Trench bucket, Thumb cutters, and many more according to work requirements.

ATTACHMENTS

Rhino Excavators come standard with the hydraulic line for attachments.



Many options buckets



Hydraulic hammers



Trenchers



Augers

and many more...

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.