



Characteristic / Característica	RHINO RFL200-DT	Toyota 8FD20	Hyster H2.0FT	Heli CPCD20
General / General				
Brand / Marca	RHINO	Toyota	Hyster	Heli
Model / Modelo	RFL200-DT	8FD20	H2.0FT	CPCD20
Machine Type / Tipo de Máquina	Diesel Forklift / Montacargas Diésel	Diesel Forklift	Diesel Forklift	Diesel Forklift
Load Capacity / Capacidad de Carga kg (lb)	2,000 (4,409)	2,000 (4,400)	2,000 (4,400)	2,000 (4,409)
Load Center / Centro de Carga mm (in)	500 (19.7)	500 (19.7)	500 (19.7)	500 (19.7)
Operating Weight / Peso Operativo kg (lb)	3,320 (7,319)	3,330 (7,341)	3,420 (7,540)	3,350 (7,385)
Engine / Motor				
Engine Make / Marca del Motor	RHINO / ISUZU	Toyota	Yanmar	Quanchai / Isuzu
Engine Model / Modelo del Motor	Rhino 490BPG / Isuzu 4 JG2PE	1DZ-II	2.6L	QC490 / C240
Number of Cylinders / Número de Cilindros	4	4	4	4
Gross Power / Potencia Bruta kW (hp)	39.0 / 39.0 (52.3)	44.0 (59.0)	33.0 (44.0)	39.0 (52.0)
Displacement / Cilindraje L (cu. in)	2.67 (163.0)	2.48 (151.0)	2.6 (158.0)	2.67 (163.0)
Drivetrain & Performance / Transmisión y Desempeño				
Transmission Type / Tipo de Transmisión	Hydraulic/Mechanical / Hidráulica/Mecánica	Powershift / Manual	Powershift (DuraMatch)	Hydraulic / Mecánica
Max. Speed (w/wo load) / Vel. Máx. km/h (mph)	17.0 / 19.0 (10.6 / 11.8)	18.5 / 19.0	18.2 / 19.1	17.0 / 19.0
Max. Gradeability / Pendiente Superable %	15 / 20	20	22	20
Dimensions / Dimensiones				
Turning Radius / Radio de Giro mm (in)	2,450 (96.5)	2,200 (86.6)	2,165 (85.2)	2,240 (88.2)
Overall Length (to fork face) / Longitud mm	3,605 (141.9)	2,560 (100.8)*	2,504 (98.6)*	2,550 (100.4)*
Overall Width / Ancho Total mm (in)	1,160 (45.7)	1,150 (45.3)	1,150 (45.3)	1,150 (45.3)
Height (Mast lowered) / Altura Mástil mm (in)	2,095 (82.5)	2,070 (81.5)	2,075 (81.7)	2,070 (81.5)



Characteristic / Característica	RHINO RFL250-DT	Toyota 8FD25	Hyster H2.5FT	Heli CPCD25
General / General				
Brand / Marca	RHINO	Toyota	Hyster	Heli
Model / Modelo	RFL250-DT	8FD25	H2.5FT	CPCD25
Machine Type / Tipo de Máquina	Diesel Forklift / Montacargas Diésel	Diesel Forklift	Diesel Forklift	Diesel Forklift
Load Capacity / Capacidad de Carga kg (lb)	2,500 (5,512)	2,500 (5,500)	2,500 (5,500)	2,500 (5,512)
Load Center / Centro de Carga mm (in)	500 (19.7)	500 (19.7)	500 (19.7)	500 (19.7)
Operating Weight / Peso Operativo kg (lb)	4,320 (9,524)	3,620 (7,980)	3,820 (8,421)	3,600 (7,936)
Engine / Motor				
Engine Make / Marca del Motor	RHINO / ISUZU	Toyota	Yanmar	Quanchai / Isuzu
Engine Model / Modelo del Motor	Rhino 490BPG / Isuzu 4 JG2PE	1DZ-II	2.6L / 3.3L	QC490 / C240
Number of Cylinders / Número de Cilindros	4	4	4	4
Gross Power / Potencia Bruta kW (hp)	42.0 / 45.0 (56.3 / 60.3)	44.0 (59.0)	44.0 (59.0)	39.0 (52.0)
Displacement / Cilindraje L (cu. in)	2.67 (163.0)	2.48 (151.0)	2.6 / 3.3	2.67 (163.0)
Drivetrain & Performance / Transmisión y Desempeño				
Transmission Type / Tipo de Transmisión	Hydraulic/Mechanical / Hidráulica/Mecánica	Powershift / Manual	Powershift (DuraMatch)	Hydraulic / Mecánica
Max. Speed (w/wo load) / Vel. Máx. km/h (mph)	18.0 / 20.0 (11.2 / 12.4)	18.5 / 19.0	18.5 / 19.3	17.0 / 19.0
Max. Gradeability / Pendiente Superable %	15 / 20	20	22	20
Dimensions / Dimensiones				
Turning Radius / Radio de Giro mm (in)	2,500 (98.4)	2,280 (89.8)	2,260 (89.0)	2,240 (88.2)
Overall Length (to fork face) / Longitud mm	3,800 (149.6)	2,635 (103.7)*	2,580 (101.6)*	2,650 (104.3)*
Overall Width / Ancho Total mm (in)	1,230 (48.4)	1,150 (45.3)	1,150 (45.3)	1,150 (45.3)
Height (Mast lowered) / Altura Mástil mm (in)	2,095 (82.5)	2,070 (81.5)	2,075 (81.7)	2,070 (81.5)



Characteristic / Característica	RHINO RFL300-DT	Toyota 8FD30	Hyster H3.0FT	Heli CPCD30
General / General				
Brand / Marca	RHINO	Toyota	Hyster	Heli
Model / Modelo	RFL300-DT	8FD30	H3.0FT	CPCD30
Machine Type / Tipo de Máquina	Diesel Forklift / Montacargas Diésel	Diesel Forklift	Diesel Forklift	Diesel Forklift
Load Capacity / Capacidad de Carga kg (lb)	3,000 (6,614)	3,000 (6,600)	3,000 (6,600)	3,000 (6,614)
Load Center / Centro de Carga mm (in)	500 (19.7)	500 (19.7)	500 (19.7)	500 (19.7)
Operating Weight / Peso Operativo kg (lb)	4,320 (9,524)	4,380 (9,656)	4,660 (10,273)	4,270 (9,414)
Engine / Motor				
Engine Make / Marca del Motor	RHINO / ISUZU	Toyota	Yanmar	Quanchai / Isuzu
Engine Model / Modelo del Motor	Rhino 490BPG / Isuzu 4 JG2PE	1DZ-II	3.3L	QC490 / C240
Number of Cylinders / Número de Cilindros	4	4	4	4
Gross Power / Potencia Bruta kW (hp)	42.0 / 45.0 (56.3 / 60.3)	44.0 (59.0)	44.0 (59.0)	39.0 (52.0)
Displacement / Cilindraje L (cu. in)	2.67 (163.0)	2.48 (151.0)	3.3 (201.0)	2.67 (163.0)
Drivetrain & Performance / Transmisión y Desempeño				
Transmission Type / Tipo de Transmisión	Hydraulic/Mechanical / Hidráulica/Mecánica	Powershift / Manual	Powershift (DuraMatch)	Hydraulic / Mecánica
Max. Speed (w/wo load) / Vel. Máx. km/h	18.0 / 20.0 (11.2 / 12.4 mph)	19.0 / 19.5	19.2 / 20.1	18.5 / 19.0
Max. Gradeability / Pendiente Superable %	15 / 20	20	22	20
Dimensions / Dimensiones				
Turning Radius / Radio de Giro mm (in)	2,500 (98.4)	2,430 (95.7)	2,416 (95.1)	2,400 (94.5)
Overall Length (to fork face) / Longitud mm	3,800 (149.6)	2,795 (110.0)*	2,725 (107.3)*	2,700 (106.3)*
Overall Width / Ancho Total mm (in)	1,230 (48.4)	1,240 (48.8)	1,186 (46.7)	1,225 (48.2)
Height (Mast lowered) / Altura Mástil mm (in)	2,095 (82.5)	2,055 (80.9)	2,170 (85.4)	2,070 (81.5)



Characteristic / Característica	RHINO RFL400-DT	Toyota 8FD40	Hyster H4.0FT	Heli CPCD40
---------------------------------	-----------------	--------------	---------------	-------------

General / General

Brand / Marca	RHINO	Toyota	Hyster	Heli
Model / Modelo	RFL400-DT	8FD40	H4.0FT	CPCD40
Machine Type / Tipo de Máquina	Diesel Forklift / Montacargas Diésel	Diesel Forklift	Diesel Forklift	Diesel Forklift
Load Capacity / Capacidad de Carga kg (lb)	4,000 (8,818)	4,000 (8,800)	4,000 (8,800)	4,000 (8,818)
Load Center / Centro de Carga mm (in)	500 (19.7)	500 (19.7)	500 (19.7)	500 (19.7)
Operating Weight / Peso Operativo kg (lb)	4,900 (10,803)	6,280 (13,845)	6,340 (13,977)	6,300 (13,889)

Engine / Motor

Engine Make / Marca del Motor	RHINO / ISUZU	Toyota	Cummins / Kubota	Quanchai / Isuzu
Engine Model / Modelo del Motor	Rhino 490BPG / Isuzu 4 JG2PE	1KD	QSF2.8 / V3800	4C6 / 6BG1
Number of Cylinders / Número de Cilindros	4	4	4	4 / 6
Gross Power / Potencia Bruta kW (hp)	42.0 / 45.0 (56.3 / 60.3)	55.0 (74.0)	55.0 (74.0)	60.0 (80.0)
Displacement / Cilindraje L (cu. in)	3.17 (193.0)	3.0 (182.0)	3.8 (232.0)	4.3 (262.0)

Drivetrain & Performance / Transmisión y Desempeño

Transmission Type / Tipo de Transmisión	Hydraulic/Mechanical / Hidráulica/Mecánica	Powershift / Manual	Powershift (DuraMatch)	Hydraulic / Mecánica
Max. Speed (w/wo load) / Vel. Máx. km/h (mph)	18.0 / 20.0 (11.2 / 12.4)	21.0 / 22.0	22.0 / 23.0	20.0 / 22.0
Max. Gradeability / Pendiente Superable %	15 / 20	20	20	20

Dimensions / Dimensiones

Turning Radius / Radio de Giro mm (in)	2,720 (107.1)	2,780 (109.4)	2,820 (111.0)	2,750 (108.3)
Overall Length (to fork face) / Longitud mm	4,100 (161.4)	3,080 (121.3)*	3,025 (119.1)*	3,050 (120.1)*
Overall Width / Ancho Total mm (ft)	1,230 (48.4)	1,450 (57.1)	1,400 (55.1)	1,480 (58.3)
Height (Mast lowered) / Altura Mástil mm (in)	2,110 (83.1)	2,235 (88.0)	2,215 (87.2)	2,230 (87.8)



Characteristic / Característica	RHINO RFL500-DT	Toyota 8FD50	Hyster H5.0FT	Heli CPCD50
General / General				
Brand / Marca	RHINO	Toyota	Hyster	Heli
Model / Modelo	RFL500-DT	8FD50	H5.0FT	CPCD50
Machine Type / Tipo de Máquina	Diesel Forklift / Montacargas Diésel	Diesel Forklift	Diesel Forklift	Diesel Forklift
Load Capacity / Capacidad de Carga kg (lb)	5,000 (11,023)	5,000 (11,000)	5,000 (11,000)	5,000 (11,023)
Load Center / Centro de Carga mm (in)	500 (19.7) / 600 (23.6)	600 (23.6)	600 (23.6)	600 (23.6)
Operating Weight / Peso Operativo kg (lb)	6,800 (14,991)	7,350 (16,200)	7,420 (16,358)	7,300 (16,093)
Engine / Motor				
Engine Make / Marca del Motor	RHINO / ISUZU	Toyota	Cummins / Kubota	Quanchai / Isuzu
Engine Model / Modelo del Motor	Rhino LR4A3 / Isuzu 6BG1	1KD	QSF2.8 / V3800	4C6 / 6BG1
Number of Cylinders / Número de Cilindros	4	4	4	4 / 6
Gross Power / Potencia Bruta kW (hp)	59.0 / 82.0 (79.1 / 110.0)	55.0 (74.0)	55.0 (74.0)	60.0 / 82.0 (80.0 / 110.0)
Displacement / Cilindraje L (cu. in)	4.3 (262.0)	3.0 (182.0)	3.8 (232.0)	4.3 (262.0)
Drivetrain & Performance / Transmisión y Desempeño				
Transmission Type / Tipo de Transmisión	Hydraulic/Mechanical / Hidráulica/Mecánica	Powershift / Manual	Powershift (DuraMatch)	Hydraulic / Mecánica
Max. Speed (w/wo load) / Vel. Máx. km/h (mph)	20.0 / 24.0 (12.4 / 14.9)	22.0 / 23.0	22.0 / 23.0	21.0 / 22.0
Max. Gradeability / Pendiente Superable %	15 / 20	20	20	20
Dimensions / Dimensiones				
Turning Radius / Radio de Giro mm (in)	3,000 (118.1)	2,970 (116.9)	2,930 (115.4)	2,950 (116.1)
Overall Length (to fork face) / Longitud mm	4,350 (171.3)	3,280 (129.1)*	3,240 (127.6)*	3,250 (128.0)*
Overall Width / Ancho Total mm (in)	1,400 (55.1)	1,450 (57.1)	1,425 (56.1)	1,480 (58.3)
Height (Mast lowered) / Altura Mástil mm (in)	2,330 (91.7)	2,390 (94.1)	2,385 (93.9)	2,380 (93.7)



Characteristic / Característica	RHINO RFL700-DT	Toyota 8FD70	Hyster H7.0FT	Heli CPCD70
General / General				
Brand / Marca	RHINO	Toyota	Hyster	Heli
Model / Modelo	RFL700-DT	8FD70	H7.0FT	CPCD70
Machine Type / Tipo de Máquina	Diesel Forklift / Montacargas Diésel	Diesel Forklift	Diesel Forklift	Diesel Forklift
Load Capacity / Capacidad de Carga kg (lb)	7,000 (15,432)	7,000 (15,400)	7,000 (15,400)	7,000 (15,432)
Load Center / Centro de Carga mm (in)	500 (19.7)	600 (23.6)	600 (23.6)	600 (23.6)
Operating Weight / Peso Operativo kg (lb)	9,500 (20,944)	9,650 (21,274)	9,800 (21,605)	9,700 (21,384)
Engine / Motor				
Engine Make / Marca del Motor	RHINO / ISUZU	Toyota	Cummins / Kubota	Isuzu / Chaochai
Engine Model / Modelo del Motor	Rhino LR4A4 / Isuzu 6BG1	14Z-II / 1KD	QSB3.3 / QSB4.5	6BG1 / 6BG1TRP
Number of Cylinders / Número de Cilindros	6	6	4 / 6	6
Gross Power / Potencia Bruta kW (hp)	59.0 / 82.0 (79.1 / 110.0)	62.0 (83.0)	82.0 (110.0)	82.0 (110.0)
Displacement / Cilindraje L (cu. in)	5.785 / 5.61 (353.0 / 342.0)	5.2 (317.0)	4.5 (275.0)	6.5 (396.0)
Drivetrain & Performance / Transmisión y Desempeño				
Transmission Type / Tipo de Transmisión	Hydraulic / Hidráulica	Powershift / Manual	Powershift (DuraMatch)	Hydraulic / Mecánica
Max. Speed (w/wo load) / Vel. Máx. km/h (mph)	22.0 / 26.0 (13.7 / 16.2)	23.0 / 25.0	24.0 / 26.0	22.0 / 25.0
Max. Gradeability / Pendiente Superable %	20 / 25	20	25	20
Dimensions / Dimensiones				
Turning Radius / Radio de Giro mm (in)	3,450 (135.8)	3,370 (132.7)	3,380 (133.1)	3,400 (133.9)
Overall Length (to fork face) / Longitud mm	4,800 (189.0)	3,580 (140.9)*	3,610 (142.1)*	3,580 (140.9)*
Overall Width / Ancho Total mm (in)	1,995 (78.5)	1,995 (78.5)	2,020 (79.5)	1,995 (78.5)
Height (Mast lowered) / Altura Mástil mm (in)	2,500 (98.4)	2,500 (98.4)	2,550 (100.4)	2,500 (98.4)



Characteristic / Característica	RHINO RFL1000-DT	Toyota 4FD100	Hyster H10XD	Heli CPCD100
---------------------------------	------------------	---------------	--------------	--------------

General / General

Brand / Marca	RHINO	Toyota	Hyster	Heli
Model / Modelo	RFL1000-DT	4FD100	H10XD	CPCD100
Machine Type / Tipo de Máquina	Diesel Forklift / Montacargas Diésel	Diesel Forklift	Diesel Forklift	Diesel Forklift
Load Capacity / Capacidad de Carga kg (lb)	10,000 (22,046)	10,000 (22,046)	10,000 (22,046)	10,000 (22,046)
Load Center / Centro de Carga mm (in)	600 (23.6)	600 (23.6)	600 (23.6)	600 (23.6)
Operating Weight / Peso Operativo kg (lb)	12,510 (27,580)	13,200 (29,101)	14,200 (31,305)	13,300 (29,321)

Engine / Motor

Engine Make / Marca del Motor	RHINO / ISUZU	Toyota / Cummins	Cummins / Mercedes	Isuzu / Xichai
Engine Model / Modelo del Motor	Rhino LR4A5 / Isuzu 6BG1	14Z-II / 6BT5.9	QSB4.5 / OM934	6BG1 / CA6110
Number of Cylinders / Número de Cilindros	6	6	4 / 6	6
Gross Power / Potencia Bruta kW (hp)	81.0 / 82.0 (108.6 / 110.0)	85.0 (114.0)	129.0 (173.0)	83.0 (111.0)
Displacement / Cilindraje L (cu. in)	5.785 (353.0)	5.9 (360.0)	4.5 / 5.3	6.5 (396.0)

Drivetrain & Performance / Transmisión y Desempeño

Transmission Type / Tipo de Transmisión	Hydraulic / Hidráulica	Powershift / Manual	Powershift (DuraMatch)	Hydraulic / Powershift
Max. Speed (w/wo load) / Vel. Máx. km/h (mph)	16.0 / 22.0 (9.9 / 13.7)	22.0 / 24.0	25.0 / 27.0	24.0 / 28.0
Max. Gradeability / Pendiente Superable %	19 / 20	20	25	21

Dimensions / Dimensiones

Turning Radius / Radio de Giro mm (in)	3,900 (153.5)	3,900 (153.5)	3,980 (156.7)	3,900 (153.5)
Overall Length (to fork face) / Longitud mm	5,480 (215.7)	4,250 (167.3)*	4,200 (165.4)*	4,210 (165.7)*
Overall Width / Ancho Total mm (in)	2,275 (89.6)	2,245 (88.4)	2,540 (100.0)	2,245 (88.4)
Height (Mast lowered) / Altura Mástil mm (in)	2,850 (112.2)	2,830 (111.4)	2,900 (114.2)	2,830 (111.4)