



Characteristic / Característica	RHINO (Modelo: 1826 EX)	Caterpillar (Modelo : B20)	Doosan (Modelo : DXB 170)	Epiroc (Modelo : MB 1700)	John Deere / NPK (Modelo : GH9)	JCB (Modelo : HM1570Q)	Indeco (Modelo : HP 3000)
General / General							
Brand / Marca	RHINO	Caterpillar	Doosan	Epiroc (Atlas Copco)	John Deere / NPK	JCB	Indeco
Model / Modelo	1826 EX	B20	DXB 170	MB 1700	GH9	HM1570Q	HP 3000
Carrier Type / Tipo de Equipo Portador	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora
Carrier Weight Class / Clase de Equipo kg (lb)	18,000 - 26,000 kg (40,000 - 57,320 lb)	18,000 - 25,000 kg (39,600 - 55,100 lb)	18,000 - 28,000 kg (39,600 - 61,700 lb)	19,000 - 32,000 kg (41,900 - 70,500 lb)	18,000 - 25,000 kg (39,600 - 55,100 lb)	18,000 - 26,000 kg (39,600 - 57,300 lb)	19,000 - 32,000 kg (41,900 - 70,500 lb)
Operating Weight / Peso Operativo kg (lb)	1,740 kg (3,836 lb)	1,800 kg (3,968 lb)	1,600 kg (3,527 lb)	1,700 kg (3,748 lb)	1,750 kg (3,858 lb)	1,650 kg (3,637 lb)	1,900 kg (4,188 lb)
Dimensions / Dimensiones							
Height (Incl. Tool) / Altura (Incl. Punta) mm (in)	2,327 mm (92.0 in)	2,450 mm (96.5 in)	2,400 mm (94.5 in)	2,420 mm (95.3 in)	2,490 mm (98.0 in)	2,380 mm (93.7 in)	2,550 mm (100.4 in)
Hydraulics / Sistema Hidráulico							
Required Oil Flow / Caudal Requerido L/min (gal/min)	130 - 150 L/min (34.0 - 40.0 gal/min)	130 - 160 L/min (34.3 - 42.3 gal/min)	130 - 180 L/min (34.3 - 47.5 gal/min)	130 - 170 L/min (34.3 - 44.9 gal/min)	140 - 180 L/min (37.0 - 47.5 gal/min)	130 - 170 L/min (34.3 - 44.9 gal/min)	140 - 190 L/min (37.0 - 50.2 gal/min)
Operating Pressure / Presión de Trabajo bar (psi)	160 - 180 bar (2,321 - 2,611 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	180 - 200 bar (2,610 - 2,900 psi)
Hose Diameter / Diámetro de Manguera in	1 in	1 in	1 in	1 in	1 in	1 in	1 in
Performance / Rendimiento							
Impact Rate / Rango de Impacto bpm	400 - 500 bpm	400 - 800 bpm	350 - 700 bpm	320 - 640 bpm	400 - 800 bpm	350 - 700 bpm	340 - 730 bpm
Impact Energy / Energía de Impacto J (ft-lb)	4,500 J (3,319 ft-lb)	4,600 J (3,393 ft-lb)	4,200 J (3,097 ft-lb)	4,400 J (3,245 ft-lb)	4,550 J (3,355 ft-lb)	4,300 J (3,171 ft-lb)	4,800 J (3,540 ft-lb)
Tool Diameter / Diámetro de la Punta mm (in)	135 mm (5.32 in)	135 mm (5.31 in)	135 mm (5.31 in)	135 mm (5.31 in)	136 mm (5.35 in)	135 mm (5.31 in)	135 mm (5.31 in)
Gas Pressure / Presión de Gas bar (psi)	6 bar (87 psi)	15 bar (217 psi)	16 bar (232 psi)	N/A (Solid Body)	15 bar (217 psi)	15 bar (217 psi)	N/A