



Characteristic / Característica	RHINO (Modelo: 254 SK)	Caterpillar (Modelo : B4)	Bobcat (Modelo : HB680)	Epiroc (Modelo : SB 152)	John Deere (Modelo : HH40C)	JCB (Modelo : HM026T)	Indeco (Modelo : HP 400)
General / General							
Brand / Marca	RHINO	Caterpillar	Bobcat	Epiroc (Atlas Copco)	John Deere	JCB	Indeco
Model / Modelo	254 SK	B4	HB680	SB 152	HH40C	HM026T	HP 400
Carrier Type / Tipo de Equipo Portador	Skid Steer / Minicargador	Skid Steer / Minicargador	Skid Steer / Minicargador	Skid Steer / Minicargador	Skid Steer / Minicargador	Skid Steer / Minicargador	Skid Steer / Minicargador
Carrier Weight Class / Clase de Equipo kg (lb)	2,500 - 4,500 kg (5,500 - 10,000 lb)	2,500 - 4,500 kg (5,500 - 9,900 lb)	2,000 - 4,000 kg (4,400 - 8,800 lb)	1,900 - 4,500 kg (4,200 - 9,900 lb)	2,000 - 4,500 kg (4,400 - 9,900 lb)	2,000 - 4,500 kg (4,400 - 9,900 lb)	2,000 - 4,500 kg (4,400 - 9,900 lb)
Operating Weight / Peso Operativo kg (lb)	150 kg (331 lb)	150 kg (331 lb)	145 kg (320 lb)	140 kg (309 lb)	155 kg (341 lb)	150 kg (331 lb)	150 kg (331 lb)
Dimensions / Dimensiones							
Height (Incl. Tool) / Altura (Incl. Punta) mm (in)	1,342 mm (53.0 in)	1,180 mm (46.4 in)	1,200 mm (47.2 in)	1,150 mm (45.3 in)	1,200 mm (47.2 in)	1,190 mm (46.8 in)	1,200 mm (47.2 in)
Hydraulics / Sistema Hidráulico							
Required Oil Flow / Caudal Requerido L/min (gal/min)	25 - 40 L/min (6.5 - 10.5 gal/min)	25 - 50 L/min (6.6 - 13.2 gal/min)	25 - 50 L/min (6.6 - 13.2 gal/min)	25 - 45 L/min (6.6 - 11.9 gal/min)	30 - 55 L/min (7.9 - 14.5 gal/min)	25 - 50 L/min (6.6 - 13.2 gal/min)	25 - 50 L/min (6.6 - 13.2 gal/min)
Operating Pressure / Presión de Trabajo bar (psi)	90 - 120 bar (1,305 - 1,740 psi)	110 - 140 bar (1,595 - 2,030 psi)	110 - 120 bar (1,595 - 1,740 psi)	100 - 150 bar (1,450 - 2,175 psi)	100 - 130 bar (1,450 - 1,885 psi)	100 - 140 bar (1,450 - 2,030 psi)	110 bar (1,595 psi)
Hose Diameter / Diámetro de Manguera in	1/2 in	1/2 in	1/2 in	1/2 in	1/2 in	1/2 in	1/2 in
Performance / Rendimiento							
Impact Rate / Rango de Impacto bpm	600 - 1,100 bpm	600 - 1,100 bpm	1,150 bpm	850 - 1,900 bpm	700 - 1,200 bpm	600 - 1,500 bpm	540 - 2,040 bpm
Impact Energy / Energía de Impacto J (ft-lb)	320 J (236 ft-lb)	350 J (258 ft-lb)	340 J (251 ft-lb)	300 J (221 ft-lb)	350 J (258 ft-lb)	320 J (236 ft-lb)	360 J (265 ft-lb)
Tool Diameter / Diámetro de la Punta mm (in)	53 mm (2.09 in)	53 mm (2.09 in)	55 mm (2.16 in)	50 mm (1.97 in)	54 mm (2.12 in)	52 mm (2.05 in)	55 mm (2.16 in)
Gas Pressure / Presión de Gas bar (psi)	16 bar (232 psi)	15 bar (217 psi)	15 bar (217 psi)	N/A (Solid Body)	15 bar (217 psi)	15 bar (217 psi)	N/A