



Characteristic / Característica	RHINO (Modelo: 2735 EX)	Caterpillar (Modelo : B30)	Doosan (Modelo : DXB 260)	Epiroc (Modelo : HB 2500)	John Deere / NPK (Modelo : GH12)	JCB (Modelo : HM2780Q)	Indeco (Modelo : HP 4000)
General / General							
Brand / Marca	RHINO	Caterpillar	Doosan	Epiroc (Atlas Copco)	John Deere / NPK	JCB	Indeco
Model / Modelo	2735 EX	B30	DXB 260	HB 2500	GH12	HM2780Q	HP 4000
Carrier Type / Tipo de Equipo Portador	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora
Carrier Weight Class / Clase de Equipo kg (lb)	27,000 - 35,000 kg (60,000 - 77,000 lb)	25,000 - 32,000 kg (55,100 - 70,500 lb)	27,000 - 34,000 kg (59,500 - 75,000 lb)	27,000 - 37,000 kg (59,500 - 81,600 lb)	25,000 - 35,000 kg (55,100 - 77,200 lb)	27,000 - 35,000 kg (59,500 - 77,200 lb)	27,000 - 35,000 kg (59,500 - 77,200 lb)
Operating Weight / Peso Operativo kg (lb)	2,420 kg (5,335 lb)	2,300 kg (5,070 lb)	2,450 kg (5,401 lb)	2,500 kg (5,511 lb)	2,400 kg (5,291 lb)	2,600 kg (5,732 lb)	2,500 kg (5,511 lb)
Dimensions / Dimensiones							
Height (Incl. Tool) / Altura (Incl. Punta) mm (in)	2,500 mm (98.0 in)	2,650 mm (104.3 in)	2,620 mm (103.1 in)	2,700 mm (106.3 in)	2,680 mm (105.5 in)	2,650 mm (104.3 in)	2,750 mm (108.3 in)
Hydraulics / Sistema Hidráulico							
Required Oil Flow / Caudal Requerido L/min (gal/min)	150 - 190 L/min (40.0 - 50.0 gal/min)	150 - 250 L/min (39.6 - 66.0 gal/min)	150 - 210 L/min (39.6 - 55.5 gal/min)	170 - 220 L/min (44.9 - 58.1 gal/min)	160 - 210 L/min (42.3 - 55.5 gal/min)	160 - 220 L/min (42.3 - 58.1 gal/min)	160 - 220 L/min (42.3 - 58.1 gal/min)
Operating Pressure / Presión de Trabajo bar (psi)	160 - 180 bar (2,321 - 2,611 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	180 - 200 bar (2,610 - 2,900 psi)
Hose Diameter / Diámetro de Manguera in	1 in	1 in	1 in	1 1/4 in	1 in	1 1/4 in	1 1/4 in
Performance / Rendimiento							
Impact Rate / Rango de Impacto bpm	300 - 450 bpm	300 - 600 bpm	350 - 500 bpm	280 - 580 bpm	300 - 500 bpm	300 - 600 bpm	340 - 730 bpm
Impact Energy / Energía de Impacto J (ft-lb)	7,000 J (5,163 ft-lb)	7,200 J (5,310 ft-lb)	6,800 J (5,015 ft-lb)	7,500 J (5,531 ft-lb)	7,100 J (5,236 ft-lb)	7,000 J (5,163 ft-lb)	7,600 J (5,605 ft-lb)
Tool Diameter / Diámetro de la Punta mm (in)	150 mm (5.91 in)	150 mm (5.91 in)	150 mm (5.91 in)	155 mm (6.10 in)	146 mm (5.75 in)	150 mm (5.91 in)	150 mm (5.91 in)
Gas Pressure / Presión de Gas bar (psi)	6 bar (87 psi)	15 bar (217 psi)	16 bar (232 psi)	N/A (Solid Body)	15 bar (217 psi)	15 bar (217 psi)	N/A