



Characteristic / Característica	RHINO (Modelo: 3255 EX)	Caterpillar (Modelo : B35)	Doosan (Modelo : DXB 320)	Epiroc (Modelo : HB 3100)	John Deere / NPK (Modelo : GH15)	JCB (Modelo : HM3370Q)	Indeco (Modelo : HP 5000)
General / General							
Brand / Marca	RHINO	Caterpillar	Doosan	Epiroc (Atlas Copco)	John Deere / NPK	JCB	Indeco
Model / Modelo	3255 EX	B35	DXB 320	HB 3100	GH15	HM3370Q	HP 5000
Carrier Type / Tipo de Equipo Portador	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora	Excavator / Excavadora
Carrier Weight Class / Clase de Equipo kg (lb)	32,000 - 55,000 kg (70,500 - 121,250 lb)	32,000 - 50,000 kg (70,500 - 110,200 lb)	30,000 - 45,000 kg (66,100 - 99,200 lb)	32,000 - 52,000 kg (70,500 - 114,600 lb)	30,000 - 45,000 kg (66,100 - 99,200 lb)	32,000 - 50,000 kg (70,500 - 110,200 lb)	27,000 - 50,000 kg (59,500 - 110,200 lb)
Operating Weight / Peso Operativo kg (lb)	3,020 kg (6,658 lb)	3,200 kg (7,055 lb)	3,100 kg (6,834 lb)	3,100 kg (6,834 lb)	3,050 kg (6,724 lb)	3,250 kg (7,165 lb)	3,150 kg (6,944 lb)
Dimensions / Dimensiones							
Height (Incl. Tool) / Altura (Incl. Punta) mm (in)	2,740 mm (108.0 in)	2,900 mm (114.2 in)	2,800 mm (110.2 in)	2,850 mm (112.2 in)	2,810 mm (110.6 in)	2,900 mm (114.2 in)	2,800 mm (110.2 in)
Hydraulics / Sistema Hidráulico							
Required Oil Flow / Caudal Requerido L/min (gal/min)	190 - 250 L/min (50.0 - 65.0 gal/min)	200 - 260 L/min (52.8 - 68.7 gal/min)	190 - 250 L/min (50.2 - 66.0 gal/min)	210 - 270 L/min (55.5 - 71.3 gal/min)	200 - 260 L/min (52.8 - 68.7 gal/min)	200 - 260 L/min (52.8 - 68.7 gal/min)	200 - 270 L/min (52.8 - 71.3 gal/min)
Operating Pressure / Presión de Trabajo bar (psi)	160 - 180 bar (2,321 - 2,611 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	160 - 180 bar (2,320 - 2,610 psi)	180 - 200 bar (2,610 - 2,900 psi)
Hose Diameter / Diámetro de Manguera in	1 1/4 in	1 1/4 in	1 1/4 in	1 1/4 in	1 1/4 in	1 1/4 in	1 1/4 in
Performance / Rendimiento							
Impact Rate / Rango de Impacto bpm	250 - 400 bpm	300 - 500 bpm	300 - 550 bpm	280 - 560 bpm	250 - 500 bpm	250 - 550 bpm	300 - 600 bpm
Impact Energy / Energía de Impacto J (ft-lb)	10,000 J (7,376 ft-lb)	10,500 J (7,744 ft-lb)	10,000 J (7,375 ft-lb)	10,500 J (7,744 ft-lb)	10,200 J (7,523 ft-lb)	10,000 J (7,375 ft-lb)	11,000 J (8,113 ft-lb)
Tool Diameter / Diámetro de la Punta mm (in)	160 mm (6.30 in)	160 mm (6.30 in)	160 mm (6.30 in)	165 mm (6.50 in)	155 mm (6.10 in)	160 mm (6.30 in)	160 mm (6.30 in)
Gas Pressure / Presión de Gas bar (psi)	9 bar (131 psi)	15 bar (217 psi)	16 bar (232 psi)	N/A (Solid Body)	15 bar (217 psi)	15 bar (217 psi)	N/A