



Characteristic / Característica	RHINO (Modelo: 47 BE)	Caterpillar (Modelo : B6 / H55E)	Bobcat (Modelo : HB980)	Epiroc (Modelo : SB 302)	John Deere (Modelo : HH60C)	JCB (Modelo : HM033T)	Indeco (Modelo : HP 500)
General / General							
Brand / Marca	RHINO	Caterpillar	Bobcat	Epiroc (Atlas Copco)	John Deere	JCB	Indeco
Model / Modelo	47 BE	B6 / H55E	HB980	SB 302	HH60C	HM033T	HP 500
Carrier Type / Tipo de Equipo Portador	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora
Carrier Weight Class / Clase de Equipo kg (lb)	4,000 - 7,000 kg (8,800 - 15,400 lb)	3,000 - 6,000 kg (6,600 - 13,200 lb)	3,500 - 6,500 kg (7,700 - 14,300 lb)	4,500 - 9,000 kg (9,900 - 19,800 lb)	3,500 - 6,500 kg (7,700 - 14,300 lb)	3,500 - 8,000 kg (7,700 - 17,600 lb)	3,500 - 7,000 kg (7,700 - 15,400 lb)
Operating Weight / Peso Operativo kg (lb)	275 kg (606 lb)	260 kg (573 lb)	290 kg (639 lb)	300 kg (660 lb)	280 kg (617 lb)	330 kg (727 lb)	320 kg (705 lb)
Dimensions / Dimensiones							
Height (Incl. Tool) / Altura (Incl. Punta) mm (in)	1,600 mm (63.0 in)	1,450 mm (57.1 in)	1,480 mm (58.2 in)	1,350 mm (53.1 in)	1,490 mm (58.6 in)	1,450 mm (57.1 in)	1,450 mm (57.1 in)
Hydraulics / Sistema Hidráulico							
Required Oil Flow / Caudal Requerido L/min (gal/min)	30 - 45 L/min (8.0 - 12.0 gal/min)	35 - 65 L/min (9.2 - 17.2 gal/min)	40 - 75 L/min (10.5 - 19.8 gal/min)	50 - 80 L/min (13.2 - 21.1 gal/min)	40 - 70 L/min (10.5 - 18.5 gal/min)	40 - 70 L/min (10.5 - 18.5 gal/min)	40 - 70 L/min (10.5 - 18.5 gal/min)
Operating Pressure / Presión de Trabajo bar (psi)	95 - 130 bar (1,378 - 1,885 psi)	120 - 150 bar (1,740 - 2,175 psi)	120 - 140 bar (1,740 - 2,030 psi)	100 - 150 bar (1,450 - 2,175 psi)	100 - 130 bar (1,450 - 1,885 psi)	120 - 150 bar (1,740 - 2,175 psi)	120 - 140 bar (1,740 - 2,030 psi)
Hose Diameter / Diámetro de Manguera in	1/2 in	1/2 in	1/2 in	1/2 in	1/2 in	1/2 in	1/2 in
Performance / Rendimiento							
Impact Rate / Rango de Impacto bpm	500 - 900 bpm	500 - 1,000 bpm	600 - 1,100 bpm	600 - 1,400 bpm	600 - 1,000 bpm	500 - 1,000 bpm	580 - 1,180 bpm
Impact Energy / Energía de Impacto J (ft-lb)	690 J (509 ft-lb)	700 J (516 ft-lb)	750 J (553 ft-lb)	680 J (500 ft-lb)	710 J (523 ft-lb)	700 J (516 ft-lb)	750 J (553 ft-lb)
Tool Diameter / Diámetro de la Punta mm (in)	68 mm (2.68 in)	68 mm (2.68 in)	72 mm (2.83 in)	80 mm (3.15 in)	70 mm (2.75 in)	68 mm (2.68 in)	65 mm (2.56 in)
Gas Pressure / Presión de Gas bar (psi)	16 bar (232 psi)	15 bar (217 psi)	15 bar (217 psi)	N/A (Solid Body)	15 bar (217 psi)	15 bar (217 psi)	N/A