



Characteristic / Característica	RHINO (Modelo: 714 BE)	Caterpillar (Modelo : B8)	Bobcat (Modelo : HB1180)	Epiroc (Modelo : SB 452)	John Deere (Modelo : HH80C)	JCB (Modelo : HM045T)	Indeco (Modelo : HP 900)
General / General							
Brand / Marca	RHINO	Caterpillar	Bobcat	Epiroc (Atlas Copco)	John Deere	JCB	Indeco
Model / Modelo	714 BE	B8	HB1180	SB 452	HH80C	HM045T	HP 900
Carrier Type / Tipo de Equipo Portador	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora	Backhoe / Mini Excavator / Retroexcavadora / Miniexcavadora
Carrier Weight Class / Clase de Equipo kg (lb)	7,000 - 14,000 kg (15,400 - 31,000 lb)	6,000 - 12,000 kg (13,200 - 26,400 lb)	5,000 - 9,000 kg (11,000 - 19,800 lb)	6,500 - 13,000 kg (14,300 - 28,600 lb)	5,000 - 10,000 kg (11,000 - 22,000 lb)	6,000 - 12,000 kg (13,200 - 26,400 lb)	7,000 - 14,000 kg (15,400 - 30,800 lb)
Operating Weight / Peso Operativo kg (lb)	500 kg (1,102 lb)	550 kg (1,212 lb)	400 kg (882 lb)	440 kg (970 lb)	450 kg (992 lb)	450 kg (992 lb)	550 kg (1,212 lb)
Dimensions / Dimensiones							
Height (Incl. Tool) / Altura (Incl. Punta) mm (in)	2,101 mm (83.0 in)	1,850 mm (72.8 in)	1,750 mm (68.9 in)	1,600 mm (63.0 in)	1,780 mm (70.1 in)	1,800 mm (70.9 in)	1,820 mm (71.6 in)
Hydraulics / Sistema Hidráulico							
Required Oil Flow / Caudal Requerido L/min (gal/min)	45 - 85 L/min (12.0 - 22.5 gal/min)	50 - 100 L/min (13.2 - 26.4 gal/min)	55 - 100 L/min (14.5 - 26.4 gal/min)	55 - 100 L/min (14.5 - 26.4 gal/min)	50 - 90 L/min (13.2 - 23.8 gal/min)	50 - 90 L/min (13.2 - 23.8 gal/min)	60 - 100 L/min (15.8 - 26.4 gal/min)
Operating Pressure / Presión de Trabajo bar (psi)	130 - 150 bar (1,885 - 2,176 psi)	130 - 150 bar (1,885 - 2,175 psi)	120 - 150 bar (1,740 - 2,175 psi)	100 - 150 bar (1,450 - 2,175 psi)	130 - 150 bar (1,885 - 2,175 psi)	130 - 150 bar (1,885 - 2,175 psi)	130 - 150 bar (1,885 - 2,175 psi)
Hose Diameter / Diámetro de Manguera in	3/4 in	3/4 in	3/4 in	3/4 in	3/4 in	3/4 in	3/4 in
Performance / Rendimiento							
Impact Rate / Rango de Impacto bpm	400 - 800 bpm	400 - 800 bpm	600 - 900 bpm	550 - 1,000 bpm	500 - 900 bpm	500 - 900 bpm	400 - 850 bpm
Impact Energy / Energía de Impacto J (ft-lb)	1,300 J (959 ft-lb)	1,400 J (1,032 ft-lb)	1,200 J (885 ft-lb)	1,350 J (995 ft-lb)	1,200 J (885 ft-lb)	1,300 J (958 ft-lb)	1,500 J (1,106 ft-lb)
Tool Diameter / Diámetro de la Punta mm (in)	85 mm (3.35 in)	85 mm (3.35 in)	80 mm (3.15 in)	95 mm (3.74 in)	80 mm (3.15 in)	85 mm (3.35 in)	90 mm (3.54 in)
Gas Pressure / Presión de Gas bar (psi)	16 bar (232 psi)	15 bar (217 psi)	15 bar (217 psi)	N/A (Solid Body)	15 bar (217 psi)	15 bar (217 psi)	N/A