



Characteristic / Característica	RHINO REX75W	Komatsu PW98MR-11	Hyundai HW65A	JCB Hydradig 110W	SANY SY65W
General / General					
Brand / Marca	RHINO	Komatsu	Hyundai	JCB	SANY
Model / Modelo	REX75W	PW98MR-11	HW65A	Hydradig 110W	SY65W
Machine Type / Tipo de Máquina	Wheeled / Ruedas	Wheeled / Ruedas	Wheeled / Ruedas	Wheeled / Ruedas	Wheeled / Ruedas
Operating Weight / Peso Operativo kg (lb)	7,500 (16,535)	9,900 (21,825)	6,200 (13,668)	11,545 (25,452)	5,920 (13,051)
Engine / Motor					
Engine Make / Marca del Motor	Rhino	Komatsu	Yanmar	JCB	SANY / Isuzu
Engine Model / Modelo del Motor	RE51360	SAA4D95LE-7	4TNV98C	EcoMAX 444	4JG1
Engine Type / Tipo de Motor	4-Stroke Diesel / Diésel 4 Tiempos	4-Stroke Diesel / Diésel 4 Tiempos	4-Stroke Diesel / Diésel 4 Tiempos	4-Stroke Diesel / Diésel 4 Tiempos	4-Stroke Diesel / Diésel 4 Tiempos
Aspiration / Aspiración	Natural / Natural	Turbocharged / Turbo	Turbocharged / Turbo	Turbocharged / Turbo	Natural / Natural
Number of Cylinders / Número de Cilindros	4	4	4	4	4
Gross Power / Potencia Bruta kW (hp)	51.0 (68.0)	50.7 (68.0)	48.0 (64.3)	81.0 (109.0)	45.0 (60.0)
Displacement / Desplazamiento L (cu. in)	3.0 (183.0)	3.2 (199.0)	3.3 (201.4)	4.4 (268.5)	3.0 (183.0)
Fuel System / Sistema de Combustible	Direct Inj. / Inyección Directa	Common Rail	Common Rail	Common Rail	Direct Inj. / Inyección Directa
Drivetrain & Wheels / Tren de Rodaje y Ruedas					
Tire Size / Tamaño de Neumático	14-17.5 (6 Ruedas)	8.25-20	12-16.5	9.00-20	8.25-16
Max. Travel Speed (Low/High) / Velocidad kph (mph)	8.0 / 30.0 (5.0 / 19.0)	10.0 / 30.0 (6.2 / 18.6)	10.0 / 29.0 (6.2 / 18.0)	20.0 / 40.0 (12.4 / 24.8)	10.0 / 30.0 (6.2 / 18.6)
Hydraulics / Sistema Hidráulico					
Hydraulic Pump Type / Tipo de Bomba Hidráulica	Axial Piston / Pistones Axiales	Variable Displacement / Caudal Variable	Variable Displacement / Caudal Variable	Variable Displacement / Caudal Variable	Variable Displacement / Caudal Variable
Pump Capacity / Capacidad de Bomba L/min (gpm)	2 x 150 (2 x 40.0)	1 x 160 (1 x 42.3)	2 x 60 (2 x 15.8)	1 x 138 (1 x 36.4)	2 x 55 (2 x 14.5)
System Relief Pressure / Presión de Alivio Mpa (psi)	18.0 (2,611)	26.5 (3,843)	22.0 (3,190)	28.0 (4,061)	22.0 (3,190)
Excavator Performance / Rendimiento de Excavación					
Standard Bucket Capacity / Cap. Cucharón m ³ (cu. yd)	0.35 (0.46)	0.28 (0.36)	0.18 (0.24)	0.31 (0.40)	0.28 (0.36)
Max. Digging Depth / Prof. Máxima Excavación mm (ft)	3,450 (11.3)	4,305 (14.1)	3,500 (11.5)	3,310 (10.8)	3,490 (11.4)
Max. Reach at Ground Level / Alcance Máximo mm (ft)	5,670 (18.6)	7,160 (23.5)	6,150 (20.1)	6,450 (21.1)	6,050 (19.8)
Max. Dumping Height / Altura Máx. Descarga mm (ft)	3,000 (9.8)	5,640 (18.5)	4,340 (14.2)	5,290 (17.3)	4,250 (13.9)
Bucket Digging Force / Fuerza Cucharón kN (lbf)	60.0 (13,489)	60.3 (13,556)	40.9 (9,194)	49.6 (11,150)	45.0 (10,116)
Arm Digging Force / Fuerza de Brazo kN (lbf)	45.0 (10,116)	42.1 (9,464)	27.0 (6,069)	31.8 (7,148)	31.0 (6,969)
Dimensions / Dimensiones					
Overall Transport Length / Longitud Transporte mm (ft)	6,500 (21.3)	5,900 (19.3)	6,100 (20.0)	5,899 (19.3)	5,920 (19.4)
Overall Cab Height / Altura a Cabina mm (ft)	1,650 (5.4)	2,755 (9.0)	2,850 (9.3)	2,988 (9.8)	2,880 (9.4)
Overall Width / Ancho Total mm (ft)	2,200 (7.2)	2,350 (7.7)	1,920 (6.2)	2,420 (7.9)	1,970 (6.4)
Wheelbase / Distancia entre Ejes mm (ft)	2,265 (7.4)	2,350 (7.7)	2,100 (6.8)	2,650 (8.6)	2,100 (6.8)
Maintenance Capacities / Capacidades de Llenado					
Fuel Tank / Tanque de Combustible L (gal)	130.0 (34.0)	130.0 (34.3)	120.0 (31.7)	165.0 (43.5)	130.0 (34.3)
Hydraulic Tank / Tanque Hidráulico L (gal)	100.0 (26.0)	90.0 (23.7)	70.0 (18.4)	114.0 (30.1)	85.0 (22.4)
Engine Oil / Aceite de Motor L (gal)	21.0 (6.0)	11.5 (3.0)	11.6 (3.0)	14.0 (3.7)	11.0 (2.9)