



| Characteristic / Característica                            | RHINO<br>RWCW-180                         | TigerCat M726G            | Barko 930B                 | CMI C300W                 |
|------------------------------------------------------------|-------------------------------------------|---------------------------|----------------------------|---------------------------|
| <b>General / General</b>                                   |                                           |                           |                            |                           |
| Brand / Marca                                              | RHINO                                     | TigerCat                  | Barko                      | CMI                       |
| Model / Modelo                                             | RWCW-180                                  | M726G                     | 930B                       | C300W                     |
| Machine Type / Tipo de Equipo                              | Wheeled Mulcher / Trituradora Ruedas      | Wheeled Forestry Mulcher  | Wheeled Industrial Mulcher | Wheeled Forestry Mulcher  |
| Drive Type / Tipo de Tracción                              | 4-Wheel Pneumatic / 4x2-4x4 Neumática     | 4-Wheel Drive / 4x4       | 4-Wheel Drive / 4x4        | 4-Wheel Drive / 4x4       |
| Operating Weight (w/ std. head) / Peso Total kg (lb)       | ~20,500 (~45,195 / 22.6 US ton)           | 21,200 (46,738)           | 20,800 (45,856)            | 19,800 (43,651)           |
| Operating Weight (w/o head) / Peso sin Cabezal kg          | 18,000 (39,683 / 19.84 US ton)            | 18,600 (41,006)           | 18,300 (40,344)            | 17,200 (37,919)           |
| <b>Engine &amp; Power / Motor y Potencia</b>               |                                           |                           |                            |                           |
| Engine Make / Marca del Motor                              | Cummins                                   | Cummins                   | Cummins                    | Cummins                   |
| Engine Model / Modelo del Motor                            | QSL 8.9L                                  | QSL9                      | QSL9                       | QSL9                      |
| Maximum Power / Potencia Máxima kW (HP)                    | 234.0 (315.0 HP) @ 2,200 rpm              | 246.0 (330.0 HP)          | 239.0 (320.0 HP)           | 224.0 (300.0 HP)          |
| Peak Torque / Torque Pico N.m (lb-ft)                      | ~1,400 (~1,033)                           | 1,425 (1,051)             | 1,400 (1,033)              | 1,350 (996)               |
| Emission Rating / Certificación Emisiones                  | Tier 3 / Tier 4 Final / Stage III-V       | Tier 4 Final / Stage V    | Tier 4 Final / Stage V     | Tier 4 Final / Stage V    |
| Fuel Tank Capacity / Cap. Tanque Combustible L (gal)       | ~450 (~119.0 US gal)                      | 510 (135.0 gal)           | 473 (125.0 gal)            | 450 (119.0 gal)           |
| <b>Drive &amp; Hydraulics / Tren de Mando e Hidráulica</b> |                                           |                           |                            |                           |
| Transmission Type / Tipo de Transmisión                    | Hydrostatic 2-speed / Hidrostático 2 vel. | Hydrostatic 2-speed       | Hydrostatic 2-speed        | Hydrostatic 2-speed       |
| Max Travel Speed / Vel. Máxima Traslado km/h (mph)         | ~14.0 (~8.7 mph)                          | 16.0 (9.9 mph)            | 15.0 (9.3 mph)             | 14.5 (9.0 mph)            |
| Working Speed / Vel. de Trabajo (Mulching) km/h            | 0 - 3.0 (0 - 1.9 mph)                     | 0 - 3.5 (0 - 2.2 mph)     | 0 - 3.2 (0 - 2.0 mph)      | 0 - 3.0 (0 - 1.9 mph)     |
| System Hydraulic Pressure / Presión Sistema bar (psi)      | ~350 (~5,076 psi)                         | 380 (5,511 psi)           | 350 (5,076 psi)            | 350 (5,076 psi)           |
| Main Hydraulic Flow / Caudal Hidráulico L/min (gpm)        | ~250 - 300 (~66 - 79 gpm)                 | 320 (84.5 gpm)            | 300 (79.2 gpm)             | 280 (74.0 gpm)            |
| Tire Size / Dimensión de Neumáticos                        | 750/65 R26                                | 28L-26 / 67x34.00-26      | 28L-26 / 30.5L-32          | 28L-26                    |
| <b>Mulching Head &amp; Cutting / Cabezal y Triturado</b>   |                                           |                           |                            |                           |
| Standard Mulching Head / Cabezal Estándar                  | Prinoth M650H-2350 / FAE 300              | TigerCat / FAE 300        | FAE 300 / Prinoth          | FAE 300 / Prinoth         |
| Cutting Width / Ancho de Corte mm (in / ft)                | 2,350 (92.5 in / 7.7 ft)                  | 2,350 (92.5 in)           | 2,350 (92.5 in)            | 2,350 (92.5 in)           |
| Max Stem Diameter / Diámetro Máximo Árbol cm (in)          | 40.0 (15.7 in)                            | 45.0 (17.7 in)            | 40.0 (15.7 in)             | 40.0 (15.7 in)            |
| Cutting Tools / Herramientas de Corte                      | Forged Steel Hammers / Martillos Forjados | Carbide Teeth / Martillos | Carbide Teeth / Martillos  | Carbide Teeth / Martillos |
| Rotor Speed / Velocidad del Rotor rpm                      | ~1,800 - 2,000                            | 1,900 - 2,100             | 1,800 - 2,000              | 1,800 - 2,000             |
| <b>Dimensions &amp; Cab / Dimensiones y Cabina</b>         |                                           |                           |                            |                           |
| Length (w/o head) / Longitud sin Cabezal mm (in)           | 6,842 (269.4 in / 22 ft 5 in)             | 6,960 (274.0 in)          | 6,880 (270.8 in)           | 6,750 (265.7 in)          |
| Overall Machine Width / Ancho Total mm (in / ft)           | 3,445 (135.6 in / 11 ft 4 in)             | 3,350 (131.9 in)          | 3,400 (133.8 in)           | 3,300 (129.9 in)          |
| Overall Machine Height / Altura Total mm (in / ft)         | 3,831 (150.8 in / 12 ft 7 in)             | 3,760 (148.0 in)          | 3,800 (149.6 in)           | 3,750 (147.6 in)          |
| Wheelbase / Distancia entre Ejes mm (in / ft)              | 3,221 (126.8 in / 10 ft 7 in)             | 3,300 (129.9 in)          | 3,250 (128.0 in)           | 3,200 (126.0 in)          |
| Ground Clearance / Distancia al Suelo mm (in)              | 725 (28.5 in)                             | 710 (28.0 in)             | 730 (28.7 in)              | 700 (27.5 in)             |
| Cab Certification / Certificación de Cabina                | EROPS / ROPS / FOPS                       | ROPS / FOPS / OPS         | ROPS / FOPS / OPS          | ROPS / FOPS / OPS         |