



| haracteristic / Característica                        | RHINO<br>RWCW-190                               | Tigercat M726G /<br>760        | Barko 930B /<br>Heavy          | CMI C500W                      |
|-------------------------------------------------------|-------------------------------------------------|--------------------------------|--------------------------------|--------------------------------|
| General / General                                     |                                                 |                                |                                |                                |
| Brand / Marca                                         | RHINO                                           | Tigercat                       | Barko                          | CMI                            |
| Model / Modelo                                        | RWCW-190                                        | M726G / 760                    | 930B Heavy                     | C500W                          |
| Machine Type / Tipo de Equipo                         | Wheeled Mulcher / Trituradora Ruedas            | Wheeled Forestry Mulcher       | Wheeled Industrial Mulcher     | Wheeled Forestry Mulcher       |
| Drive Type / Tipo de Tracción                         | 4-Wheel Pneumatic AWD / 4x4                     | 4-Wheel Drive / 4x4            | 4-Wheel Drive / 4x4            | 4-Wheel Drive / 4x4            |
| Operating Weight (w/ std. head) / Peso Total kg (lb)  | ~21,500 (~47,400 / 23.7 US ton)                 | 22,500 (49,600)                | 21,800 (48,060)                | 21,200 (46,738)                |
| Operating Weight (w/o head) / Peso sin Cabezal kg     | ~19,000 (~41,888 / 20.9 US ton)                 | 19,800 (43,651)                | 19,200 (42,328)                | 18,500 (40,785)                |
| Engine & Power / Motor y Potencia                     |                                                 |                                |                                |                                |
| Engine Make / Marca del Motor                         | Cummins / RHINO                                 | Cummins                        | Cummins                        | Cummins                        |
| Engine Model / Modelo del Motor                       | QSX15 / RHINO 554                               | QSX15                          | QSX15                          | QSX15                          |
| Gross Power / Potencia Bruta kW (HP)                  | 413-416 (554-558 HP) @<br>1,750-1,800 rpm       | 425.0 (570.0 HP)               | 402.0 (540.0 HP)               | 410.0 (550.0 HP)               |
| Max Torque / Torque Máximo N.m (lb-ft)                | 2,300-2,348 (1,697-1,732) @<br>1,450-1,500 rpm  | 2,400 (1,770)                  | 2,300 (1,697)                  | 2,350 (1,733)                  |
| Emission Rating / Certificación Emisiones             | Tier 3 / Stage IIIB                             | Tier 4 Final / Stage V         | Tier 4 Final / Stage V         | Tier 4 Final / Stage V         |
| Drive & Hydraulics / Tren de Mando e Hidráulica       |                                                 |                                |                                |                                |
| Transmission Type / Tipo de Transmisión               | High-Capacity CVT<br>(Continuously Variable)    | Hydrostatic 2-speed            | Hydrostatic 2-speed            | Hydrostatic 2-speed            |
| Max Travel Speed / Vel. Máxima Traslado km/h (mph)    | 15.0 (9.3 mph)                                  | 16.0 (9.9 mph)                 | 15.0 (9.3 mph)                 | 15.0 (9.3 mph)                 |
| Working Speed / Vel. de Trabajo (Mulching) km/h       | 0 - 3.0 (0 - 1.9 mph)                           | 0 - 3.5 (0 - 2.2 mph)          | 0 - 3.2 (0 - 2.0 mph)          | 0 - 3.0 (0 - 1.9 mph)          |
| System Hydraulic Pressure / Presión Sistema bar (psi) | ~380 (~5,511 psi)                               | 380 (5,511 psi)                | 350 (5,076 psi)                | 380 (5,511 psi)                |
| Main Hydraulic Flow / Caudal Hidráulico L/min (gpm)   | ~300 - 380 (~79 - 100 gpm)                      | 380 (100.3 gpm)                | 350 (92.5 gpm)                 | 360 (95.1 gpm)                 |
| Tire Size / Dimensión de Neumáticos                   | 800/70 R32                                      | 30.5L-32 / 73x44.00-32         | 30.5L-32                       | 30.5L-32                       |
| Mulching Head & Cutting / Cabezal y Triturado         |                                                 |                                |                                |                                |
| Standard Mulching Head / Cabezal Estándar             | RHINO RWCW-190 (equiv.<br>4061-30)              | Tigercat / FAE 500             | FAE 300 / Prinoth M700         | Prinoth M700                   |
| Head Power / Potencia al Cabezal kW (HP)              | 360.0 (483.0 HP)                                | 380.0 (510.0 HP)               | 350.0 (469.0 HP)               | 360.0 (483.0 HP)               |
| Cutting Width / Ancho de Corte mm (in / ft)           | 3,100 (122 in / 10 ft 2 in)                     | 3,100 (122 in)                 | 3,100 (122 in)                 | 3,100 (122 in)                 |
| Max Stem Diameter / Diámetro Máximo Árbol cm (in)     | 42.0 (16.5 in)                                  | 45.0 (17.7 in)                 | 42.0 (16.5 in)                 | 42.0 (16.5 in)                 |
| Cutting Tools & Rotor / Herramientas y Velocidad      | Horizontal Drum - Carbide<br>Teeth / ~2,000 rpm | Carbide Teeth Drum / 2,000 rpm | Carbide Teeth Drum / 2,000 rpm | Carbide Teeth Drum / 2,000 rpm |
| Dimensions & Ergonomics / Dimensiones y Ergonomía     |                                                 |                                |                                |                                |
| Length (w/o head) / Longitud sin Cabezal mm (in)      | ~7,600 (~299 in / 24.9 ft)                      | 7,750 (305 in)                 | 7,650 (301 in)                 | 7,550 (297 in)                 |
| Overall Machine Width / Ancho Total mm (in / ft)      | 3,650 (143.7 in / 11.97 ft)                     | 3,600 (141.7 in)               | 3,620 (142.5 in)               | 3,580 (140.9 in)               |
| Overall Machine Height / Altura Total mm (in / ft)    | ~3,600 (~141.7 in / 11.8 ft)                    | 3,750 (147.6 in)               | 3,700 (145.7 in)               | 3,680 (144.9 in)               |
| Wheelbase / Distancia entre Ejes mm (in / ft)         | 3,256 (128.2 in / 10 ft 8.2 in)                 | 3,350 (131.9 in)               | 3,300 (129.9 in)               | 3,250 (128.0 in)               |
| Ground Clearance / Distancia al Suelo mm (in)         | ~450 (~17.7 in)                                 | 460 (18.1 in)                  | 450 (17.7 in)                  | 450 (17.7 in)                  |
| Cab Certification / Certificación de Cabina           | EROPS / ROPS / FOPS                             | ROPS / FOPS / OPS              | ROPS / FOPS / OPS              | ROPS / FOPS / OPS              |