RHINO
EQUIPMENT

POWERING
A STRONGER
TOMORROW

BUILT
TO PERFORM

PEOPLE
PRODUCTS
SUPPORT
GLOBAL REACH

# EQUIPMENT CATALOG

SOLUTIONS FOR A REAL WORLD




I MAKE AMERICA.

AMERICAN
STRENGTH.
GLOBAL IMPACT.

www.rhinoequipment.us
info@rhinoequipment.us

# TABLE OF CONTENTS


4




WHEEL LOADERS, MOTORGRADERS

5




EXCAVATORS, BULLDOZERS

6




WHEEL EXCAVATORS, BACKHOES

7




WHEEL DOZERS, PIPELAYERS, TRACK LOADERS

8




SKID STEERS, TRUCKS

9




COLD PLANERS, ASPHALT PAVERS

10




TANDEM ROLLERS, PNEUMATIC ROLLERS

11




SOIL COMPACTORS, VIBRATORY COMPACTORS

12




FORKLIFTS, REACH STACKERS

13




LIGHT TOWERS, ATTACHMENTS

14




TOWER CRANES, HAMMERS

15




POWER GENERATORS

16



MINING

17



AGRICULTURE

18



TELEHANDLERS




**Rhino Equipment® is the result of the collaboration of various private equity business groups with more than 25 years of experience in manufacturing, production, and commercialization of machines for construction, demolition, mining, and power generation with applications and acceptance around the globe.**



In our assembly plants we apply the best practices, standard processes, and global standards to improve safety, quality, speed, and cost. This allows us to make products more efficiently and meet deadlines more consistently, and to have a better response from the time an order arrives until the product is delivered.




Your Rhino® dealer provides peace of mind with expert parts and service support. Factory-trained technicians will service your equipment promptly and maintain your investment.




Need to add equipment to fulfill a new stimulus contract? Feel saddled with old, inefficient construction and mining equipment? Now Rhino Equipment® can help, with our new full machinery line 0% / low monthly finance program. It's a great way for constructors, contractors and engineers to finance and acquire productive and reliable new machinery with a single phone call.




Our genuine Rhino® parts are designed to work in perfect harmony with your machine for optimum performance and productivity.

Rhino® uses superior materials and exacting manufacturing processes to keep our customers up and running.



Equipment specifications and images may change without previous notice

# WHEEL LOADERS



| SPECIFICATIONS | RWL65 | RWL102 | RWL132 | RWL163 | RWL186 | RWL235 | RWL315 |
|---|---|---|---|---|---|---|---|
| **Engine** | 4BT3.3-C | 6BT5.9-C | 6BTA5.9 or QSB5.9 | 6CTA8.3-C215 | 6CTAA8.3-C | 6CTA8.3 / 6LTAA8.9 | QSM11 |
| **Rated Output** kW (hp)@rpm | 74(100)2,200 | 87(117)2,200 | 97(130) / 126 (169)2,200 | 160(215)2,200 | 179(240)2,200 | 216(290)2,200 | 250(335)2,100 |
| **Operational Weight** Kg (lb) | 6,550(14,440) | 10,200(22,487) | 13,200(29,101) | 16,300(35,935) | 18,600(41,006) | 23,500(51,809) | 31,500(69,446) |
| **Rated Load** Kg (lb) | 1,880(3,968) | 3,000(6,614) | 4,000(8,818) | 5,000(11,023) | 6,000(13,228) | 7,500(16,535) | 9,000(19,842) |
| **Bucket Capacity** m3 (cu.Yd) | 1.0(1.3) | 1.4(1.8) | 2.0(2.6) | 2.5(3.3) | 3.0(3.9) | 3.5(4.6) | 4.4(5.8) |
| **Breakout Force kN** (lbf) | 57(12,566) | 96(21,164) | 134(29,542) | 150(33,069) | 186(41,006) | 220(48,502) | 264(58,202) |

### Options



Waste Handling



General Purpose



Pallet Forks

Buckets can be custom made depending on client requirements such as a bigger bucket for lighter material handling or clam buckets or among many other options.

**Other Options:** Tier 2, Tier 3, Tier 4 Engine, Pallet forks, Grapples, ROPS, FOPS cab, A/C, Solid Tires, Hydraulic Line, and more...




# MOTOR GRADERS



| SPECIFICATIONS | RM80 | RM120 | RM123 | RM138 | RM165 | RM166 |
|---|---|---|---|---|---|---|
| **Engine** | RM80-4J12T or Cummins 4BT | RM80-4J12T or Cummins 4BT | RD140-8A or Cummins 6CTAA | 6CTA8.3 | QSB6 | RHCB220 |
| **Rated Output** kW (hp)@rpm | 60(80)2,800 | 85(114)2,400 | 132(177)2,200 | 142(190)2,200 | 164(220)2,200 | 164(220)2,200 |
| **Operational Weight** Kg (lb) | 6,000(13,228) | 6,110(13,470) | 14,500(31,967) | 15,200(33,510) | 16,400(36,156) | 16,600(36,597) |
| **Length** mm (ft) | 6,800(22.3) | 6,900(22.6) | 8,615(28.3) | 9,140(30) | 9,140(29.5) | 8,990(29.5) |
| **Blade Length** mm (ft) | 2,200(7.2) | 2,200(7.2) | 3,660(12) | 4,270(14) | 4,320(14.2) | 4,320(14.2) |

### Options



Dozer Blade



Rear Ripper



Front V Blade



Mid Body Scarifier

Rhino Motor Graders come standard with rear ripper. They can come with front scarifier, front dozer blade, mid-body scarifier, and rear scarifier. As well as many other options depending on client requirements.

**Other Options:** Tier 2, Tier 3, Tier 4 Engine, Front V Scarifier, Front V dozer Blade, Rear Ripper 5 Shank, Rear Ripper 3 Shank, All Wheel Drive, A/C, ROPS/FOPS, and more...








Equipment specifications and images may change without previous notice

# EXCAVATORS



| SPECIFICATIONS | REX10 | REX15 | REX20 | REX30 | REX40 | REX42 | REX50 | REX60 | REX80 |
|---|---|---|---|---|---|---|---|---|---|
| **Engine** | Kubota Z482 | Kubota D722 | Kubota D1105 | Kubota D1105 | Kubota D1703 | Yanmar 4TNV88 | Yanmar 4TNV94L | Kubota V2607 | Kubota V2607 |
| **Rated Output** kW (hp)@rpm | 10(13.4)2,500 | 10.2 (13.7)2,200 | 14(18.8)2,200 | 14(18.8)2,200 | 18.2 (24.4)2,200 | 25(34)2,200 | 36.9(50)2,100 | 42.4 (56.9)2,000 | 42.4 (56.9)2,000 |
| **Operational Weight** Kg (lb) | 1,000(2,205) | 1,500(3,307) | 2,000(4,409) | 3,000(6,614) | 4,000(8,818) | 4,200(9,259) | 5,710(12,588) | 6,000(13,228) | 8,000(17,637) |
| **Max. Digging Depth** mm (ft) | 1,880(6.2) | 1,980(6.5) | 2,630(8.6) | 2,990(9.8) | 2,990(9.8) | 3,076(10.1) | 3,935(12.9) | 3,935(12.9) | 4,038(13.2) |
| **Bucket Capacity** m3 (cu.Yd) | 0.06 (0.08) | 0.025 (0.03) | 0.07 (0.09) | 0.1 (0.13) | 0.12 (0.16) | 0.17 (0.22) | 0.28 (0.36) | 0.21 (0.27) | 0.35 (0.46) |



| SPECIFICATIONS | REX130 | REX150 | REX210 | REX230 | REX330 | REX360 | REX450 | REX700 | REX800 |
|---|---|---|---|---|---|---|---|---|---|
| **Engine** | 4BTAA3.9/ QSF3.8 | Kubota V3800 | V50009/ QSB6.7/ 6BTAA5.9 | Kubota V5009 | 6BTAA5.9/ 6BG1TRP | 6CTAA8.3-C | QSM11 | QSX15 | QSM15 77C/ 6WG1 |
| **Rated Output** kW (hp)@rpm | 86(115)2,200 | 95 (127.4)2,200 | 133(178)/125 (168)2,000 | 155 (207.9)2,200 | 241(323)2,000 | 192(257)2,000 | 251(337)2,200 | 264(354)1,800 | 563(755)/ 377 (506)2,100 |
| **Operational Weight** Kg (lb) | 13,000 (28,660) | 15,000 (33,069) | 21,354 (47,078) | 23,000 (50,706) | 33,000 (72,753) | 34,500 (76,059) | 45,800 (100,972) | 70,000 (154,324) | 76,500 (168,653) |
| **Max. Digging Depth** mm (ft) | 5,500(18) | 6,200(20.4) | 6,515(21.4) | 6,480(21.3) | 7,370(24.2) | 7,370(24.2) | 7,810(25.6) | 7,185(23.6) | 7,050(23.1) |
| **Bucket Capacity** m3 (cu.Yd) | 0.53 (0.7) | 0.6 (0.78) | 1 (1.3) | 1.1 (1.44) | 1.4 (1.8) | 1.6 (2.1) | 2.1 (2.7) | 4 (5.2) | 5(6.5) |

### Options

Rhino excavators come standard with the hydraulic line for attachments. Attachments include hydraulic hammers, thumb cutters, and many more.

**Other Options:** Tier 2, Tier 3, Tier 4, EPA 4 (EURO 5) Engine, Rakes, Compactors, Cutters, Augers, Grapples, Longer Arm Length, Grinders, Rock Buckets and more...




# BULLDOZERS



| SPECIFICATIONS | RD8 | RD13 | RD15 | RD17 | RD24 | RD36 | RD50 | RD55 |
|---|---|---|---|---|---|---|---|---|
| **Engine** | 4BTA3.9 | 6BT5.9 | RD140-8A | RH52E871 | NT855/NTA855 | NTA855 | KTA19-C525 | QSK19 |
| **Rated output** kW (hp)@rpm | 70(94)2,300 | 93(125)2,600 | 105(140)1,500 | 131(176)1,850 | 175(235) / 209 (280)1,800 | 257(345)2,000 | 308(413)2,000 | 388(520)1,800 |
| **Operational weight** Kg(lb) | 8,480(18,695) | 13,000(28,660) | 15,800(34,833) | 16,500(36,376) | 23,450(51,698) / 30,700(67,681) | 35,900(79,146) | 49,500(109,129) | 61,500(135,584) |
| **Blade width** mm (ft) | 2,480(8.1) | 3,135(10.3) | 3,200(10.5) | 3,416(11.2) | 3,823(12.5) | 4,130(13.5) | 4,314(14.2) | 4,695(15.4) |

### Options


Waste Blade


Semi U Blade


Multi Shank Ripper


Single Shank Ripper

Blades can be custom made depending on client requirements such as a bigger blade for lighter material handling or among many other options.

**Other Options:** Tier 2, Tier 3, Tier 4 Engine, Triple Grouser Shoes, Swamp Shoes, Angle Blade, Straight Blade, Pat Blade, 6 - Way Blade, U-Blade, Semi-U Blade, Waste Blade, and more...








Equipment specifications and images may change without previous notice

# WHEEL EXCAVATORS




| SPECIFICATIONS | REX60W | REX74CW | REX75W | REX210W |
|---|---|---|---|---|
| **Engine** | Rhino A498BPG | Rhino A498BPG | Cummins QSF2.8 | Cummins 6BT5.9 |
| **Rated Output** kW (hp)@rpm | 45(60)2,500 | 45(60)2,500 | 53(71)2,200 | 112(150)2,200 |
| **Operational Weight** Kg (lb) | 5,980(13,184) | 7,400(16,314) | 7,090(15,630) | 20,600(45,415) |
| **Max. Digging Depth** mm (ft) | 2,857(9.4) | 2,990(9.8) | 3,930(12.8) | 6,330(20.8) |
| **Bucket Capacity** m3 (cu.Yd) | 0.2(0.3) | 0.2(0.3) | 0.2(0.3) | 1(1.3) |




### Options


Hydraulic Hammers


General Purpose Buckets


Shears


Dozer Blades

Rhino excavators can come with hydraulic line for attachments. Attachments include hydraulic hammers, thumb cutters, and many more.

**Other Options:** Tier 2, Tier 3, Tier 4 Engine, Rakes, Compactors, Cutters, Augers, Grapples, Longer Arm Length, Grinders, Rock Buckets and more...

# BACKHOE LOADERS



| SPECIFICATIONS | RBH70 |
|---|---|
| **LOADER** | |
| **Engine** | 4BTA3.9 |
| **Rated Output** kW (hp)@rpm | 82(110) / 60(80)2,200 |
| **Operational Weight** Kg (lb) | 7,600(16,755) |
| **Rated Load** kg (lb) | 2,750(6,063) |
| **Max. Load Breakout Force kN** (lb) | 44(9,892) |
| **BACKHOE** | |
| **Rated Digging Capacity** m3 (cu.Yd) | 0.3(0.4) |
| **Max. Digging Depth** mm (ft) | 4,340(14.2)/6,000(19.7) |
| **Max. Digging Force kN (ft)** | 55(12,364) |
| **Max. Dumping Height** mm (ft) | 3,640(11.9)/4,930(16.2) |
| **Bucket Size Range** mm (in) | 305-813(12-32) |




### Options


Hydraulic Hammers


General Purpose Buckets


4 in 1 Buckets

Rhino backhoes can come with the hydraulic line for attachments. Attachments include hydraulic hammers, thumb cutters, and many more.

**Other Options:** Tier 2, Tier 3, Tier 4 Engine, Heavy Duty Bucket, Trench Hoe Bucket, Bucket Quick Couplers, Grapples, Pallet Forks, Augers, A/C, ROPS/FOPS, and more...





Equipment specifications and images may change without previous notice

# WHEEL DOZERS





| SPECIFICATIONS | RWD132 | RWD235 | RWD315 |
|---|---|---|---|
| **Engine** | 6BTA5.9 | 6CTA8.3/6LTAA8.9 | QSM11 |
| **Rated Output** kW (hp) @ rpm | 132(180)2,200 | 179/(240)/178 (238)2,200/220 (295)2,100 | 220(300)2,100 |
| **Operational Weight** Kg (lb) | 13,000(28,660) | 21,000(46,297)/ 22,200(48,943)/ 23,000(50,706) | 26,500 (58,422) |
| **Blade Width** mm (ft) | 3,300(10.8) | 3,600(11.8) | 4,500(14.7) |
| **Blade Capacity** m3 (cu. Yd) | 3.0(3.9) | 4.5(5.9) | 5.3(6.9) |



### Options


Waste Blade


Semi U Blade


Multi Shank Ripper

Blades can be custom made depending on client requirements such as a bigger blade for snow, lighter material handling or among many other options.

**Other Options:** Tier 2, Tier 3, Tier 4 Engine, Angle Blade, Straight Blade, U-Blade, Semi-U Blade, Waste Blade, and more...

# TRACK LOADERS





| SPECIFICATIONS | RTL17 | RTL24 | RTL36 |
|---|---|---|---|
| **Engine** | Rhino C6 | Cummins NT855 | Cummins NTA855 |
| **Rated Output** kW (hp) @ rpm | 131(176)1,850 | 164(220)2,000 | 257(345)2,000 |
| **Operational Weight** Kg (lb) | 20,068(44,242) | 23,340(51,456) | 35,750(78,815) |
| **Bucket Capacity** m3 (cu. Yd) | 1.7(2.2) | 2.3(3.0) | 3.7(4.8) |



### Options


Waste Handling


General Purpose


Multi Shank Ripper

Buckets can be custom made depending on client requirements such as a bigger bucket for lighter material handling or clam buckets or among many other options.

**Other Options:** Tier 2, Tier 3, Tier 4 Engine, Pallet forks, Grapples, ROPS, FOPS cab, Triple Grouser Shoes, Swamp Shoes, Hydraulic Line, and more...

# PIPELAYERS





| SPECIFICATIONS | RPL25 | RPL45 | RPL70 |
|---|---|---|---|
| **Engine** | Rhino WD | Cummins NT855 | Cummins NTA855 |
| **Rated Output** kW (hp) @ rpm | 120(161)1,850 | 169(227)2,000 | 235(315)2,000 |
| **Operational Weight** Kg (lb) | 22,000(48,502) | 34,000(74,957) | 47,500(104,720) |
| **Lifting Capacity** kg (lb) | 25,000(55,116) | 45,000(99,208) | 70,000(154,324) |



### Options





Tier 2, Tier 3, Tier 4 Engine, Triple Grouser Shoes, Swamp Shoes, 610mm Shoes, 1,100 mm Shoes, A/C, ROPS/FOPS, Central Lubrication, and more...





Equipment specifications and images may change without previous notice

# SKID STEERS



| SPECIFICATIONS | RS50-S | RS60-S | RS70-S |
|---|---|---|---|
| **Engine** | Rhino A498BPG | Rhino RHA4C6-88C33/ Kohler KDI2504TCR | Rhino RH4J1/ Perkins 1104C-44T |
| **Rated Output** kW (hp)@rpm | 45(60)2,500 | 65(84)2,200/55.4 (74.3)2,600 | 85(113)2,200/74.5 (99.9)2,300 |
| **Operational Weight** Kg (lb) | 3,100(6,834) | 3,520(7,760) | 4,260(9,391) |
| **Rated Load** Kg (lb) | 1,060(2,337) | 1,100(2,425) | 1,400(3,086) |
| **Bucket Capacity** m3 (cu. Yd) | 0.47(0.6) | 0.55(0.7) | 0.55(0.7) |
| **Tires** | 10-16.5 | 12-16.5 | 12.16.5 |

### Options






Tier 2, Tier 3, Tier 4 Engine, FOPS/ROPS Cab, Central Lubrication System, High Flow Pump, Augers, Backhoe, Bale Movers, Dozer Blade, Snow Blade, Boom Lifts, Hydraulic Hammers, Brooms, Waste Bucket, 4 in 1 Bucket, High Dump Bucket, Skeleton Rock Bucket, Utility Fork Bucket, Chipper, Cold Planers, Cement Mixer, Grader Blade, Grapples, Hitch Adapter, Mowers, Pallet Forks, Rakes, Rock Wheel, Roto Tiller, Scarifier, Scrapers, Snow Blower, Spreaders, Solid Tires, Grouser Tracks, Trench Filler, and more...

# TRUCKS



| OFF-HIGHWAY TRUCKS | RT50 | RT70 | RT100 |
|---|---|---|---|
| **Engine** | QSX15 | QSK23 | QST30 |
| **Rated Output** kW (hp)@rpm | 392 (526) 2,100 | 567 (760) 2,100 | 783 (1,050) 2,100 |
| **Operational Weight** Kg (lb) | 35,890 (79,124) | 46,000 (101,413) | 69,000 (152,119) |
| **Body Capacity** m3 (cu. Yd) | 28.0 (36.6) | 41.0 (53.6) | 58.0(75.9) |
| **Payload** kg (lb) | 45,000 (99,208) | 65,000 (143,300) | 91,000 (200,621) |




| ARTICULATED TRUCKS | RADT30 | RADT40 | RADT60 |
|---|---|---|---|
| **Engine** | M11 | M11 | QSK19 |
| **Rated Output** kW (hp)@rpm | 330(442) 2,200 | 350(469) 2,400 | 522 (700) 2,000 |
| **Operational Weight** Kg (lb) | 53,000 (116,845) | 73,000 (160,937) | 108,000 (238,099) |
| **Carriage Capacity** m3 (cu. Yd) | 13.9 (18.1) | 18.5 (24.1) | 31.0 (40.5) |
| **Payload** kg (lb) | 30,000(66,138) | 39,000(85,980) | 60,000(132,277) |



| MINING TRUCKS | RMT50 | RMT55 | RMT60 | RMT80 |
|---|---|---|---|---|
| **Engine** | Rhino WD50 | Rhino WD55 | Rhino WD60 | Rhino T12 |
| **Rated Output** kW (hp)@rpm | 247(331) 2,200 | 279(374) 2,400 | 309 (414) 2,100 | 279 (374) 2,000 |
| **Operational Weight** Kg (lb) | 22,000 (48,502) | 22,000 (48,502) | 25,000 (55,116) | 26,000 (57,320) |
| **Body Capacity** m3 (cu. Yd) | 25.4 (33.2) | 25.4 (33.2) | 27.2 (35.6) | 36.4 (47.6) |
| **Payload** kg (lb) | 50,000(110,231) | 55,000(121,254) | 60,000(132,277) | 80,000(176,370) |

### Options



Tier 2, Tier 3, Tier 4 Engine, Engine Brake, Central Lubrication, External Cameras, 16.00 R25 Tires, A/C, and more...


# COLD PLANERS



| SPECIFICATIONS | RCP500W | RCP1000W | RCP1300W | RCP2100T |
|---|---|---|---|---|
| **Engine** | Deutz F4 | Rhino SC8D190G2B1 | Rhino SC8D190G2B1 | Cummins QSX15 |
| **Rated Output** kW (hp)@rpm | 46(62)2,200 | 140(188)2,200 | 140(188)2,200 | 447(599)2,100 |
| **Operational Weight** Kg (lb) | 4,800(10,582) | 15,500(34,172) | 15,800(34,833) | 32,500(71,650) |
| **Milling Width** mm (in) | 500(19.7) | 1,000(39.4) | 1,300(51.2) | 2,100(82.7) |
| **Milling Depth** mm (in) | 60(2.4) | 150(5.9) | 120(4.7) | 320(12.6) |




### Options



Power Milling Drum



Fine Milling Drum

Tier 2, Tier 3, Tier 4 Engine, Power Milling Drum, Fine Milling Drum, Smaller Milling Drum, Auto Leveling, Central Lubrication, 4WD, and more...

# ASPHALT PAVERS



| SPECIFICATIONS | RAP45T | RAP70T | RAP75T | RAP90T | RAP45W | RAP60W |
|---|---|---|---|---|---|---|
| **Engine** | Rhino 4J | QSB5.9-C190 | Rhino SC | QSB6.7 | Rhino 4J | QSB3.9-C125 |
| **Rated output** kW (hp)@rpm | 55(74) 2,000 | 133(178) 2,200 | 174(233) 2,000 | 194(260) 2,000 | 55(74) 2,000 | 93(125) 2,200 |
| **Operational weight** kg (lb) | 11,000 (24,251) | 18,500(40,790) | 25,000 (55,116) | 27,500(60,627) | 11,000 (24,251) | 17,000(37,480) |
| **Min. Paving Width** mm (ft) | 2,500(8.2) | 2,500(8.2) | 3,000(9.8) | 3,000(9.8) | 2,500(8.2) | 2,500(8.2) |
| **Max. Paving Width** mm (ft) | 4,500(14.8) | 7,000(23.0) | 7,500(24.6) | 9,000(29.5) | 4,500(14.8) | 6,000(19.7) |







### Options



Rubber Tracks



Steel Tracks



Extension Screeds

Tier 2, Tier 3, Tier 4 Engine, Infrared Heating Screed, Full Hydraulic Extension Screed, Auto-Leveling, Steel Tracks, and more...






Equipment specifications and images may change without previous notice


# TANDEM ROLLERS

| SPECIFICATIONS | RCT10H | RCT15H | RCT30H | RCT40H | RCT60H | RCT80H | RCT100H | RCT120H | RCT14H3 |
|---|---|---|---|---|---|---|---|---|---|
| **Engine** | XR420CC | 627CC | Rhino CZ380Q | Rhino ZN390Q | Rhino ZN390Q | 4BTA3.9 | 4BTA3.9 | 4BTA3.9 | 6BTAA |
| **Rated Output** kW (hp) | 13,5 (18) | 17 (23) | 26,5 (35.5) | 33,6 (45.7) | 34 (45) | 93 (125) | 93 (125) | 93 (125) | 110 (148) |
| **Operational Weight** Kg (lb) | 1,000 (2,204) | 1,500 (3,306) | 3,000 (6,614) | 4,000 (8,819) | 6,000 (13,228) | 8,000 (17,637)/ 8,900 (19,622) | 10,000 (22,046) | 12,000 (26,455) | 14,000 (30,865) |
| **Drum Width** mm (ft) | 800 (2.6) | 900 (2.9) | 1,250 (4.1) | 1,400 (4.5) | 1,350 (4.4) | 1,870 (6.1) | 2,130 (7.0) | 2,130 (7.0) | 2,130 (7.0) |
| **Exciting Force kN** (lb) | 25 (5,620) | 30 (6,744) | 60 (13,489) | 39 (8,768) | 60 (13,489) | 180 (40,466) | 230 (51,706) | 230 (51,706) | 350 (78,683) |
| **Vibration Frequency** Hz (vpm) | 70 (4,200) | 65 (3,900) | 50 (3,000) | 50 (3,000) | 50 (3,000) | 50 (3,000) | 50 (3,000) | 50 (3,000) | 55 (3,300) |

**Options**



Pressurized Water Spray



Edge Cutter

ROPS/FOPS Cab, Tier 2, Tier 3, Tier 4 Engine, Pressurized Water Spray, Anti-Freeze Kit for Water Tanks, and more...




# PNEUMATIC ROLLERS

| SPECIFICATIONS | RPR109 | RPR1611 | RPR2011 |
|---|---|---|---|
| **Engine** | 4BT3.9/6BT5.9 | 4BT5.9 | 6BTA5.9 |
| **Rated Output** kW (hp)@rpm | 73.5(98.5)2,400 | 110(148)2,400 | 125(170)2,400 |
| **Min. Operational Weight** Kg (lb) | 10,000(22,046) | 16,000(35,274) | 20,000(44,092) |
| **Max. Operational Weight** Kg (lb) | 16,000(35,274) | 26,000(57,320) | 30,000(66,139) |
| **Ballast Volume** m3 (cu. Ft) | 3.9(138) | 3.2(113) | 3.2(113) |




**Options**



Pressurized Water Spray

ROPS/FOPS Cab, Tier 2, Tier 3, Tier 4 Engine, Pressurized Water Spray, Anti-Freeze Kit for Water Tanks, and more...





Equipment specifications and images may change without previous notice

# SOIL COMPACTORS



| SPECIFICATIONS | RSC220 | RSC223 | RSC226 | RSC228 | RSC230 | RSC233 |
|---|---|---|---|---|---|---|
| **Engine** | RSC8DK20 | RSC8DK23 | RSC9DK26 | RSC9DK26 | RSC9DK30 | QSM11 |
| **Rated Output** kW (hp)@rpm | 147(197)2,200 | 147(197)2,200 | 192(257)2,200 | 192(257)2,200 | 250(335)2,200 | 250(335)2,200 |
| **Operational Weight** Kg (lb) | 20,000(44,092) | 23,000(50,706) | 26,000(57,320) | 28,000(61,729) | 30,000(66,139) | 33,000(72,753) |
| **Drum Diameter** mm (ft) | 1,500(4.9) | 1,500(4.9) | 1,620(5.3) | 1,620(5.3) | 1,620(5.3) | 1,620(5.3) |

**Options**



Waste Blade



Semi U Blade



Refuse Compaction Wheels

ROPS/FOPS Cab, Tier 2, Tier 3, Tier 4 Engine, Infrared Outside Camera, Tilt Cylinder for Blade, A/C, U-Blade, Semi-U Blade, Soil Compaction Drums, Refuse Compaction Wheels, Soil Compaction Wheels, Woodchip Blade, Coal U Blades and more...





# VIBRATORY COMPACTORS



| SPECIFICATIONS | RC30 | RC70 | RC80 | RC100 | RC120 | RC140 | RC160 | RC180 | RC200 |
|---|---|---|---|---|---|---|---|---|---|
| **Engine** | Rhino ZN | RhinoA4 | 4BT or Rhino A4 | 4BT/6BT or Rhino A4 | 4BT/6BT or Rhino A4 | 6BT5 | 6BT5 | 6BT5 | 6BT5 |
| **Rated output** kW (hp)@rpm | 22 (30)2,600 | 42(56)2,500 | 42/80 (56/ 107)2,300 | 77/110 (103/ 148)2,300 | 77/110 (103/ 148)2,300 | 110 (148)2,300 | 110 (148)2,300 | 132 (177)2,300 | 132 (177)2,300 |
| **Operational weight** kg (lb) | 3,000 (6,614) | 7,000 (15,432) | 8,000 (17,637) | 10,200 (22,487) | 12,000 (26,455) | 14,000 (30,865) | 16,000 (35,274) | 18,000 (39,683) | 20,000 (44,092) |
| **Drum width** mm (ft) | 1,200 (3.9) | 1,700 (5.6) | 1,700 (5.6) | 2,100 (6.9) | 2,100 (6.9) | 2,100 (6.9) | 2,100 (6.9) | 2,100 (6.9) | 2,100 (6.9) |
| **Static line force** N/cm (lb/in) | 114 (65) | 215 (123) | 226 (129) | 242 (138) | 303 (173) | 373 (213) | 457 (261) | 470 (268) | 500 (286) |
| **Static drum weight** Kg (lb) | 1,510 (3,329) | 4,900 (10,803) | 3,900 (8,598) | 4,850 (10,692) | 6,500 (14,330) | 8,500 (18,739) | 8,500 (18,739) | 9,500 (20,944) | 10,500 (23,149) |

**Options**



Drum Drive System




Pad Foot System

Rhino Engine, Tier 2, Tier 3, Tier 4 Engine, ROPS/FOPS Cab, A/C, Pressurized Water Spray System, Drum Drive System, Pad Foot, Dozer Blade, Water Tank System, Asphalt Wheels, Central Lubrication, and more...








Equipment specifications and images may change without previous notice

# FORKLIFTS

| SPECIFICATIONS | RFL200DT | RFL250DT | RFL300DT | RFL400DT | RFL500DT | RFL700DT | RFL1000DT | RFL1200DT |
|---|---|---|---|---|---|---|---|---|
| **Rated Capacity** kg(lb) | 2,000 (4,409) | 2,500 (5,512) | 3,000 (6,614) | 4,000 (8,818) | 5,000 (11,023) | 7,000 (15,432) | 10,000 (22,046) | 12,000 (26,455) |
| **Power Type** | Diesel | Diesel | Diesel | Diesel | Diesel | Diesel | Diesel | Diesel |
| **Power** kW(hp) | 39 (52.3) | 39 (52.3) | 42 (56.3) | 45 (60.3) | 59 (79.1) | 81(108.6) | 81(108.6) | 97 (130) |
| **Lifting Height** mm (in) | 3,000 (118.1) | 3,000 (118.1) | 3,000 (118.1) | 3,000 (118.1) | 3,000 (118.1) | 3,000 (118.1) | 3,000 (118.1) | 3,000 (118.1) |
| **Turning Radius** mm(in) | 2,450 (96.5) | 2,500 (98.4) | 2,500 (98.4) | 2,720 (107.1) | 3,000 (118.1) | 3,450 (135.8) | 3,900 (153.5) | 4,200 (165.4) |

| SPECIFICATIONS | RFL1500DT | RFL1600DT | RFL2000DT | RFL2500DT | RFL3000DT | RFL3500DT | RFL4500DT |
|---|---|---|---|---|---|---|---|
| **Rated Capacity** kg(lb) | 15,000 (33,069) | 16,000 (35,274) | 20,000 (44,092) | 25,000 (55,116) | 30,000 (66,139) | 35,000 (77,162) | 45,000 (99,208) |
| **Power Type** | Diesel | Diesel | Diesel | Diesel | Diesel | Diesel | Diesel |
| **Power** kW(hp) | 142 (190) | 142 (190) | 160 (215) | 179(240) | 191(256) | 191(256) | 250 (335) |
| **Lifting Height** mm (in) | 3,500 (137.8) | 3,500 (137.8) | 3,500 (137.8) | 3,500 (137.8) | 3,500 (137.8) | 3,500 (137.8) | 4,000 (157.5) |
| **Turning Radius** mm(in) | 5,800 (228.3) | 5,800 (228.3) | 6,250 (246.1) | 6,700 (263.8) | 7,260 (285.8) | 7,260 (285.8) | 8,600 (338.6) |

| SPECIFICATIONS | RFL200LPG | RFL300LPG | RFL350LPG |
|---|---|---|---|
| **Rated Capacity** kg(lb) | 2,000 (4,409) | 3,000 (6,614) | 3,500 (7,716) |
| **Power Type** | Gasoline/LPG | Gasoline/LPG | Gasoline/LPG |
| **Power** kW(hp) | 41 (55.0) | 41 (55.0) | 41 (55.0) |
| **Lifting Height** mm (in) | 3,000 (118.1) | 3,000 (118.1) | 3,000 (118.1) |
| **Turning Radius** mm(in) | 2,400 (94.5) | 2,550 (100.4) | 2,575 (101.4) |

| SPECIFICATIONS | RFL200E | RFL300E | RFL350E |
|---|---|---|---|
| **Rated Capacity** kg(lb) | 2,000 (4,409) | 3,000 (6,614) | 3,500 (7,716) |
| **Power Type** | Battery / Electric | Battery / Electric | Battery / Electric |
| **Load center** mm (in) | 500 (19.7) | 500 (19.7) | 500 (19.7) |
| **Lifting Height** mm (in) | 3,000 (118.1) | 3,000 (118.1) | 3,000 (118.1) |
| **Turning Radius** mm(in) | 2,200 (86.6) | 2,350 (92.5) | 2,400 (94.5) |

# REACH STACKER



| SPECIFICATIONS | RRS4500 |
|---|---|
| **Rated Capacity** kg(lb) | 45,000 (99,208) |
| **Power Type** | Diesel |
| **Lifting Speed (unload/loaded)** mm/s (in/s) | 104/60 (4/2) |
| **Lifting Height** mm (in) | 15,100 (594) |
| **Turning Radius** mm(in) | 8,200 (323) |




**Options**

**Options:** Tier 2, Tier 3, Tier 4 Engine, Different wheel/tire types, power-line, side shifter, torque converter, temperature warning, A wide range of different platforms, front and fork attachments are available. And more...





Equipment specifications and images may change without previous notice

# LIGHT TOWERS

| SPECIFICATIONS | RLT4000M | RLT4000H | RLT4X150 Solar |
|---|---|---|---|
| Number & Power of Lights | 4x1000W | 4x1000W | 4x150W |
| Mast Height(Fully Extended) m (ft) | 7.5(24.6) | 9(29.5) | 9(29.5) |
| Mast Lifting & Extension | Manual Operation | Hydraulic | Hydraulic |
| Fuel Tank Capacity L (gal) | 100(26,4) | 75(19.8) | N/A |
| Net Weight kg (lb) | 740(1,631) | 1,148(2,531) | 1,950(4,299) |




**Options**



Standard Bulb



LED Lamp

Rhino Equipment offers the perfect lighting solutions to tackle your applications. Trusted power generator packages, exceptional lamp performance, and flexible modular designs allow you to choose the model that best supports: construction sites, outdoor events, and industrial settings Available with tier 2, tier 3, tier 4 engine and more...




# ATTACHMENTS



**Pallet forks**



**Rock wheels**



**Buckets**



**Brooms**



**Augers**



**Skid hoe**



**Grapples**



**Trench fillers**

... and much more

**CONTACT A DEALER NEAR YOU**





Equipment specifications and images may change without previous notice


# TOWER CRANES

| SPECIFICATIONS | RTC-2325 | RTC-4708 | RTC-4807 |
|---|---|---|---|
| **Reach** m (ft) | 25 (82) | 47 (154) | 48 (157) |
| **Capacity** tons@mts (lb@ft) | 0.8@25-2@11.7 (1,764@82-4,000@38.4) | 0.8@47 - 4@12.3 (1,764@154-8,000@40.4) | 0.71@48 - 4@10.7 (1,565@157.5-8,000@35.1) |
| **Max. capacity** tons (lb) | 2 (4,000) | 4 (8,000) | 4 (8,000) |
| **Standard height** mts(ft) | 23 (75.5) | 28.3 (92.8) | 29.7 (97.4) |
| **Max. height** m (ft) | 35 (114.8) | 120 (393.7) | 120 (393.7) |

| SPECIFICATIONS | RTC5013 | RTC-5512 | RTC-6014 |
|---|---|---|---|
| **Reach** mts(ft) | 50 (164) | 55 (180) | 60 (196.9) |
| **Capacity** tons@mts(lb@ft) | 1.3@50 - 6@13.7 (2,866@164-12,000@45) | 1.2@55 - 8@11.2 (2,646@180.4-16,000@37) | 1.4@60 - 8@15 (3,087@197-16,000@49) |
| **Max. capacity** tons(lb) | 6 (12,000) | 8 (16,000) | 8 (16,000) |
| **Standard height** mts(ft) | 40 (131.2) | 46 (150.9) | 46 (151.6) |
| **Max. height** mts(ft) | 140 (459.3) | 150 (492.1) | 161 (528.2) |

| SPECIFICATIONS | RTC-6014B | RTC-6516 | RTCE-5012T |
|---|---|---|---|
| **Reach** mts (ft) | 60 (197) | 65 (213) | N/A |
| **Capacity** tons@mts(lb@ft) | 1.4@60 - 10@11.7 (3,087@197-20,000@38) | 1.6@65 - 10@15 (3,527@213-20,000@49) | 2 (4,000) |
| **Max. capacity** tons (lb) | 10 (20,000) | 10 (20,000) | 2 (4,000) |
| **Standard height** mts (ft) | 46.2 (151.6) | 46.2 (151.6) | 50 (164.0) |
| **Max. height** mts (ft) | 200 (656.2) | 200 (656.2) | 300 (984.3) |

**Options**









Concrete Buckets, Pallet forks, Height Modules, Platforms, Grippers, Dumping bins, A/C, and more...

# HAMMERS

| SPECIFICATIONS | 254SK | 47SK-47BE | 714BE | 1826EX | 2735EX | 3255EX |
|---|---|---|---|---|---|---|
| **Equipment class** tons (lb) | 2.5-4.5 (5,512-9,921) | 4.0-7.0 (8,819-15,432) | 7.0-14 (15,432-30,865) | 18-26 (39,683-57,320) | 27-35 (59,525-77,162) | 32-55 (70,547-121,254) |
| **Operational weight** Kg (lb) | 150 (331) | 275 (606) | 500 (1,102) | 1,740 (3,836) | 2,420 (5,335) | 3,020 (6,658) |
| **Height** mm (ft) | 1,342 (4.4) | 1,600 (5.2) | 2,101 (6.9) | 2,327 (7.6) | 2,500 (8.2) | 2,740 (9.0) |
| **Operating pressure** bar (psi) | 90-120 (1,305-1,740) | 95-130 (1,378-1,885) | 130-150 (1,885-2,176) | 160-180 (2,321-2,611) | 160-180 (2,321-2,611) | 160-180 (2,321-2,611) |
| **Impact range** bpm | 600-1,100 | 500-900 | 400-800 | 400-500 | 300-450 | 250-400 |
| **Hose diameter** mm (in) | 12.7 (0.5) | 12.7 (0.5) | 19.05 (0.75) | 25.4 (1.0) | 25.4 (1.0) | 31.7 (1.25) |

**Options**


Tools


Underwater Kit

Moil Tool, Chisel Tool, Blunt Tool, Asphalt Chisel, Wide Chisel, Underwater Kit, and more...








Equipment specifications and images may change without previous notice

# GENERATORS






## 50 HZ

| Model | Max. Power (kw) |
|---|---|
| RG25-1 | 26 |
| RG40-1 | 40 |
| RG60-1 | 55 |
| RG100-1 | 100 |
| RG115-1 | 110 |
| RG140-1 | 132 |
| RG180-1 | 180 |
| RG220-1 | 207 |
| RG250-1 | 243 |
| RG260-1 | 254 |
| RG265-1 | 257 |
| RG300-1 | 291 |
| RG312-1 | 321 |
| RG320-1 | 310 |
| RG350-1 | 343 |
| RG365-1 | 351 |
| RG375-1 | 407 |
| RG400-1 | 369 |
| RG450-1 | 448 |
| RG500-1 | 504 |
| RG580-1 | 575 |
| RG585-1 | 555 |
| RG625-1 | 610 |
| RG780-1 | 731 |
| RG800-1 | 789 |
| RG900-1 | 895 |
| RG1000-1 | 970 |
| RG1125-1 | 1089 |
| RG1250-1 | 1227 |
| RG1400-1 | 1429 |
| RG1900-1 | 1790 |
| RG2000-1 | 1915 |

## 60 HZ

| Model | Max. Power (kw) |
|---|---|
| RG25-2 | 30 |
| RG38-2 | 45 |
| RG60-2 | 65 |
| RG100-2 | 115 |
| RG120-2 | 132 |
| RG125-2 | 140 |
| RG175-2 | 207 |
| RG200-2 | 230 |
| RG250-2 | 265 |
| RG280-2 | 317 |
| RG320-2 | 347 |
| RG350-2 | 399 |
| RG385-2 | 448 |
| RG460-2 | 511 |
| RG515-2 | 563 |
| RG550-2 | 605 |
| RG600-2 | 658 |
| RG700-2 | 747 |
| RG825-2 | 895 |
| RG935-2 | 1007 |
| RG1035-2 | 1112 |
| RG1140-2 | 1220 |
| RG1265-2 | 1380 |
| RG2000-2 | 2500 |

### Single Phase

| | |
|---|---|
| RG25-2SC | 30 |
| RG38-2SC | 45 |
| RG55-2SC | 65 |

### Rhino Engine

| | |
|---|---|
| RG16-R | 20 |
| RG20-R | 25 |

## 50 HZ

| Model | Max. Power (kw) |
|---|---|
| RG9-1 | 9.3 |
| RG13-1 | 13.3 |
| RG20-1 | 20.3 |
| RG27-1 | 27 |
| RG30-1 | 30.4 |
| RG45-1 | 45.6 |
| RG60-1 | 59.3 |
| RG65-1 | 64.3 |
| RG80-1 | 79.1 |
| RG100-1 | 99.5 |
| RG136-1 | 133.5 |
| RG150-1 | 143 |
| RG185-1 | 175.5 |
| RG200-1 | 199 |
| RG230-1 | 217 |
| RG250-1 | 239 |
| RG350-1 | 349 |
| RG400-1 | 392 |
| RG450-1 | 435 |
| RG500-1 | 478 |
| RG600-1 | 574 |
| RG650-1 | 609 |
| RG730-1 | 685 |
| RG800-1 | 760 |
| RG850-1 | 787 |
| RG905-1 | 839 |
| RG1022-1 | 947 |
| RG1253-1 | 1166 |
| RG1364-1 | 1263 |
| RG1505-1 | 1395 |
| RG1705-1 | 1579 |
| RG1752-1 | 1607 |
| RG1844-1 | 1690 |
| RG2058-1 | 1886 |

## 60 HZ

| Model | Max. Power (kw) |
|---|---|
| RG10-2 | 11.4 |
| RG14-2 | 15.9 |
| RG20-2 | 23.9 |
| RG28-2 | 32.6 |
| RG30-2 | 35.4 |
| RG50-2 | 53.9 |
| RG60-2 | 67.5 |
| RG65-2 | 75.5 |
| RG80-2 | 90.2 |
| RG100-2 | 111 |
| RG135-2 | 147 |
| RG140-2 | 155.3 |
| RG150-2 | 163.4 |
| RG180-2 | 196.3 |
| RG200-2 | 220 |
| RG215-2 | 235 |
| RG350-2 | 381 |
| RG400-2 | 435 |
| RG450-2 | 490 |
| RG500-2 | 543 |
| RG550-2 | 598 |
| RG600-2 | 652 |
| RG675-2 | 715 |
| RG750-2 | 795 |
| RG780-2 | 821 |
| RG880-2 | 924 |
| RG1100-2 | 1166 |
| RG1200-2 | 1263 |
| RG1325-2 | 1395 |
| RG1500-2 | 1875 |

### Options


Digital Control Panel


Automatic Transfer Switch



Composed of Cummins, Perkins or Rhino diesel engine, Tier 2, Tier 3, Tier 4 Engine, Stamford, Marathon or Rhino alternator, Key start panel control system as standard, digital auto-start panel, 8-hour operation base tank, Open type or silent type and more...



Equipment specifications and images may change without previous notice

# FACE DRILLS



| SPECIFICATIONS | RFD1X-2045 | RFD1X-2050 | RFD1X-2060 | RFD1X-2565 | RFD1X-3570 | RFD1X-3068 | RFD1X-4010 |
|---|---|---|---|---|---|---|---|
| **Engine** | RFD50T/4TNV94L | RFD65T/B3.3T | RFD67T/B3.3T | RFD67T/B3.3T | RFD97T/QSB4.5 | RFD56T/4TNV98T | RFD97T/BF4M |
| **Electric Engine** kW (hp) | 55 (74) | 55 (74) | 55 (74) | 55 (74) | 2x55 (74) | 55 (74) | 75 (101) |
| **Drilling Power** kW (hp) | 18 (24) | 18 (24) | 24 (32) | 24 (32) | 25 (33) | 18 (24) | 18 (24) |
| **Diesel Engine** kW (hp) | 49 (66) | 65 (87) | 67 (90) | 67 (90) | 97 (130) | 56 (75) | 97 (130) |
| **Min. Coverage Area** m | 2.0 x 2.0 | 2.3 x 2.3 | 5.3 x 5.7 | 2.5 x 2.5 | 3.0 x 3.0 | 3.0 x 3.0 | 4.5 x 4.5 |
| **Max. Coverage Area** m | 5.0 x 4.5 | 5.5 x 4.5 | 6.5 x 6.1 | 6.5 x 6.0 | 7.0 x 6.5 | 6.8 x 6.7 | 10.0 x 13.0 |



| SPECIFICATIONS | RFD1X-4511 | RFD2X-4070 | RFD2X-4590 | RFD2X-5012 | RFD3X-6017 | RFD2XD-5015 |
|---|---|---|---|---|---|---|
| **Engine** | RFD119T/ BF4M1013FC | RFD97T/ WP4G120E310 | RFD164T/QSB5.9 | RFD208T/QSB6.7 | RFD209T/6CTA8.3 | RFD119T/BF4M |
| **Electric Engine** kW (hp) | 95 (127) | 2x55 (74) | 110 (148) | 150 (201) | 3x55 (74) | 2x55 (74) |
| **Drilling Power** kW (hp) | 22 (30) | 18 (24) | 18 (24) | 22 (30) | 18 (24) | 22 (30) |
| **Diesel Engine** kW (hp) | 119 (160) | 97 (130) | 164 (220) | 208 (280) | 209 (280) | 119 (160) |
| **Min. Coverage Area** m | 4.5 x 4.5 | 4.0 x 4.0 | 4.5 x 4.5 | 5.0 x 5.0 | 6.9 x 5.5 | 5.0 x 5.0 |
| **Max. Coverage Area** m | 11.9 x 16.0 | 7.0 x 6.7 | 13.8 x 9.7 | 12.0 x 8.6 | 17.5 x 13.0 | 15.9 x 12.0 |

## UNDERGROUND WHEEL DOZERS



| SPECIFICATIONS | RWD132M | RWD235M | RWD315M |
|---|---|---|---|
| **Engine** | 6BTA5.9 | 6LTAA8.9-C295 | M11-C |
| **Engine Power** kW (hp) | 132 (177) | 220 (295) | 250 (335) |
| **Operating Weight** kg (lb) | 13,000 (28,660) | 21,000 (46,297) | 34,500 (76,059) |
| **Blade Capacity** m3 (cu. yd) | 3.0 (3.9) | 4.5 (5.9) | 5.3 (6.9) |
| **Overall Height** mm (ft) | 2,800 (9.19) | 2,800 (9.19) | 2,800 (9.19) |

## TRUCKS



| SPECIFICATIONS | RMU-T20 | RMU-T30 | RMU-T45 |
|---|---|---|---|
| **Engine** | RMUT256T/ TAD853VE | RMUT329T/ TAD1352VE | RTM630A/ TAD1651VE |
| **Engine Power** kW (hp) | 256 (343) | 329 (441) | 469 (629) |
| **Operating Weight** kg (lb) | 22,600 (49,824) | 31,000 (68,343) | 40,100 (88,405) |
| **Payload Capacity** kg (lb) | 20,000 (44,093) | 30,000 (66, 139) | 45,000 (99,208) |
| **Hopper Capacity** m3 (cu. yd) | 10.0 (13.1) | 15.0 (19.6) | 21.5 (28.1) |

# UNDERGROUND WHEEL LOADERS



| SPECIFICATIONS | RMWL-308E | RMWL-103 | RMWL-305 | RMWL-400 | RMWL-500 | RMWL-600 |
|---|---|---|---|---|---|---|
| **Engine** | RMWL700E | RMWL92.5T/ TAD850VE | RMWL179T/ TAD850VE | RHINO | RMWL262T/TAD853 | RMWL 290T/ TAD1350VE |
| **Engine Power** kW (hp) | 340 (456) | 93 (125) | 179 (240) | 235 (315) | 252 (338) | 290 (389) |
| **Payload Capacity** kg (lb) | 7,000 (15,432) | 2,000 (4,409) | 7,000 (15,432) | 9,500 (20,943) | 10,000 (22,046) | 15,000 (33,069) |
| **Bucket Capacity** m3 (cu. yd) | 3.5 (4.6) | 1.0 (1.3) | 3.5 (4.6) | 4.0 (5.2) | 5.0 (6.5) | 6.0 (7.8) |
| **Operating Weight** kg (lb) | 22,000 (48,502) | 7,200 (15,873) | 19,250 (42,439) | 28,500 (62,832) | 28,500 (62,832) | 38,000 (83,776) |
| **Breakout Force** kN | 175.9 | 117.9 | 175.9 | 188.3 | 188.3 | 228.4 |



Equipment specifications and images may change without previous notice

# ROCK BOLTING RIGS








| SPECIFICATIONS | RBR-125 | RBR-135 | RBR-168 | RBR-154 | RBR-156 | RBR-210 |
|---|---|---|---|---|---|---|
| **Engine** | RBR64T/4BTA 3.9 | RBR60T/QSF2.8 | RBR134T/QSB4.5 | RBR67T/QSF3.8 | RBR71T/QSF3.8 | RBR100T/QSF3.8 |
| **Engine Power** kW (hp) | 64 (86) | 60 (80) | 134 (180) | 80 (107) | 85 (114) | 91 (122) |
| **Drill Power** kW (hp) | 15 (21) | 8 (11) | 8 (11) | 27 (36) | 32 (43) | 40 (54) |
| **Operating Weight** kg (lb) | 12,965 (28,582) | 13,500 (29,762) | 16,800 (37,037) | 15,400 (33,951) | 15,600 (34,392) | 21,000 (46,297) |
| **Min. Coverage Area** m | 2.8 x 2.8 | 3.5 x 3.0 | 4.5 x 4.5 | 7.1 x 6.7 | 8.0 x 7.6 | 11.4 x 8.7 |
| **Max. Coverage Area** m | 5.1 x 5.6 | 6.0 x 6.0 | 6.3 x 7.6 | 10.0 x 9.7 | 13.0 x 10.5 | 16.0 x 12.5 |

## UNDERGROUND SCALERS




| SPECIFICATIONS | RUS600 | RUS800 |
|---|---|---|
| **Engine** | RUS67/4TNV98 | RUS65/4TNV98CT |
| **Engine Power** kW (hp) | 67 (90) | 70 (94) |
| **Vertical Reach** mm (ft) | 6,022 (19.75) | 8,035 (26.36) |
| **Operating Weight** kg (lb) | 9,500 (20,943) | 10,500 (23,148) |
| **Max. Scaling Height** mm (ft) | 6,035 (19.79) | 8,040 (26.37) |
| **Max. Horizontal Reach** mm (ft) | 5,248 (17.21) | 5,235 (17.17) |

## SURFACE DRILL RIGS



| SPECIFICATIONS | RSD150 |
|---|---|
| **Engine** | RSD242/QSB6.7 |
| **Engine Power** kW (hp) | 268 (359) |
| **Drill Power** kW (hp) | 20 (27) |
| **Drilling Depth** mm (ft) | 28,000 (91.86) |
| **Operating Weight** kg (lb) | 15,000 (33,069) |
| **Max. Total Height Vertical Feed** mm (ft) | 7.177 (23.54) |

## TRACKS JAW CRUSHER MOBILE STATION



| SPECIFICATIONS | RCRUSH400 |
|---|---|
| **Engine** | Cummins |
| **Production Capacity** t/h | 300 – 400 |
| **Crusher Weight** tons (lb) | 29 (58,000) |
| **Bucket Capacity** m3 (cu.yd) | 3.2 (4.2) |
| **Feed Height** mm (ft) | 4,900 (16.07) |
| **Engine Power** kW (hp) | 328 (440) |

## CRAWLER-TYPE MOBILE SCREENING STATION



| SPECIFICATIONS | RHSCR-2040 |
|---|---|
| **Engine** | 6CTA8.3 |
| **Production Capacity** t/h | 200 – 400 |
| **Operating Weight** tons (lb) | 68 (149,914) |
| **Mesh Size** mm | 5 – 100 |
| **Feed Height** mm (ft) | 4,600 (15.09) |
| **Engine Power** kW (hp) | 120 (161) |

## WOOD CHIPPERS





| SPECIFICATIONS | RCW1015T | RCW1520T | RCW2030T |
|---|---|---|---|
| **Production Capacity** t/h | 10 – 15 | 15 – 20 | 20 – 30 |
| **Engine Power** kW (hp) | 160 (215) | 200 (268) | 358 (480) |
| **Chain Plate Length** mm (ft) | 4,000 (13.12) | 4,500 (14.76) | 4,000 (13.12) |
| **Chain Plate Width** mm (ft) | 1,300 (4.26) | 1,400 (4.59) | 1,300 (4.26) |
| **Feeding Inlet Size** mm | 1.300 × 600 | 1.400 × 600 | 1.300 × 560 |

## FORESTRY MULCHER




| SPECIFICATIONS | RWCW-180 | RWCW-190 |
|---|---|---|
| **Engine Power** kW (hp) | 234 (315) | 413/416 (554/558) |
| **Cutting Width** mm (ft) | 2,350 (7.70) | 3,100 (10.17) |
| **Work Speed** km/h (mph) | 0-3.0 (0-1.86) | 0-3.0 (0-1.86) |
| **Head Power** kW (hp) | 330 (443) | 360 (483) |
| **Operating Weight** kg (lb) | 18,000 (39,683) | 19,000 (41,887) |





Equipment specifications and images may change without previous notice

# TELEHANDLERS






| SPECIFICATIONS | RTH23-3 | RTH23-3.5 | RTH35-3.5 | RTH23-4 |
|---|---|---|---|---|
| **Engine** | YN38GBZ | YN38GBZ | YCD4M22T-105 | YCD4J22T-115 |
| **Engine Power** kW (hp) | 76 (103) | 76 (103) | 77.3 (103) | 55 (74) |
| **Lift Height** mm (ft) | 7,000 (22.97) | 7,000 (22.97) | 10,600 (34.78) | 7,000 (22.97) |
| **Rated Capacity** kg (lb) | 3,000 (6,610) | 3,500 (7,720) | 3,500 (7,720) | 4,000 (8,820) |
| **Max. Reach** m (ft) | 3.2 (10.5) | 3.2 (10.5) | 5.7 (18.7) | 3.2 (10.5) |
| **Tires** | 16/70-20 (Pneumatic) | 16/70-20 (Pneumatic) | 16/70-20 (Pneumatic) | 400/70-24 (Tubeless) |






| SPECIFICATIONS | RTH32-4 | RTH45-4 | RTH57-4 | RTH32-5 |
|---|---|---|---|---|
| **Engine** | YCD4J22T-115 | YCD4J22T-115 | YCD4J22T-115 | YCD4J22T-125 |
| **Engine Power** kW (hp) | 85 (114) | 85 (114) | 85 (114) | 91 (122) |
| **Lift Height** mm (ft) | 9,800 (32.15) | 13,800 (45.28) | 17,600 (57.74) | 9,800 (32.15) |
| **Rated Capacity** kg (lb) | 4,000 (8,820) | 4,000 (8,820) | 4,000 (8,820) | 5,000 (11,023) |
| **Max. Reach** m (ft) | 6.1 (20) | 7.0 (23) | 12.0 (39.4) | 5.0 (16.4) |
| **Tires** | 400/70-24 (Tubeless) | 440/80-24 (Tubeless) | 440/80-24 (Tubeless) | 16/70-24 (Semi-Solid) |





| SPECIFICATIONS | RTH45-5 | RTH57-5 | RTH57-6 |
|---|---|---|---|
| **Engine** | YCD4J22T-125 | YCD4J22T-125 | 4BT3.9-C125 |
| **Engine Power** kW (hp) | 91 (122) | 91 (122) | 110 (150) |
| **Lift Height** mm (ft) | 13,800 (45.28) | 17,550 (57.58) | 17,600 (57.74) |
| **Rated Capacity** kg (lb) | 5,000 (11,023) | 5,000 (11,023) | 6,000 (13,228) |
| **Max. Reach** m (ft) | 8.0 (26.3) | 11.2 (36.8) | 12.0 (39.4) |
| **Tires** | 440/80-24 (Tubeless) | 440/80-24 (Tubeless) | 17.5-25 (Tubeless) |



Equipment specifications and images may change without previous notice

RHINO
EQUIPMENT

BUILT
TO PERFORM

# GLOBAL SOLUTIONS
# LOCAL IMPACT

At Rhino Equipment, we provide reliable machinery, innovative solutions and dedicated support to help our customers build, move and grow a stronger future.




QUALITY MACHINES | TRUSTED PARTNERS | EXPERT SUPPORT | A STRONGER TOMORROW



PRESENCE IN:

**+80** COUNTRIES

**33** PRODUCT LINES

**+160** MODELS

**+25** ATTACHMENTS

PEOPLE. PROJECTS. PROGRESS.

I MAKE AMERICA

AMERICAN STRENGTH. GLOBAL IMPACT.

www.rhinoequipment.us
info@rhinoequipment.us
1-855-744-6650
Florida, USA

FOLLOW US

VISIT OUR WEBSITE